

HALE

TRAILER

BRAKE & WHEEL



A019321-A019332



VIN: 560601-560612

Flatbed

SALES | RENTALS | PARTS | SERVICE

Allentown, PA:	800-383-8894	Jacksonville, FL:	800-828-3055
Baltimore, MD:	888-601-7500	Little Rock, AR:	833-424-8944
Boston, MA:	800-854-5310	Portland, ME:	800-325-4253
Concord, NC:	800-438-2250	Richmond, VA:	866-839-3495
Delmar, DE:	866-486-1400	Scranton, PA:	800-569-1400
Des Moines, IA:	888-673-5011	Springfield, MA:	800-854-5306
Elkton, MD:	800-544-7127	Voorhees, NJ:	866-315-0235

HaleTrailer.com | @haletrailer     

800-232-6535 *FINANCING AVAILABLE

GVWR

GVWR:	Trailer to meet 68,000 Pound GVWR
VIN PLATE:	US - VIN Plate to Read in English (Standard)
Product Type:	HT Combo Duralite

GEOMETRY

* Length - Exterior:	45'-0"
Width - Exterior:	102.36"
Fifth Wheel Height:	47"
King Pin Location:	36"
Landing Gear Location:	102" from King Pin (+ 1"/-1/4")
Duralite Front Deck Height:	59-3/4" (± 1/2")
Duralite Rear Deck Height:	54-5/16" (± 1/2")

TIRES & WHEELS

Tire Furnished:	Factory Furnished
* Tire Manufacturer:	Hankook TL21(G), Low Rolling Resistance Tire
* Tire Size:	11R22.5
Wheel Furnish:	Factory Furnished
Wheel Material:	All Steel Wheel
Wheel Manufacturer:	HT Standard (TCC 361)
Wheel Size:	8.25 x 22.5, 5-Hand Hole (Steel, Inner & Outer)
Wheel Finish for Steel:	Powder Coated White Steel Disc
Tire Stem Valve Position:	Dual Wheel Steel / Aluminum / Combo (STD 180°outboard & straight inboard)
Wheel Finish for Aluminum:	None (Due to All Steel Wheel Application)
* Valve Stem & Cap:	Myers TR-572-F19 Valve stem

UPPER COUPLER

Approach Plate:	1/4" Thick 80,000 PSI Yield (Duralite)
King Pin & Manufacturer:	Standard (Jost) AAR Cruciform King Pin

DURALITE OPTIONS

* Cross Members:	4" Steel I-Beams (80,000 PSI) : 12" C/L
* Cross Members - Options:	4"X7.7lb Heavy Duty Cross Member For Princeton Forklift
Main Web:	3/16" Thick. Welded One Piece Type (100 KSI Domex)
Top Flange:	3/8" Thick, 100 KSI Domex, 5" Wide One Piece Type
Bottom Flange:	3/8" Thick, 100 KSI Domex, 5" Wide One Piece Type
Holes on Main web:	Diamond Shape
Gusset Type:	Pipe Type
Gusset Specification:	(3) on Each Side (HT STD)
Front Sill:	HT Standard Aluminum Extrusion
* Front Stake Pockets:	4 EA for Steel Bulkhead Installation
* Bulkhead:	Steel Removable Type - Hot Dip Galvanized
* Bulkhead Specification:	60" High x No Wrap
* Rear Sill:	Steel Sill For Forklift Installation
* Side Rail:	HT Integrated Aluminum High Impact Side Rail
* Winch Rail:	Aluminum Winch Rail for Sliding Winches OR Combination (SLD+ FIX) Winches
Winches:	Sliding Steel Winches, (12) on Each Side
Sliding Winch Stoppers:	Stoppers at Front and Rear (Flatbed STD for Sliding Winches)

Fastener Options: Standard Fasteners
** Forklift: Install HT Forklift Mounting Kit (Accommodates Princeton PB50 and Moffett M50) w/
Adjustable Wheels Stops

FLOOR

Duralite Floor Specification: 1-1/8" Aluminum with 4 Apitong Nailer Strips (Combo STD)
Floor Screws: HT Duralite Standard (2 Screws Per Board on I-beams)

FRONT

Gladhands: Phillips Qwik-E with Filters Control Line Only. Overlaid Straight Type
Front Receptacle(7-Way): HT Duralite Standard (Phillips 7-Way Integrated with Main Harness)
Gladhand/7-Way Location: (Interior Harness Routing) Overlaid on Lower Centerline Front

REAR

* Rear Underride Guard: 4" Tube Weld on Assembly w/ Bolt on Perforated(Pooched) Foldable Horizontal
* Dock Bumper: Do Not Apply Bumper per Customer Request

LANDING GEAR

L/Gear Spec.: Jost 420
L/Gear Shoes: 10" X 10" X 4" Sand Shoe (HT Duralite STD)
L/Gear Crank Handle: Roadside
L/Gear Cross Brace Design: HT Standard Cross Brace attachment Design

RUNNING GEAR

Bogie Type: Sliding Tandem(2) Axle Bogie
Axle Spacing: 49" Axle Spacing
Axle ABS System: Tandem Axle w/2S1M ABS System
Duralite Bogie & Axle Location: HT Sliding Axle STD Location (CA Compliant; KP to Rear Most Axle 40#)
Susp. Manufacturer: Hendrickson
Suspension Capacity: Standard Duty
Duralite Susp. Specification: Hendrickson AAZNT46K Air Ride (Tandem Sliding)
Surelok (Anti-Dock): No Surelok (No Anti-Dock)
* Susp. Dump Valve: Auto Dump Valve
Locking Pin Mechanism: Air-Assist Pin Puller or Quik Draw
Type of Susp Spring: Air Bag
Spring Specification: Air Bag
Axle Supplier: Hendrickson
Axle-General Spec.: Axle - Tandem (2) Axle included in Suspension (For 2S1M or 2S2M System)
Axle-Track Length: 77-1/2"
Axle-Spindle Type: Parallel Spindle
Brake Lining Size: 16.5" X 7"
Brake Lining Spec.: Hendrickson Extended Service (Abex-3030-197)
Brake Control System: 2S/1M Wabco ABS
Spring Brake Control: Sealco 110500 Springbrake Priority
Drain Valve & Other: Parker DC604-4 Drain Cock
Slack Adjuster Spec.: Gunitite Auto-5.5", 28 Spline
Brake Chamber Spec.: TSE 3030 Tamper Resist (HT standard)
Stroke Length: MFG's Standard Stroke Length
Hub Specification: HT Standard (KIC) 10 Stud Hub Piloted Outboard Iron Hub
Drum Specification: HT Standard (KIC) Cast Drum
Hub/Drum-Opt(Nut&Other): Standard
Bearing Specification: Stemco
Lubrication Spec.: Chev Delo Gear EP5 80-90 oil
Wheel Seals Spec.: Stemco Platinum Performance Plus, Discover Seals, Sentinel Hub Cap, Pro-Torq Nut

ELECTRICAL

Harness-General Spec.: Molded Color Code Phillips Harness (Sta-Dry)
Harness-Special Feature: Manufacturer's Standard Feature
ID/Marker Light Spec: (3) Trucklite 30 Series ID Light / Trucklite 33 Series Marker Light

S/T/Tail Light-Detail Spec: (4) Trucklite 44326R LED (Super 44 Black) Flange Mounted w/ Stainless Steel Rivets
Main Mid-Turn Light-Detail Spec: (2) Trucklite 60420Y LED Flange Mounted w/ Stainless Steel Ring
* ABS Light Detail Spec: (1) Trucklite 33275Y LED PC Rated w/ Grommet 33725 w/ anti-theft hardware
License Light: (1) Trucklite 33210C LED with 33815 Anti-Theft Flange

MARKING/DECALS

Decal Package: Factory Furnished Hyundai Information & Regulatory Decal Package with FMCSA Specified in Notes
Conspicuity Markings: Hyundai Standard Conspicuity with Logo Applied to Side Bottom Rail
License Plate: Temporary For Delivery. Fasten On HDG Mounting Plate
License Plate Brk't Install: HT DuraLite Standard Location
Furnish Document Holder: Factory Furnished
Document Holder Detail Spec: (1) Phillips 16-802
Document Holder/Manifest Loc.: Overlaid on Lower R/S Front

PAINTE/FINISH

Axle & Components Finish: Black Undercoating
Susp. Sub-Frame Finish: Black Undercoating
L/Gear(K-Bracing) Finish: Hot Dip Galvanized
L/Gear(Upper Leg) Finish: Black Undercoating
Rear Underride-Finish & Spec.: Hot Dip Galvanized & Bolted Horizontal Member
Duralite Product Finish: Hot Dip Galvanized

MISCELLANEOUS

Mudflap Provider: Factory Furnished Mudflaps
Mudflap Specification: 24"x24" White Plain Plastic with Hyundai Logo 3/8# thick with Anti-spray ribs
Mudflap Mounting Method/Install: STD Location w/ H.D Washer Retainer

DISCLAIMER

Specifications are believed to be correct, but may contain errors and/or omissions. Photographs are the representative of the subject equipment but may not be identical.
Equipment availability, prices and specifications are subject to change without notice.