

HALE TRAILER BRAKE & WHEEL



A019405-A019406
VIN: 870302-870303

SALES | RENTALS | PARTS | SERVICE

Allentown, PA:	800-383-8894	Jacksonville, FL:	800-828-3055
Baltimore, MD:	888-601-7500	Little Rock, AR:	833-424-8944
Boston, MA:	800-854-5310	Portland, ME:	800-325-4253
Concord, NC:	800-438-2250	Richmond, VA:	866-839-3495
Delmar, DE:	866-486-1400	Scranton, PA:	800-569-1400
Des Moines, IA:	888-673-5011	Springfield, MA:	800-854-5306
Elkton, MD:	800-544-7127	Voorhees, NJ:	866-315-0235

HaleTrailer.com | @haletrailer

800-232-6535 *FINANCING AVAILABLE

Fifth wheel height : 50	Schnable <input checked="" type="checkbox"/> Base and Mid
Gooseneck; <input checked="" type="checkbox"/> 1 <input checked="" type="checkbox"/> 2 cylinders	Overall length: 54' 6"(without extention)
<input checked="" type="checkbox"/> Powered with 13 HP Honda power pack front <input checked="" type="checkbox"/> Long front coupler <input checked="" type="checkbox"/> 54" gooseneck insert	Width outside tire to tire : 144"
Tower Attachment: <input checked="" type="checkbox"/> Hooks at bottom with hydraulic top	Axles : <input checked="" type="checkbox"/> 3+ 3
Hydraulic Coupling: <input checked="" type="checkbox"/> 4 port quick manifold	Suspension : <input checked="" type="checkbox"/> Turner HT-250
King Pin Location <input checked="" type="checkbox"/> Bolt on <input checked="" type="checkbox"/> Other 22	<input checked="" type="checkbox"/> Scale-O-Matic <input checked="" type="checkbox"/> Dump valve <input checked="" type="checkbox"/> Ball valve on air bag <input checked="" type="checkbox"/> (2) control box
Coupler : Plate <input checked="" type="checkbox"/> Other :1/2"	Axle location: 60-60-14'1"-60-60
Frame : 100,000 PSI Steel	Steering axles : <input checked="" type="checkbox"/> Yes, Qty: 3
X-Members: Fabricated	Steering mecanism : <input checked="" type="checkbox"/> Force steer with front turn table
Front fenders : <input checked="" type="checkbox"/> No	Steering control : <input checked="" type="checkbox"/> Automatic <input checked="" type="checkbox"/> Manual <input checked="" type="checkbox"/> 13 HP Honda power pack
Rear fenders: <input checked="" type="checkbox"/> Plastic	Axles : <input checked="" type="checkbox"/> D-22
D-Rings: <input checked="" type="checkbox"/> Yes Location: To lift the dolly	Brake type: <input checked="" type="checkbox"/> Drum brakes
Bumper : <input checked="" type="checkbox"/> Long	Seals : Stemco Guardian HP Bearings : Stemco
Mud flaps : <input checked="" type="checkbox"/> Témisko Location : At each axle	Brake chambers: <input checked="" type="checkbox"/> TSE 30
Lights : <input checked="" type="checkbox"/> Truck-lite round type (2/s) <input checked="" type="checkbox"/> Strobe light <input checked="" type="checkbox"/> Extensible lights <input checked="" type="checkbox"/> Oversized sign Extra 7 way plug at rear for beacon light	Automatic Slack adjuster : <input checked="" type="checkbox"/> Haldex
Tool box : <input checked="" type="checkbox"/> Alum. Checkered plate	Brake valve : Rockwell Wabco
	Hubs : <input checked="" type="checkbox"/> 8 studs steel piloted hubs
	Drum : <input checked="" type="checkbox"/> Standard
	Rims : Qty : 24 <input checked="" type="checkbox"/> 17.5 x 6.75 <input checked="" type="checkbox"/> Aluminium machined finish
	<input checked="" type="checkbox"/> Plastic spacer (rim & rim) <input checked="" type="checkbox"/> Plastic spacer (hub & rim)
	Tires : Qty : 24 Model : Mich. XTA2 Size : 245/70R17.5
	Hubodometer : <input checked="" type="checkbox"/> No Location :
	Title holder : <input checked="" type="checkbox"/> Truck-lite Location :
	Paint : Color: Black Color code: <input checked="" type="checkbox"/> Tape 100%
	Trim : <input checked="" type="checkbox"/> No Rim : <input checked="" type="checkbox"/> Natural
Special	
Return configuration hook points on dolly	Air locks on gooseneck tilt system
Wireless remote for manual steering	Spare tire rack on gooseneck
Steps on goosneck for quick hookup	80ft of rubber air lines and 70ft of hydaulic lines
Platform at quick hookup tower to change position of hooks	Rear push-pull point
Racheting winches on dolly	Cross chain hookup at rear on dolly
Steel ladder at front	Bypass valve for empty return
Extension for tandem jeep and tandem truck. Jeep and truck has 14' 1" inter-axle	

DISCLAIMER

Specifications are believed to be correct, but may contain errors and/or omissions. Photographs are the representative of the subject equipment but may not be identical. Equipment availability, prices and specifications are subject to change without notice.