








A019516-A019519
VINS: 41859-41862

SALES | RENTALS | PARTS | SERVICE

Allentown, PA: 800-383-8894	Jacksonville, FL: 800-828-3055
Baltimore, MD: 888-601-7500	Little Rock, AR: 833-424-8944
Boston, MA: 800-854-5310	Portland, ME: 800-325-4253
Concord, NC: 800-438-2250	Richmond, VA: 866-839-3495
Delmar, DE: 866-486-1400	Scranton, PA: 800-569-1400
Des Moines, IA: 888-673-5011	Springfield, MA: 800-854-5306
Elkton, MD: 800-544-7127	Voorhees, NJ: 866-315-0235

HaleTrailer.com | @haletrailer     

800-232-6535 *FINANCING AVAILABLE

Serial #: 41859 - 41862

components description

CAPACITY Standard Beam Pkg - 80,000 GVWR (60,000 in 10' Span)

OVERALL LENGTH 53' - Base Weight 13,990# - Including Length of Beavertail

UPPER DECK LENGTH 10'6"

LOWER DECK LENGTH 38'1"

DOVETAIL 53.13" - Steel Smooth Plate & Traction Bars

OVERALL WIDTH 8' 6"

KING PIN SETTING 24" - Tapered Front

UPPER COUPLER PLATE 1/4"

UPPER COUPLER HEIGHT 48"

MAINFRAME 26" Fab.-PreCamb.I-Beams-(80K Pkg)

BULKHEAD None

SIDE RAILS 6" - 6.5# Per Foot

TOP DECK FLOOR SILLS 4" Steel I-Beam - 18" O.C.

LOWER DECK FLOOR SILLS 4" Steel I-Beam 12" O.C. HD Pkg

COIL HAUL PACKAGE NONE

FLOOR DECKING 1-1/8" Apitong

WINCHES 12

WINCH TRACK Steel Slide Entire Length of Drivers Side

STRAPS None

LANDING GEAR Two Speed - Jost A500

SUSPENSIONS Air Ride - Hendrickson Intraax - 23K - 2 Axles - 22.5

SUSPENSION LOCATION King Pin to Center of Rear Axle 43'

AXLES (2) 23K Capacity - Type 30 Chambers -Auto Slacks -ABS - 22.5 Tires (1463#)

AXLE SPACING 49" (+35#)

Closed Tandem.

DUMP VALVE Manual-Position In Rear Skirt Gusset DIS-Dump All Axles

LIFT AXLE None

SCALES None

PARKING BRAKES All Axles

ABS SYSTEM Wabco ABS System 2S/1 M

DUST SHEILDS None

WHEELS Disc- Hub Pilot-22.5 (2-AX)-Polish ALUMINUM 4 Outside Wheels(4-Steel Inside) (-148#)

TIRES 255/70R 22.5 - 41" Loaded Deck Height - Double Coin

TIRE INFLATION SYSTEM None

STAKE POCKETS 24" O.C. & 4 Across Front

ANTI-SAIL MUD FLAPS Behind Rear Axle

PIPE SPOOLS Double

RUB BAND STEEL 3/8" X 2-1/2" Recessed for DOT Tape

DOCK BUMPERS None

LOADING RAMPS (2)-Spring Assisted

CONTAINER TWIST LOCKS None

CARGO TIE DOWN None

TIRE CARRIERS Tire Carrier Positioned In Front of Main Beams Between Landing Gear

TOOLBOX MATERIAL Aluminum- Smooth Box & Doors

TOOLBOX TYPE 18Hx18Dx60L-Alum Box-Barn Style Double Door- CAM LOCK STYLE 17-PRT-AH596

TOOLBOX LOCATION Driver Side- Behind Landing Gear

LIGHTS Accent Total LED Pkg- 5 Micros Per Side & Mid Turn-4/3/4 Strobe Rear

5 Total Markers Per Side.

Rear Strobes With Toggle Switch.

CUSTOM LIGHTS None

PAINT Black - PPG Epoxy Primer and Acrylic Polyurethane - Shot Blasted

DISCLAIMER

Specifications are believed to be correct, but may contain errors and/or omissions. Photographs are the representative of the subject equipment but may not be identical.

Equipment availability, prices and specifications are subject to change without notice.