

HALE

T R A I L E R

B R A K E & W H E E L

Hale Trailer Brake & Wheel
019558-019560

Base Model: CW45-102 Northeast Spec
components description
OVERALL LENGTH 45'
OVERALL WIDTH 8' 6" - 45ft
OVERALL HEIGHT FRONT 12'-10"= 6" Bow Rise in tarp system included in height
UPPER COUPLER HEIGHT 48"
UPPER COUPLER PLATE 5/16" Plate
KING PIN SETTING 36"
SWING CLEARANCE 90"= 36KP
LANDING GEAR Two Speed
SUSPENSIONS Air Ride - Hendrickson Intraax 25K - Slider (Manual Dump)
Air Gauge At Nose Roadside.
SUSPENSION LOCATION Slider/Variable
AXLES (2) 25K Capacity - Type 30 Chambers - Auto Slacks - ABS - Air Ride
AXLE SPACING 49"
LIFT AXLE None
WHEELS Disc - Hub Piloted- 22.5- (-56#)
TIRES 11R22.5 General RA 16 PLY
FRONT TYPE 10" Diagonal
FRONT MATERIAL Aluminum .063 - Pre Painted Black Aluminum
LADDERS Aluminum Nose
REAR DOOR TYPE Heavy Duty Dry Van Style Door
Quad Door Locks.
REAR DOOR MATERIAL Galv./Quilted Stainless Steel - Plywood
SIDE SHEET MATERIAL .063 Aluminum Smooth
Install Customer Furnish .100 Rear Sheets (1) Per Side.
INTERIOR LINING None
SIDE SHEET COLOR Black - Pre-Painted
SIDE POST Extruded Aluminum on 12" Centers
Half Round Post.
LOWER RAIL Heavy Duty Aluminum Lower Rail
FLOOR HallcoWalkFloorSyst,6000Series,7/32"STDDeck,Alum.Sub,45'-102WD
3.5" Drive Unit With 24" Wear Pads.
FLOOR SILLS 4" Alum. I-Beams between L.G.& Susp. & L.G.& 5th Wheel
SILL SPACING 8"/10"/8" Heavy Duty
Alum Sills On 8" Centers Between Fifth Wheel and Landing Gear.

****Alum Sills On 10" Centers in Bay Area.****
PARKING BRAKES All Axles
DUST SHEILDS None
ANTI-SAIL MUD FLAPS Behind Rear Axle
BUMPER H. D. 3" x 4" Push Bumper
****Stainless Steel Rear Frame.****
****Cathedral Rear Frame.****
TARP SYSTEM Shur-Co Brand Solid Lock and
Roll-Frt&RrCap-0Bows-22oz-2Straps-45'-102WD
**** (3) 6" Arch Sidewall Stiffeners.****
TARP COLOR BLACK
LIGHTS Sealed Wiring Harness W/ LED PKG
****LED Back Up Lights Mounted in Bumper - Work Lights Inside Front - Wired to**
Front in Waterproof Switch.**
****5 Marker Lights Per Side Along Lower Rail.****
PAINT Black - Fifth Wheel
GAWR 24.5K
Reference #8582

DISCLAIMER

Specifications are believed to be correct, but may contain errors and/or omissions. Photographs are the representative of the subject equipment but may not be identical. Equipment availability, prices and specifications are subject to change without notice.