



Hale Trailer Brake & Wheel

019648-019649

X-L SPECIALIZED TRAILERS, INC.

OAL: 27' 9"

OAW: 102"

MODEL: XL100JPS

DIST: 100,000

CONC.

WEIGHT +/-3% 0

2 AXLE JEEP

GOOSENECK-

LENGTH: 11' 5"
KING PIN SETTING: 16" 35"
SWING CLEARANCE: 105" 86"
5TH WHEEL HEIGHT: 50"
D-RINGS: 1 PAIR OF BENT D-RINGS
LANDING GEAR: 2 SPEED LANDING GEAR WITH HANDLE ON DRIVERSIDE

REAR DECK:

5TH WHEEL: PURCHASED 72" SLIDER
LOADED 5TH WHEEL HEIGHT: 51"
AXLES: (2) 25,000 NOMINAL, 77 1/2" TRACKING
SUSPENSION: HEND-TURNER / 25,000 AIR
AXLE SPACING: 60"
ABS: N/A , SPRING BRAKES PER 1 AXLE
TIRES: 275 / 70R / 22.5
WHEELS: 8.25 X 22.5 STEEL INSIDE, ALUMINUM POLISHED OUTSIDE DISC WHEELS
BRAKES: 16 1/2" X 7"
DRUMS: OUTBOARD
ELECTRICAL: 12V SEALED GROTE SYSTEM WITH 2 TAIL LIGHT PACKAGE
D-RINGS: 1 PAIR OF BENT D-RINGS
RAISE AND LOWER VALVE

ADDITIONAL:

PAINT: BLACK URETHANE ENAMEL WITH 2 PART EPOXY PRIMER
LIQUID FILLED AIR GAUGE
FRAME REINFORCEMENT, AIR ,ELECTRIC AND BRACKETS FOR AN ADDITIONAL AXLE
MANUAL RIDE HEIGHT CONTROL

DISCLAIMER

Specifications are believed to be correct, but may contain errors and/or omissions. Photographs are the representative of the subject equipment but may not be identical. Equipment availability, prices and specifications are subject to change without notice.