		SALES	RENTALS	PARTS	SERVICE
		Allentown, PA:	800-383-8894	Jacksonville, FL:	800-828-3055
		Baltimore, MD:	888-601-7500	Little Rock, AR:	833-424-8944
TRA	ILER	Boston, MA:	800-854-5310	Portland, ME:	800-325-4253
BRAKE	& WHEEL	Concord, NC:	800-438-2250	Richmond, VA:	866-839-3495
EAST GENESIS UNLOADER		Delmar, DE:	866-486-1400	Scranton, PA:	800-569-1400
	313 UNLUADER	Des Moines, IA:	888-673-5011	Springfield, MA:	800-854-5306
OPEN TOP X	A019765-A019770	Elkton, MD:	800-544-7127	Voorhees, NJ:	866-315-0235
EAST.	VIN: 87081-87086	HaleTrailer	.com @hale	trailer f У	
		800-232	2-6535 *	FINANCING	AVAILABLE

"GENESIS" B	ODY: WEDGE DESIGN	TAILGATE:		CHASSIS:	
WIDTH (INCHES)	102	HEIGHT	FULL	MODEL	TRIAXLE-2 FIXED-1 LIFT
LENGTH (FEET)	50	TYPE	SPLIT VAN DOORS	TYPE	ALUM SUB FRAME(11)
HEIGHT (INCHES)	104-107 NOTE (7)	STYLE	GENESIS	AXLE TO AXLE	60" - 60"
SIDE MAT'L (OUTBOAR	D) "GENESIS"	MAT'L THICKNESS	0.100	REAR AXLE SETTING	54"
FRONT 0.135		S / S HINGE ON	BOTH 4-3-4	5TH WHEEL HT	50"
MIDDLE 0.135		GATESEAL	RUBBER	PIN SETTING	36" + 3/8" KP PLATE
F	REAR 0.135	GATE LADDER	N/A	SUSPENSION	AAT30K/E1-2 L LIFT-E3
POLISHED SIDES	YES-INCLUDES BH	TARP HOOKS	NONE	SPRINGS	AIR(16)(17)(18)(19)(20)
ROOF	NONE	WINDERS	N/A	AXLES	TP
ROOF MAT'L	NONE	GATE GUIDE	N/A	BRAKES	HEND MAXX 22T
BULKHEAD	3/16" (1)(6)(8)(9)	GATE CONTROL	DBL LOCK RODS	DUSTSHIELDS	YES
TARP HOOKS	NONE	POCKETS	EXTRUDED	BRAKE CHAMBERS	AIR DISC BRAKES
TARP BASKET	NONE	CROSSPIPE (S)	TWO (14) CENTER	ABS	2S / 1M
TARP	NONE		& REAR - TUBE TYPE	HUBS	10 S LW STEEL
CATWALK	74" INTERMEDIATE				
B.H. LADDER	COMMERCIAL-D/S	COMPA	COMPACTOR:		8.25 X 24.5 4 HP/4MP
CROSSMEMBER	"I"BEAM- 12" C/L	SIDE LATCH	N/A		.(21)
FLOOR MAKE	KEITH - 3.5" DRIVES	CENTER LATCH		TIRES	11R 24.5 HSR 2 H 16
FLOOR MAT'L	#2295-24" WEAR STRIP	PIN DIA.			PLY CONTIN. (22)
WEARPADS	REAR + FILLER STRIP F	RONT		DOLLIES 2 SPEED	JOST HX151
TAPE COLOR	NONE	HYDRAULICS:		LOCATION	D/S CRANK
LIGHT PANEL	LED IN BODY (12)	HOSES	TWO-4000 PSI	BUMPER	STEEL UNDER RIDE
MARKER LIGHTS	LED (13)	LENGTH	108"W/ BOX ON BH	TOW HOOK(S)	TWO
MIDMOUNT SIGNALS	LED - MODEL 60	FITTINGS	WINGNUT	PUSH BLOCKS	YES
MUDFLAPS	YES (26)	HP	1" MALE	PAINT	BLACK
HOSE HANGER	YES	LP	1" FEMALE		
TIRE CARRIER	NONE (27)	HOSE LOCATION	P/S-REF PIC BELOW		
		AIR & ELECTRICAL	CENTER (2)(3)(5)		

OVERALL HEIGHT

<u>13' - 5"</u>

<u>20,387</u> EMPTY WEIGHT (#)

CUBIC YARDS

<u>134</u>

REMARKS: PRICING SUBJECT TO CHANGE 12 WEEKS PRIOR TO ESTIMATED BUILD DATE

1. NO CAST STEPS INSIDE OF BULKHEAD OPPOSITE OUTSIDE LADDER ON D/S

2. RIGHT WEIGH OIL FILLED GAUGE (LBS.) MOUNTED ON NOSE TOWARDS D/S- REFERENCE PIC BELOW.

3. FILTERED GLADHANDS

5. ADD AUXILIARY ISO 7 WAY PLUG LABELED '7 WAY ISO'.

6. MANDOOR IN CENTER OF BULKHEAD.

7. TOP RAIL SECTION 99246 - LIGHT WEIGHT TOP RAIL

8. KEITH ALUMINUM SUBFRAME. STAINLESS STEEL HYDRAULIC TUBING. ADD DRIVE UNIT BRACES. STANDARD SPLASH BEARINGS.

9. ALUMINUM AIR TANKS TO HAVE CABLE OPERATED DRAINS EXTENDED TO D/S BOTTOM RAIL.

10. FLOOR OPENING MOVED FORWARD FOR TRIDEM, MAKE SURE DRIVE UNIT OPENING MISSES ALL AXLES, NOTE AXLE SPACING AND SETTINGS. 11. EXTEND SUBFRAME AS NEEDED TO ACCOMMODATE AXLE SPACING AND HAVE ALL AXLES MISS DRIVE UNIT.

TI. EXTEIND SUBFRAME AS NEEDED TO ACCOMINIODATE AXLE SPACING AND HAVE ALL AXLES MISS DRIVE OF

12. LIGHT PANEL IN BODY AND TO HAVE LED BACK UP LIGHTS OOOX 000 XOOO

13. LED-5 PR OF 30385Y/R MARKER LIGHTS BOTTOM & TOP -NO PROTECTORS. TOP ROW 16" DOWN FROM TOP OF TOP RAIL. EVENLY SPACED.

14. CROSSPIPE TO BE IN STANDARD PLACEMENT.

15. STANDARD NYLON T BLOCKS

16. AAT30K FOR AXLES #1 & #2 AND AAL30K LIFT AXLE AS AXLE #3 (REAR AXLE) - ALL AXLES TO EQUALIZE

17. REAR LIFTING AXLE TO HAVE BRAKE RELEASE VALVE - REAR AXLE ACTUATED WITH FRAME SWITCH + ELEC CC (WIRED THROUGH AUX. PLUG) 18. ALL CONTROLS IN POLYCARBONATE BOX AHEAD OF AXLE #1 AND WIRED FOR CC THROUGH AUX PLUG-REF.69464.

19. GALVANIZED SUSPENSION HANGERS.

20. 16" BLACK MUDFLAPS AHEAD OF TIRES FOR AXLE #1, #2, #3

21. NO WHEEL GUARD INSULATORS.

22. TIREMAXX PRO ON ALL AXLES.


23. 073-20176-01 - HALE KNURLED MANDOOR STEP

24. ONE PAIR OF LED BOXED IN BACK UP LIGHTS LOCATED AHEAD OF SUSPENSION SHINING REARWARD AND WIRED WITH OTHER B/U LIGHTS

25. C/L OF LANDING GEAR TO END OF THE FLOOR TO BE APPROXIMATELY 34'.

26. ADD CENTER BLACK MUDFLAP AHEAD OF AXLE #1, ADD CENTER REAR CHASSIS BLACK MUDFLAP-REF PIC, MOVE REAR MUDFLAPS FORWARD SO THEY ARE INLINE WITH THE CENTER FLAP-REF PICS

27. ADD ONE 24" X 24" X 48" 1/8" MATERIAL TOOLBOX WITH CAMLOCK DOUBLE DOOR; D/S AHEAD OF SUSPENSION







Specifications are believed to be correct, but may contain errors and/or omissions. Photographs are the representative of the subject equipment but may not be identical. Equipment availability, prices and specifications are subject to change without notice.

DISCLAIMER