



Hale Trailer Brake & Wheel 019883-019888

CAPACITY Standard Beam Pkg - 80,000 GVWR (60,000 in 10' Span)
OVERALL LENGTH 48' - Base Weight 10,640#
UPPER DECK LENGTH 10'
LOWER DECK LENGTH 38'
OVERALL WIDTH 8' 6"
KING PIN SETTING 18" - Squared Front
UPPER COUPLER PLATE 1/4"
UPPER COUPLER HEIGHT 48"
FRONT SKIRT Steel
REAR SKIRT Aluminum
BULKHEAD Removable Steel - 48" - NO Side Return - 4 Posts DOT-(+387#)
MAIN FRAME 26" Fab.-PreCamb.I-Beams-(80K Pkg)**44" Frame Centers**
SIDE RAILS 6"-Alum-Extruded W/Double L Track
TOP DECK FLOOR SILLS 4" Steel I-Beam - 18" O.C.
LOWER DECK FLOOR SILLS 4" Steel I-Beam 12" O.C. HD Pkg
COIL HAUL PACKAGE Single Coil Placement - 5 Extra Stud Sils-Ctr On Trailer
FLOOR DECKING 1-1/8" HD Aluminum W/4 Nailer Boards
WINCHES 12 DOUBLE L (+)#75
WINCH TRACK Double L Aluminum - Extruded Siderail R/S Only
TIE BAR Curb Side - Full Length - 3/8" x 2"
STRAPS None
LANDING GEAR Two Speed
SUSPENSIONS Air Ride - Meritor MTA 23K 2 Axle - Fixed
SUSPENSION LOCATION Center of KP To Center of Axle Group 41'
AXLES (2) 22.5K Cap.- Type 30 Chambers - Auto Slacks - ABS - 22.5 Tires (1463#)
AXLE SPACING 49" (+35#)
LIFT AXLE None
DUMP VALVE None
SCALES None
PARKING BRAKES All Axles
ABS SYSTEM ABS System 2S/1M
DUST SHEILDS None
WHEELS Disc - Hub Piloted - 22.5 - Steel (672#)
TIRES 255/70R 22.5 - 41" Loaded Deck Height - Double Coin
TIRE INFLATION SYSTEM None
ANTI-SAIL MUD FLAPS Behind Rear Axle

STAKE POCKETS 24" O.C. Sides & 5 Across Rear
SPOOL Triangular Shaped
RUB BAND ALUM 3/8" x 3" - Aluminum - Recessed for DOT Tape
DOCK BUMPERS Rubber Inboard
CARGO TIE DOWN 14 Pair of Recessed Chain Ties Evenly Spaced
CONTAINER TWIST LOCKS None
TIRE CARRIERS None
DUNNAGE RACK None
TOOLBOX MATERIAL None
TOOLBOX TYPE None
TOOLBOX LOCATION None
LIGHTS Sealed Wiring Harness- 2 Micros Per Side & Mid Turn-3/3/3 Rear
CUSTOM LIGHTS None
PAINT Black

DISCLAIMER

Specifications are believed to be correct, but may contain errors and/or omissions. Photographs are the representative of the subject equipment but may not be identical. Equipment availability, prices and specifications are subject to change without notice.