



Hale Trailer Brake & Wheel
019916-019923

X-L SPECIALIZED TRAILERS, INC.

OAL: 53'
OAW: 102"

MODEL: XL 70HDGSM DIST: 70,000# CONC. 60,000# IN 16'

WEIGHT +/-3%

GOOSENECK-

LENGTH: 11' FULL WIDTH SCRAPER NECK
 KING PIN SETTING: 16"
 SWING CLEARANCE: 86"
 5TH WHEEL HEIGHT: 49" W/ 5 VARIABLE RIDE HEIGHT POSITIONS
 DECKING: 1 1/8" APITONG DECKING FLUSH
 D-RINGS: 2 BENT D-RINGS PER SIDE - 4 TOTAL
 HYDRAULICS: 13HP HONDA POWER UNIT WITH DUAL HYDRAULICS - ALUMINUM COVER
 TOOL BOX: NONE

MAIN DECK-

3 BEAM DESIGN
 LENGTH: 33'
 LOADED DECK HGT: 12" W 4" GROUND CLEARANCE
 DECKING: STEEL DECKING BETWEEN MAIN BEAMS
 1 1/8" APITONG DECKING, FLUSH BETWEEN MAIN BEAMS AND OUTER BEAMS
 CROSSMEMBER: PER ENGINEERING
 SIDE BEAMS: FAB I-BEAMS 8"
 D-RINGS: 10 BENT D-RINGS PER SIDE- 20 TOTAL
 CHAIN DROPS: CHAIN DROPS ON 18" CENTERS
 RAMPS: TAPERS TO 4"
 OUTRIGGERS: NONE

REAR DECK:

LENGTH: 9'
 LOADED DECK HEIGHT: 40"
 AXLES: (2) 25,000 NOMINAL, 77 1/2" TRACKING
 SUSPENSION: HEND-TURNER / 25,000 AIR
 AXLE SPACING: 54"
 ABS: 4S2M WITH SPRING BRAKES ON 2 AXLES
 TIRES: 255 / 70R / 22.5 HANKOOK
 WHEELS: 8.25 X 22.5 STEEL INSIDE, ALUMINUM POLISHED OUTSIDE DISC WHEELS
 BRAKES: 16 1/2" X 7"
 DRUMS: HUB PILOT / OUTBOARD DRUMS
 ELECTRICAL: 12V SEALED GROTE SYSTEM WITH 3 TAIL LIGHT ALUMINUM PACKAGE
 4" AMBER STROBE WITH SWITCH TO MAKE 3 STT
 DECKING: 1 1/8" APITONG DECKING, FLUSH
 D-RINGS: 2 BENT D-RINGS IN TAIL CHANNEL

ADDITIONAL:

PAINT: BLACK URETHANE WITH 2 PART EPOXY PRIMER
 LIQUID FILLED AIR GAUGE WITH CHART
 4-WAY PLUG AT REAR
 MANUAL RIDE HEIGHT CONTROL
 LED LIGHTING
 FRAME REINFORCEMENT, AIR, ELECTRIC AND BRACKETS FOR FLIP AXLE
 RAISE AND LOWER VALVE
 2 PAIR OF PAN D-RING ON REAR BRIDGE PLATFORM CORNERS

DISCLAIMER

Specifications are believed to be correct, but may contain errors and/or omissions. Photographs are the representative of the subject equipment but may not be identical. Equipment availability, prices and specifications are subject to change without notice.