

Hale Trailer Brake & Wheel 019936-019939

X-L SPECIALIZED TRAILERS, INC. OAL: 53' OAW: 102"

MODEL: XL 80HDGSM DIST: 80,000# CONC. 80,000# IN 16' WEIGHT +/-3%

GOOSENECK-

LENGTH: 11' FULL WIDTH SCRAPER NECK

KING PIN SETTING: 16"
SWING CLEARANCE: 86"

5TH WHEEL HEIGHT: 49" W/ 5 VARIABLE RIDE HEIGHT POSITIONS

DECKING: 1 1/8" APITONG DECKING FLUSH
D-RINGS: 2 BENT D-RINGS PER SIDE - 4 TOTAL

HYDRAULICS: 13HP HONDA POWER UNIT, DUAL HYDRAULICS WITH ALUMINUM COVER

TOOL BOX: NONE

FLIP NECK: FRAME REINFORCEMENT, AIR, ELECTRIC AND BRACKETS FOR 36" FLIP NECK EXT.

36" FLIP NECK EXTENSION

MAIN DECK- 3 BEAM DESIGN

LENGTH: 33' (32' 6" OF CLEAR DECK)
LOADED DECK HGT: 12" W 4" GROUND CLEARANCE

DECKING: STEEL DECKING BETWEEN MAIN BEAMS WITH DURABAK

1 1/8" APITONG DECKING, FLUSH BETWEEN MAIN BEAMS AND OUTER BEAMS

CROSSMEMBER: 4" JR. I I BEAMS ON 12" CENTERS

MID-HEADER IN MAIN DECK

SIDE BEAMS: FAB I-BEAMS 8"

D-RINGS: 10 BENT D-RINGS PER SIDE- 20 TOTAL

RAMPS: TAPERS TO 4"
OUTRIGGERS: NONE

REAR DECK:

LENGTH: 9'
LOADED DECK HEIGHT: 40"

AXLES: (2) 25,000 NOMINAL, 77 1/2" TRACKING

SUSPENSION: HEND-TURNER / 25,000 AIR

AXLE SPACING: 54"

ABS: 4S2M WITH SPRING BRAKES ON 2 AXLES

TIRES: 255 / 70R / 22.5 HANKOOK

WHEELS: 8.25 X 22.5 STEEL INSIDE, ALUMINUM POLISHED OUTSIDE DISC WHEELS

BRAKES: 16 1/2" X 7"

DRUMS: HUB PILOT / OUTBOARD DRUMS

ELECTRICAL: 12V SEALED GROTE SYSTEM WITH 3 TAIL LIGHT ALUMINUM PACKAGE

4" AMBER STROBE WITH SWITCH TO MAKE 3 STT

DECKING: 1 1/8" APITONG DECKING, FLUSH
D-RINGS: 2 BENT D-RINGS IN TAIL CHANNEL
2 PAIR OF PAN STYLE D-RINGS

ADDITIONAL:

PAINT: BLACK URETHANE WITH 2 PART EPOXY PRIMER

LIQUID FILLED AIR GAUGE WITH CHART

4-WAY PLUG AT REAR

MANUAL RIDE HEIGHT CONTROL

LED LIGHTING

FRAME REINFORCEMENT, AIR, ELECTRIC AND BRACKETS FOR FLIP AXLE

RAISE AND LOWER VALVE