	SALES RENTALS PART	TS SERVICE
	Allentown, PA: 800-383-8894 Jacksonv	ville, FL: 800-828-3055
		ock, AR: 833-424-8944
		and, ME: 800-325-4253
		ond, VA: 866-839-3495
		ton, PA: 800-569-1400
	DOONAN A020134-A020135 Des Moines, IA: 888-673-5011 Springfi	eld, MA: 800-854-5306
	- SPECIALIZED- Elkton, MD: 800-544-7127 Voorh	ees, NJ: 866-315-0235
	VIN: 625510-625511	
	HaleTrailer.com @haletrailer	
	800-232-6535 *FINAN	CING AVAILABLE
FRAME	Est GVWR: 90,000#	Est Beam Rating in 16': 80,000#
Туре	Double Drop	
Model	Black Gold	
Neck Type	Fixed Gooseneck - Full Width	
Extendible	None	
	Feet Inches	
Length	Overall length 48 0	
	Gooseneck length 10 0 Rear deck length #VALUE! #VALUE!	
	Well length #VALUE! #VALUE!	
	Swing Clearance 82	
Width	102 Inches	
Beams	4 Main Beams - 2 Beams (Near Center) and 2 Beams (Outer Perimeter).	40" Beam centers
Inner Beam Flange	Steel: 3/4" x 7" Top Flange & 3/4" x 7" Bottom Flange	
Web Thickness	Steel: 3/8" Thickness	
Inner Beam Depth	12" - Double Drop Only	
Beam Holes	None	
Well Deck Height	20" - Well Deck Height When Loaded	Build with 8" Ground clearance
Sill Height	Steel: Alternating 6" & 4" Crossmembers Height on 12" Centers	
Coil Kit	None	
Rear Deck Height	40 Inches - Dropdeck (BG/Dia - Based on 22.5" Tires)	Rear deck height will be closer to 42-
Fifth Wheel Height	49 Inches	43" deck height with 295 Rubber
-	16 Inches	
King Pin Side Rail	Not Available (See Perimeter Beams Options Section)	
Extra Stake Pockets		
Conspicuity Tape	None Pair Qty 0 Conspicuity Tape on Perimeter Beam 0	
Front & Rear Plates	FRONT: Steel Sqr Cnr NO-Stake Pkts - REAR: Steel NO-Stake Pkts & Rubrail	
Flag Holders	None	
Rubber Dock Bumpers		
Drop Plate	40" Steel Drop Plate (Lowbed with 12" Beam Depth)	
Knee Braces	None	
Paint	Black	
Flooring	TOP: 1 3/8" Apitong, WELL: 1 3/8" Apitong, REAR: 1 3/8" Apitong	
-		Same Landing Leg and sand shoe as
Load Hook Flooring	No Load Hook Track in Floor	Unit 622308
		Oversized Sand shoe - Design
Landing Gear	Jost Fleetcraft J - Handle: Road	brackets so will wind up to allow them
		to be above bottom flange
Rear Enclosure	Large Rear Plate For Perimeter Beams - Lights in Rear Sill, No Filler Panels	
PERIMETER BEAM OPTI	· · · · ·	e Ungrouped
Outer Beam Flange	Steel: 1/2" x 6" Top Flange & 1/2" x 6" Bottom Flange	
Outer Beam Depth	Same As Inner Beam - DD	
RGN - Lower Deck Nose	None	
Pull-outs	None	
Outriggers	None erightory 0	• · · · · · · · ·
L Type Chain Anchors	Yes (Enter Qty in Pairs) - Specify Location Pair Qty 5	Stagger in well with D rings
Perimeter Beam D-Rings	D-Rings - 1" Steel Weld-on (Specify Qty in Pairs in space to th Pair Qty 13	
OILFIELD OPTIONS	No Options Selected - Oilfield Options May be Group	
STRUCTURAL OPTIONS		
SUSPENSIONS & AXLES	GAWR: 20,280 # 2	Axles on this Configuration
Suspension Type	Air Ride Suspension - Hendrickson HT250	Front susp built on 39" centers - Rear
		suspension built on 38" Centers

Axle Type	Other Est GVWR: 90,000#	Use Hendrickslon TRLAXLE with Mountain brakes to get a 23,500
		GAWR
Number of Axles	2 Axles - Standard	
Sliding Axles	None	
Axle Spacing	54 Inches Inches 0	
Overhang	Other Inches 26	
Cal & Can Legal	California Legal - Trailers with Overall Length 48 Ft or Less are Exempt	
Steerable Axle	None	
Lift Kits	None	
Axle Straps	None	
• ••	N-Type (All Axles)	
Brake Type	Drum Brakes - Spring brakes with auto slack adjusters	
Hub Type	Cast - Hub Piloted	
Drum Type	Cast	
Brake Dust Covers	None	
Bearing Lubricant	Synthetic Semi Fluid Solid Grease	
	None	
Inflation Sys & Crossfires	None	
Mudflaps	Single Mudflap in Rear with a Bolt-on Spring-loaded Bracket	
TIRES & WHEELS	8	Wheels and Tires in this Configuration
Tires	Other - Doonan Supplied	Must use General RA 295/75R22.5 to get 23,500# GAWR
Outer Wheels	22.5" Standard Duty Steel - White	
Inner Wheels	22.5" Standard Duty Steel - White	
Spare Tire	None	
Spare Wheel	None	
Tire Carrier	None	
LIGHTS		
Rear Lights	4-3-4 Light Pattern - Center 3 are MicroDot Lights, Outers are 4" LED	
Extra Row of Rear Light	None	
	Backup Lights (LED)	Oval lights Wired to switch in box
Strobe Lights	Strobe Lights – Inside Tail Light Hole Wired to Toggle Switch in Box	
Over Dimension Lights	None Pair Qty 0	
Side Marker Lights	MicroDot Lights - Qty 3 Pairs Pair Qty 3	
	None	
AIR & ELECTRICAL OPTIC		
Anti-lock Braking System		
	(Standard) One Set of Glad Hands & 7-way Connections	
	Air Raise & Lower Valve In A Polycarbonate Box (Mounted on Bracket)	Locate In rear sill
	None	
Pull Lanyards on Air Tanks		
	None	
	No Options Selected - Load Securement Options May	/ be Grouped
	None (Steel Side Rail)	
	None	
	None Qty 0	
j	None Qty 0	
J	None Qty 0	
Recessed Floor D-Rings	None Pair Qty 0	
_		
Chain Ties	None Pair Qty 0	
Chain Ties Rope Hooks		

J-Hooks	None	Est GVWF	R: 90,000#	Qty 0			
J-Hook Carriers	None			Qty 0			
Container Locks	None						
Load Bunks	None			Qty 0			
Bulkheads	None			Location None			
BOXES		No Options Selected - Box Options May be Grouped					
Tool Boxes: Type 1	None	Door: None	Locks: None	Qty 0			
Tool Boxes: Type 2	None	Door: None	Locks: None	Qty 0			
Gooseneck Boxes	None						
Belly Boxes	None						
Racks	None						
Weight: 16,146 #							

DISCLAIMER