



A020144-A020146
VIN: 229806-229808



SALES | RENTALS | PARTS | SERVICE

Allentown, PA:	800-383-8894	Jacksonville, FL:	800-828-3055
Baltimore, MD:	888-601-7500	Little Rock, AR:	833-424-8944
Boston, MA:	800-854-5310	Portland, ME:	800-325-4253
Concord, NC:	800-438-2250	Richmond, VA:	866-839-3495
Delmar, DE:	866-486-1400	Scranton, PA:	800-569-1400
Des Moines, IA:	888-673-5011	Springfield, MA:	800-854-5306
Elkton, MD:	800-544-7127	Voorhees, NJ:	866-315-0235

HaleTrailer.com | @haletrailer
800-232-6535 *FINANCING AVAILABLE

ITEM	DESCRIPTION
TYPE	SEMI-TRAILER, TELESCOPIC STEEL DROP PLATFORM.
DIMENSIONS	
LENGTH	53'-0" closed.
LENGTH	71'-0" opened.(78" OVERLAP)
OPENINGS	5'-0" increments in closed position.
WIDTH	102", 97" between side rails.
HEIGHT	Floor, approximately 61" high at front and 41" at the bumper.
DROP HEIGHT	21", located at *** 11'-6" *** from front.
COUPLING	
COUPLER PLATE	1/2", plug welded structure. (K.P. at 18")
KING PIN LOCATION	18" from front.
COUPLER HEIGHT	50".
STRUCTURE	Frame with "CAMBER".
FLANGES	Female section, exterior, 1/2" x 6", 100 000 psi steel, 24" high. ***minimum of 78" overlap***
FLANGES	Male section (interior), 3/4" x 6", 60 000 psi steel, 17 5/8" high and 16 1/2" above suspension.
WEB	1/4", 80 000 psi full length.
GOOSENECK	12 1/4" high, 48" straight behind king pin.
CROSSMEMBERS	I beams, 4" @ 3.64 lbs/ft, 80 000 psi steel. 16" center to center in gooseneck and the remaining 12" c/c.
FLOOR	Apitong or equivalent, 1 1/8" thick shiplap finished, no preservative.
FLOOR FASTENING	Two screws per board at each crossmember.
SIDE RAILS	6" channel @ 8.2 lbs/ft.
SIDE BOXES	3/16" steel plate, 1 5/8" x 3 5/8" interior, 4" high. (USA Dimensions).
RUB RAILS	3/8" x 2 1/2" shaped steel.
CORNERS	Bevelled.
FENDERS	Over tires at rear, checker plate 1/8".
DIAGONAL BRACES	2" x 2" x 3/16" angles, welded in web and to a crossmember, located each side.
LOCKS	Air operated with a third glad hand at front.
ROLLERS	4, 2 on female sections of frames and 2 on male sections.
ENDS	
FRONT RAIL	Formed steel 1/4".
BUMPER	CMVSS 223-RIG approved (in accordance with Canada & USA regulations). Uprights integrated with frames, 4" x 4" cross bar roll formed tubing at a maximum height of 22" from under tubing to ground.
POCKETS	2 bolted galvanised pockets at front for removable headboard.
REAR RAIL	11" high, 9 gauge formed steel, including 3 boxes at rear and 3/8" x 2 1/2" shaped steel.
BUMPER	Bracing for a ***flip-up axle*** and (1) rubber dock at top front Same as U#215306
ELECTRICAL	



ITEM	DESCRIPTION
FRONT CONNECTOR ELECTRICAL SYSTEM MAIN SYSTEM TURN SIGNAL REAR ADD. CONNECTOR STROBE LIGHTS	7 way (SAE J560), Phillips brand. Shock proof lights, polycarbonate lenses, in compliance with CMVSS 108. Grote Ultra Blue LED, sealed beams Grote, tail lights with male pins #54332, markers #47122, 47233 (2 1/2" dia.), licence light #60280-M, with vapor proof junction box Truck-Lite #50400. Sealed beams LED, one lamp including side marker and flasher, each side at middle point, amber. 4 way. Sealed beams (Grote LED #77353 strobe) amber. Qty: (1) each side. toggle switch installed: IN THE CONTROL BOX
LANDING GEAR SAND SHOES CRANK	Holland, Mark V (LGH-4F010), heavy duty, with mounting plate. 18" x 18", solid axle. Road side.
BOGIE BASIC SUSPENSION BOGIE SUSPENSION LIFT DEVICE U-BOLTS SPRINGS AXLE(S) SPIDERS CAM SHAFTS TRACK DUST SHIELDS BRAKES BEARINGS SLACK ADJUSTERS SEALS BRAKE CHAMBERS HUBS AND DRUMS RIMS TIRES	Fixed. Hendrickson HT-250US (6.5), tandem, 60" spread. Hendrickson HT-250US (6.5) with Manac center lift. located at 60" rear of tandem ***controlled manually*** Only 1 1/2" of clearance from the ground if used at rear. *** NO WARRANTY ON THE TIRES NOR GROUND AXLES, (FLAT SPOT) *** With nuts at bottom. Air. Hendrickson, HP-S506, 27 000 lbs. capacity. Welded. 28 splines. 77 1/2". None (Hendrickson axles). 16 1/2" standard, long life H26-HXS Hendrickson lining. HM 218248 and HM 212049. Meritor, automatic, 28 splines. Stemco, "Guardian" type, with "Gearlube" mineral oil, SAE 80W90. T.S.E. brake, "Omnibrake" (30-30), (push rod 9 3/4"), long stroke. (4 years warranty by T.S.E. for parts only). WEBB, 10 studs disc hubs, balanced drums 117 lbs, outboard mount, 285.75mm B.C., single flange nuts. For dual steel wheels or single wheels. (Heavy duty 25000 lbs cap.) (Bearings HP). 22.5 x 8.25, disc (10 holes), 285.75mm B.C., single flange nuts, 2 hand holes. Light duty Continental, 275/70 R 22.5 HSR2 SA 18 ply (38.0")
AIR SYSTEM GLAD HANDS AIR VALVES VALVE(S) VALVE	Fixed. Meritor Wabco, ABS, 2 sensors 1 modulator. Fast-brake kit. Manual blow down valve in a control box, with auto-reset feature,



ITEM	DESCRIPTION
CONTROL BOX	including Glycerin filled pressure gauge, in P.S.I., to indicate load with a conversion table. Stainless steel
ACCESSORIES REGISTRATION HOLDER WINCHES SLIDING TRACK MUD FLAPS EXTRA MUD FLAPS	One plastic, Betts-PS-1 or equivalent. Qty: 12, KINEDYNE #1020SV, silver painted slider (5 7/8"). Full length, "LL" extruded aluminum, road side. One set, rubber with Manac logo and vertical grooves to reduce spray. Qty: 2, rubber. Located: 1 at front of landing gear in between main frames, to protect roller and 1 at front of suspension in between main frames, to protect air boosters.
FINISHING PAINT AXLE(S) PAINTED HUBS WHEELS OR RIMS RETROREFLECTIVE TAPES	Shot blasted, one coat of epoxy primer and two polyurethane acrylic top coats Color: black, code: PPG AU37-FP908. Color: Black, code:PPG AU37-FP908 Color: Black, code:PPG AU37-FP908 White. Conspicuity striping in compliance with CMVSS 108. Gray and red, each side, fully covers rear sill and horizontal underride protection bar.
ADDITIONAL OPTIONS R	Ref. U#215306 *** 78" overlap *** Due to the deep backlogs, material/component availability, price fluctuation and transportation costs, Manac reserves the right to adjust the price based these instabilities. If needed, Manac will contact the dealer or customer app 3 months prior to assembly with revised pricing, or a change in components. At that time, the customer will have the option to accept the change or cancel This will prevent and any possible cancellation fees from our suppliers.
CONFORMITY	This semi-trailer does not comply with GHG regulations. Should GHG regulations come into force prior to the production of the trailer(s), Manac will have the obligation to ensure the trailer(s) produced meet minimum GHG guidelines. Any modifications required to meet the GHG regulations will be added to the initial purchase price and charged back to the customer.

DISCLAIMER

Specifications are believed to be correct, but may contain errors and/or omissions. Photographs are the representative of the subject equipment but may not be identical.
 Equipment availability, prices and specifications are subject to change without notice.