

HALE TRAILER BRAKE & WHEEL



A020152-A020157
VIN: 43749-43754

SALES | RENTALS | PARTS | SERVICE

Allentown, PA:	800-383-8894	Jacksonville, FL:	800-828-3055
Baltimore, MD:	888-601-7500	Little Rock, AR:	833-424-8944
Boston, MA:	800-854-5310	Portland, ME:	800-325-4253
Concord, NC:	800-438-2250	Richmond, VA:	866-839-3495
Delmar, DE:	866-486-1400	Scranton, PA:	800-569-1400
Des Moines, IA:	888-673-5011	Springfield, MA:	800-854-5306
Elkton, MD:	800-544-7127	Voorhees, NJ:	866-315-0235

HaleTrailer.com | @haletrailer     

800-232-6535 *FINANCING AVAILABLE

Model: Axle Attachment
Capacity in tons: 55

1. DESIGN PARAMETERS

Type	Flip-up & removable
Framework	Fabricated
Suspension	Ridewell air
Axle attachment connections	Attachment to be equipped with top and bottom connecting ears, pin tubes with bolts and nuts, shims, chrome tapered connecting pins, air and electrical connections
Axle capacity	25,000# - GAWR 24,700#
Brakes	16-1/2" x 7" air actuated
Wheels	Ten (10) stud; 285.75mm B.C. aluminum/steel disc hub piloted system with oil seals, inner wheels steel with outer aluminum wheels polished
Anti-lock brake system	None
Tires	Four (4) 275/70R22.5 (H) 16PR radials
Bridge width	8'-6"
Axle frame height	41" frame; 37" bolster
Half bolster	With flag holder slots
Lash rings	2 at rear bent style
Lights and wiring	12 volt system with the following: All lights to be LED excluding license plate light All marker/I.D. lights to be 3/4" bullet style 4 combination (2 PER SIDE) stop/turn/tail and back-up lights, back-up lights wired to switch on marker light circuit Strobe lights with switch at rear Wire for battery back-up
Paint	Valspar standard Talbert black, R-Cure 800 series paint with ZINC RICH primer
Mudflaps	Talbert anti-sail
Additional design specifications	1) 2 rubber bumpers on top 2) 54" axle spacing 3) Over ride chains 4) Estimated empty weight: 2,850#
Compatibility	With existing Talbert Trailer, 55SA or 55CC

DISCLAIMER

Specifications are believed to be correct, but may contain errors and/or omissions. Photographs are the representative of the subject equipment but may not be identical. Equipment availability, prices and specifications are subject to change without notice.