

HALE

TRAILER

BRAKE & WHEEL



A020211-A020214
VIN: 5A4371-5A4374

SALES | RENTALS | PARTS | SERVICE

Allentown, PA: 800-383-8894	Jacksonville, FL: 800-828-3055
Baltimore, MD: 888-601-7500	Little Rock, AR: 833-424-8944
Boston, MA: 800-854-5310	Portland, ME: 800-325-4253
Concord, NC: 800-438-2250	Richmond, VA: 866-839-3495
Delmar, DE: 866-486-1400	Scranton, PA: 800-569-1400
Des Moines, IA: 888-673-5011	Springfield, MA: 800-854-5306
Elkton, MD: 800-544-7127	Voorhees, NJ: 866-315-0235

HaleTrailer.com | @haletrailer     

800-232-6535 *FINANCING AVAILABLE

Renegade N12 Air Tandem, 12 inch Loaded Deck Height, Narrow Hydraulic Gooseneck (Model: RENEGADE N12)

RENXLN12F*833542

Est. Wt.: 20,385# +/- 3%

Capacity: 30 tons in 16-foot length - GAWR and tire ratings determine legal loads- 30 tons in 20 foot with 3rd axle

Load Base: 16-foot rigid 2-point load centered in deck

Length (Trailer Only): 53 feet 0 inches

Width: 8 feet 6 inches

Compatibility: Designed to accept optional low profile third flip axle

Gooseneck Design: Narrow hydraulic removable non-ground bearing - swing radius of 96 inches (11 ft 2 in overall gooseneck length) - set up for wet line operation

Loaded Fifth Wheel Height: 50 in nominal loaded fifth wheel height via dual cam pawl arm assembly with 7 ride height positions

Power Source: None

Deck Design: Flat level deck design

Deck Length: 32 feet 11 inches clear deck length

Loaded Deck Height: 12 inches with 4 inch ground clearance (Fully Loaded)

Crossmembers: On 18 inch centers

Flooring: 1 3/8 inch nominal Apitong wood (full width)

Recessed Floor Mounted D-Ring Package: None

Front Ramps: None, front of deck sloped top down to assist in loading with traction cleats

Extension Brackets: None

Front Bogie Ramp: Sloped steel bogie ramp (full width)

Deck to Bogie Connection: Fixed

Number of Axles: 2

Axle Capacity: 25,000 lb. nominal capacity per axle NOTE: GAWR determined by suspension type, brakes, tires and other components.

Axle Spread: 50 inches (between axles)

Brakes: 16.5 inches x 7 inches with 5.5 inches autoslacks - heavy duty brake drums - outboard mount

Spring Brakes: Spring brakes (2 axles)

Dust Shields: None

Framework: All main longitudinal members fabricated with 100,000# minimum yield steel flanges with 50,000# webs

Suspension: Air ride with automatic controls

ABS: 4S/2M system without diagnostic tool and cable

Load Scale: None Standard

Wheels: 8.25 x 22.5 LVL One buffed outside/steel inside - hub-piloted

Tire Brand: OEM Standard

Tires: 255/70R 22.5 H ply OEM Standard

Hubodometer: None Standard

Tire Inflation: None Standard

Covered Rear Bogie: Rear bogie platform with 1 1/8 inch wood floor

Rear Bogie Height: 41.5 inches

Bumper: 3 tail light package

Connections for Future Axle Attachment: Air and electrical connections to go along with connecting ears	
Mini Boom Trough & Traction Cleats: None	
Liquid Filled Gauge: Standard	
Electrical System: DOT sealed beam and harness with LED lights and 4 inch flush mounted battery powered amber strobes	
Marker Lights: 6 marker lights per side including mid-turn	
Electrical Receptacle: J560 7-pin connector	
Additional Marker Lights: None Standard	
Paint: Fontaine black polyurethane enamel	
Lash Rings: 12 pair - 24 total	
Flag Holders: 2 pair flag holders	
Registration/Document Holder: Registration/document holder installed	
Please Note: Price includes commodity surcharges	
Commercial Terms: Ex Works- Springville, AL, USA	
Flip Axle: None	
Dust Shields on Flip Axle: None	

DISCLAIMER

Specifications are believed to be correct, but may contain errors and/or omissions. Photographs are the representative of the subject equipment but may not be identical. Equipment availability, prices and specifications are subject to change without notice.