

HALE

TRAILER

BRAKE & WHEEL

GENESIS FRAME DUMP



A020278-A020279
VIN: 87857-87858

SALES | RENTALS | PARTS | SERVICE

Allentown, PA:	800-383-8894	Jacksonville, FL:	800-828-3055
Baltimore, MD:	888-601-7500	Little Rock, AR:	833-424-8944
Boston, MA:	800-854-5310	Portland, ME:	800-325-4253
Concord, NC:	800-438-2250	Richmond, VA:	866-839-3495
Delmar, DE:	866-486-1400	Scranton, PA:	800-569-1400
Des Moines, IA:	888-673-5011	Springfield, MA:	800-854-5306
Elkton, MD:	800-544-7127	Voorhees, NJ:	866-315-0235

HaleTrailer.com | @haletrailer

800-232-6535 *FINANCING AVAILABLE

Length	37'	BODY SPECIFICATIONS		Body
Width	102" INBOARD	Tarp	NONE	Accessories
Side Height	66" SOLID	Bow Holders	NONE	
Top Rail	9" DUMP	Tarp Bows	NONE	
Side Mat'l-front	8' - .100 WALL	Tarp Basket	NONE	
-middle	23' - .140 WALL	Tarp Hooks	NONE	TAILGATE
-rear	6' - .180 WALL	Bulkhead Mat'l	3/16"	Height
Side Options	NONE	Bulkhead	D/S-MANDOOR (15)	Mat'l Thkness
Floor Mat'l	1/4" FULL LENGTH	Options	5" SLOPE PLATES	Slope
Crsmbr Spacing	12"	Body Fenders	SQUARED OFF	Hinges
Floor Options	STUB LONGITUDINALS	Ladders (Out)	D/S-REAR	Side Swing
Tailgate Control	AIR / FRAME + ELEC CC (4)	Inside	NONE	Gateseal
Body Pkg	NONE (17)	Shovel Hgr	D/S-FRAME	Safety Latch
Options		Light Panel	FULL - LED; X=LED B/U LIGHTS OOOX ooo XOOO	Coal/Grain Door
Vibrator	NONE	Marker Lights	LED - 14 PR TOP & BOTTOM	Coal Chute
Mudflaps	STD + ACROSS REAR (1)	MMTS	BELOW RAIL - LED	Gate Options
		Apron	NONE	

CHASSIS SPECIFICATIONS

Model	TRIAxLE-2 FIXED-FRONT LIFT	ABS	2S/1M	Tire Carrier	NONE
Beam Mat'l	ALUMINUM			Landing Gear	2 SPEED JOST AX150 D/S CRANK
Length	36' 6" FLUSH MOUNT			Chassis Lights	NONE
Width	102"	Independ. Susp(s)		Elec Coupler	7 WAY + ISO 7 WAY LABELED 'AUXILIARY'
Hoist	85-285 (2)(12)	Distance:		Hyd Tank	NONE
Chassis Neck	STD	From:		Hyd Hose Fitting	WINGNUT
King Pin Setting	18"	Controls		Hyd Hose Length	108"
5th Whl Plate	3/8" W/ 3/8"X 3" X 7" MOUNT	Location		Tow Hooks	TWO-ONE EACH SIDE
5th Whl Ht	50"	Axle(s)		Paint	BLACK SOFTCOAT
Overhang	6"	Accessories			NONE
Rear Axle Setting	21.5"	Brakes		Chassis	CHASSIS REAR CM: TAPERED
K/P To Rear Axle	398.5"	Drums		Options:	W/ DIAMOND PLATE COVER
Suspension	AAT30K / E3-2 L LIFT-E1 (3)(5)	Hubs			REMARK (13)(14)
Susp Control	FRAME + ELEC CC (4)(10)	Wheels			86,000 GVWR
Susp Spacing	52" - 52" (6) (16)	Tires			
Susp Options	GALVANIZED HANGERS				
Springs	AIR				
Axles	TP SPINDLES				
Accessories	NONE				
Brakes	HENDRICKSON MAXX 22T				
Drums	N/A				
Hubs	10 STUD STEEL - PILOT W/ HXL-5; GREASED HUBS				
Wheels	8.25 x 24.5 6 HP/ 6 MP				
Tires	11R 24.5 R268 16 PLY BS (11)				

REMARKS: - PRICE SUBJECT TO CHANGE 12 WEEKS PRIOR TO BUILD DATE

1. BLACK RUBBER FLAP AHEAD OF AXLE #1 IN THE CENTER.-MUDFLAP 4" FORWARD OF STANDARD POSITION.
2. REMOTE GREASE ZERK FROM TOP PIN TO BOTTOM D/S FACING FORWARD.
3. RIGHT WEIGH OIL FILLED GAUGE (LBS.)(FLUSH MOUNT) ON FRONT CHASSIS CROSSMEMBER.
4. WIRED TO AUXILIARY ISO 7 WAY PLUG
5. HEIGHT CONTROL VALVE ON AXLE #2.
6. LIFT AXLE TO BE CONTROLLED THROUGH FRAME SWITCH & ELEC CC (WIRED TO AUX. PLUG) AND TO HAVE BRAKE RELEASE (LIFT AXLE TO SPIN FREELY).
7. ALL FRAME SWITCHES TO BE IN POLYCARBONATE BOX ON D/S NEAR LANDING GEAR.
8. PLASTIC INSULATORS BETWEEN WHEEL/DRUM & WHEEL/HUB ALL AXLES.
9. REMOTE GREASE ZERKS FOR LATCH BAR
10. LED BACK UP WORK LIGHTS BOXED IN & ANGLED JUST REAR OF MMTS WIRED TO OTHER B/U LIGHTS AND HAVE A FRAME SWITCH (NEAR BOX
11. TIREMAXX PRO INFLATION SYSTEM ON ALL THREE AXLES
12. NO ACCESS ON OUTSIDE OF BULKHEAD OR FLAP, ACCESS ONLY ON DOGHOUSE IN INSIDE.
13. HINGE SHOE GREASE ZERKS-REMOTE ZERKS TO D/S MANIFOLD
14. REAR PIN BUSHING LUBE-REMOTE GREASE ZERKS TO D/S MANIFOLD
15. 073-20176-01 - HALE KNURLED MANDOOR STEP
16. 86,000 GVWR RATING
17. ALL EAST LOGOS TO BE DECALS ONLY-NOT RIVETTED OR WELDED

DISCLAIMER

Specifications are believed to be correct, but may contain errors and/or omissions. Photographs are the representative of the subject equipment but may not be identical.
Equipment availability, prices and specifications are subject to change without notice.