



Hale Trailer Brake & Wheel 020375-020379

OVERALL LENGTH 48FT 3Axle GVWR 100,000LBS
OVERALL WIDTH 8' 6" - 48ft
OVERALL HEIGHT FRONT 13'-3" = Flat Top Tarp System Included in Height
UPPER COUPLER HEIGHT 48"
UPPER COUPLER PLATE 3/8" Plate
KING PIN SETTING 36"
SWING CLEARANCE 90"= 36KP
LANDING GEAR Two Speed
No Undercoat On Landing Gear, Paint Black.
SUSPENSIONS Air Ride - Hendrickson Intraax 25K - Fixed (Manual Dump)
Air Gauge At Nose Roadside.
SUSPENSION LOCATION Set at Rear Most Position
AXLES (3) 25K Capacity - Type 30 Chambers - Auto Slacks - ABS - Air Ride
AXLE SPACING 61" Spread
LIFT AXLE Air Lift Rear Axle - Air Ride
WHEELS Disc - Hub Piloted-24.5- (6) Steel Inner & (6) Polish ALum (3AX)
TIRES 11R24.5 General RA 16 PLY
FRONT TYPE 10" Diagonal
FRONT MATERIAL Aluminum .063 - Pre Painted Black Aluminum
LADDERS Steel Platform
REAR DOOR TYPE Heavy Duty Dry Van Style Door
Quad Door Locks.
Stainless Steel Door Hardware.
REAR DOOR MATERIAL Galv./Quilted Stainless Steel Plywood
SIDE SHEET MATERIAL .063 Aluminum Smooth
INTERIOR LINING Interior Liner for 45' to 53' .145 Gator Plate
SIDE SHEET COLOR Black - Pre-Painted
SIDE POST Extruded Aluminum on 12" Centers
Half Round Post.
LOWER RAIL Heavy Duty Aluminum Lower Rail
FLOOR KeithWalkFloorSyst,3-1/2",7/32"2190Deck,Alum.Sub,48'-102WD
3.5" Drive Unit With 24" Wear Pads.
Stainless Steel Hydraulic Lines.
FLOOR SILLS 4" Alum. I-Beams between L.G.& Susp. & L.G.& 5th Wheel
SILL SPACING 8"/10"/8" Heavy Duty
Alum Sills On 8" Centers Between Fifth Wheel and Landing Gear.
Alum Sills On 10" Centers in Bay Area.

PARKING BRAKES All Axles
DUST SHEILDS None
ANTI-SAIL MUD FLAPS Behind Rear Axle
BUMPER H. D. 3" x 4" Push Bumper
****Stainless Steel Rear Frame.****
TARP SYSTEM None
**** (3) 6" Flat Sidewall Stiffeners.****
TARP COLOR None
LIGHTS Sealed Wiring Harness W/ LED PKG
****LED Back Up Lights Mounted in Bumper - Work Lights Inside Front - Wired to Front in Waterproof Switch.****
****5 Marker Lights Per Side Along Lower Rail.****
PAINT Black - Fifth Wheel and Landing Gear
GVWR 100K
GAWR 24.5K

DISCLAIMER

Specifications are believed to be correct, but may contain errors and/or omissions. Photographs are the representative of the subject equipment but may not be identical. Equipment availability, prices and specifications are subject to change without notice.