



**Hale Trailer Brake & Wheel  
020393-020398**

Base Model:CV45-96 Spring Ride  
components description  
CAPACITY 45FT 2Axle GVWR 66,290LBS  
OVERALL LENGTH 45'  
OVERALL WIDTH 8'  
OVERALL HEIGHT FRONT 13'-1" = Flat Top tarp system included in height  
UPPER COUPLER HEIGHT 48"  
UPPER COUPLER PLATE 5/16" Plate  
KING PIN SETTING 36"  
SWING CLEARANCE 90"= 36KP  
LANDING GEAR Two Speed  
SUSPENSIONS Spring Ride - Hutchens-2 Axle  
SUSPENSION LOCATION Set at Rear Most Position  
AXLES (2) 22,500K Capacity - Type 30 Chambers - Auto Slacks - ABS  
AXLE SPACING 49"  
LIFT AXLE None  
WHEELS Disc - Hub Piloted- 22.5- (-56#)  
TIRES 11R22.5-Manufacturer Choice  
FRONT TYPE 10" Diagonal  
FRONT MATERIAL Aluminum .050 - Pre Painted White Aluminum  
LADDERS Aluminum Nose Only  
REAR DOOR TYPE Heavy Duty Aluminum Top Hinged Chip Gate W/Wear Pads  
REAR DOOR MATERIAL Heavy Duty Galvanized Mesh  
SIDE SHEET MATERIAL .050 Aluminum - Smooth  
INTERIOR LINING None  
SIDE SHEET COLOR Pre-Painted White  
SIDE POST Extruded Aluminum on 16" Centers  
LOWER RAIL Heavy Duty Aluminum Lower Rail  
FLOOR Corr Fabricated Aluminum  
FLOOR SILLS 4" Steel - Wax-Dipped I-Beam w/ Undercoating  
SILL SPACING 12"/16"/12" STD  
DUST SHEILDS None  
ANTI-SAIL MUD FLAPS Behind Rear Axle  
BUMPER H. D. 3" x 4" Push Bumper

**TARP SYSTEM Shur-Co Flat Mesh Shur-Lok  
-Frt&RrCap-0Bows-22oz-2RidgeStraps-45'-102WD  
ADDITIONAL TARP BOWS None  
TARP COLOR BLACK  
LIGHTS Sealed Wiring Harness W/ LED PKG  
PAINT Silver - Ladder,Fifth Wheel, and Rear Frame  
Custom None**

**DISCLAIMER**

Specifications are believed to be correct, but may contain errors and/or omissions. Photographs are the representative of the subject equipment but may not be identical. Equipment availability, prices and specifications are subject to change without notice.