Hale Trailer Brake & Wheel
020418-020422

Base Model: CW45-102 Spring Fixed
components description
CAPACITY 45FT 2Axle GVWR 66,290LBS
OVERALL LENGTH 45'
OVERALL WIDTH 8' 6" - 45ft
OVERALL HEIGHT FRONT 13'-3" = 3" Bow Rise In Tarp System Included In Height
UPPER COUPLER HEIGHT 48"
UPPER COUPLER PLATE 5/16" Plate
KING PIN SETTING 36"
SWING CLEARENCE 90"= 36KP
LANDING GEAR Two Speed
SUSPENSIONS Spring Ride - Hutchens-2 Axle
SUSPENSION LOCATION Set at Rear Most Position
AXLES (2) 22,500K Capacity - Type 30 Chambers - Auto Slacks - ABS
AXLE SPACING 49"
LIFT AXLE None
WHEELS Disc - Hub Piloted- 22.5- (-56#)
TIRES 11R22.5-Manufacturer Choice
FRONT TYPE 10" Diagonal
FRONT MATERIAL Aluminum .050 - Pre Painted White Aluminum
LADDERS Aluminum Nose Only
REAR DOOR TYPE Heavy Duty Aluminum Barn Style Doors - Mesh
REAR DOOR MATERIAL Heavy Duty Galvanized Mesh
SIDE SHEET MATERIAL .050 Aluminum - Smooth
INTERIOR LINING None
SIDE SHEET COLOR Pre-Painted White
SIDE POST Extruded Aluminum on 12" Centers
Half-Round Post.
LOWER RAIL Heavy Duty Aluminum Lower Rail
FLOOR Install Customer Furnished Walking Floor
Keith 7/32" 24" Wear Pads.
FLOOR SILLS 4" Steel - Wax-Dipped I-Beam w/ Undercoating
SILL SPACING 12"/12"/12" Heavy Duty / Live Floor

DUST SHEILDS None
ANTI-SAIL MUD FLAPS Behind Rear Axle
BUMPER H. D. 3" x 4" Push Bumper
TARP SYSTEM Shur-Co 3"Arch Solid Shur-Lok
-Frt&RrCap-8Bows-22oz-2RidgeStraps-45'-102WD
3" Caps and Bows.
ADDITIONAL TARP BOWS None
TARP COLOR BLACK
LIGHTS Sealed Wiring Harness W/ LED PKG
PAINT Silver - Fifth Wheel, and Rear Frame
Custom None

DISCLAIMER

Specifications are believed to be correct, but may contain errors and/or omissions. Photographs are the representative of the subject equipment but may not be identical. Equipment availability, prices and specifications are subject to change without notice.