

## Hale Trailer Brake & Wheel 020445-020448



Base Model: CW43-102 components description

CAPACITY 43FT 2Axle GVWR 65,830LBS

OVERALL LENGTH 43' OVERALL WIDTH 8' 6"

OVERALL HEIGHT FRONT 12'-10"= 6" Bow Rise in tarp system included in height

\*\*Arched Cross Ties.\*\*

**UPPER COUPLER HEIGHT 48"** 

UPPER COUPLER PLATE 3/8" Plate

KING PIN SETTING 36"

SWING CLEARENCE 90"= 36KP

LANDING GEAR Two Speed - Holland Mark "V"

SUSPENSIONS Air Ride - Hendrickson Intraax 25K - Fixed

\*\*Auto Dump, Gladhand Activated.\*\*

SUSPENSION LOCATION Set at Rear Most Position

AXLES (2) 25K Capacity- Type 30 Chambers- Auto Slacks

**AXLE SPACING 49"** 

LIFT AXLE Front Axle With Manual Valve

WHEELS Disc - Hub Piloted- 22.5- (-56#)

TIRES 11R22.5 General RA 16 PLY

FRONT TYPE 10" Diagonal

\*\*Hinge Style Front Slope Sheet.\*\*

FRONT MATERIAL Aluminum .050 - Pre Painted Black

LADDERS Aluminum Nose Only

REAR DOOR TYPE Heavy Duty Dry Van Style Door

\*\*Quad Door Locks.\*\*

REAR DOOR MATERIAL Galv./Pre Painted Black- Composite

SIDE SHEET MATERIAL .050 Aluminum - Smooth

\*\*Last 2 Sheet .100 Customer Furnished.\*\*

INTERIOR LINING None

SIDE SHEET COLOR Black - Pre-Painted

SIDE POST Extruded Aluminum on 12" Centers

\*\*Half-Round Post.\*\*

LOWER RAIL Heavy Duty Aluminum Lower Rail

FLOOR Hallco Floor 6000Unit, 7/32 Slats Alum Sub Deck

\*\*24" Wear Pads. \*\*

FLOOR SILLS 4" Alum. I-Beams 12" ctrs between L.G.& Susp. & L.G.& 5th Wheel

SILL SPACING 12"/8"/12" Heavy Duty / Live Floor

**DUST SHEILDS 2 Axles** 

ANTI-SAIL MUD FLAPS Behind Rear Axle

BUMPER H. D. 3" x 4" Non-Push Bumper(Arched Header)

\*\*Arched Rear Header.\*\*

TARP SYSTEM Shur-Co 6"Arch Solid Shur-Lok -Frt&RrCap-8Bows-22oz-2RidgeStraps-45'-102WD

ADDITIONAL TARP BOWS None

TARP COLOR BLACK

LIGHTS Sealed Wiring Harness W/ LED PKG

PAINT Black - Fifth Wheel and Rear Frame

Custom Air Gauge D/S Corner

**24.5K GAWR** 

## DISCLAIMER