



# Hale Trailer Brake & Wheel 020449-020451

## X-L SPECIALIZED TRAILERS, INC.

OAL: 53'  
OAW: 102"

MODEL: XL 90 BM

DIST: 85,000# CLOSEI CONC.

WEIGHT+/-3%=-

### GOOSENECK-

LENGTH: 9'  
 KING PIN SETTING: 19"  
 SWING CLEARANCE: 77"  
 5TH WHEEL HEIGHT: 49"  
 LANDING GEAR: 2 SPEED LANDING GEAR - HANDLE ON CURSIDE  
 DROP LEGS FOR PARKING LOADED TRAILER  
 FENDERS: BOLT ON ALUMINUM FRONT FENDERS  
 D-RINGS: (2) D-RINGS ON FRONT  
 (2) D-RINGS PER SIDE - 4 TOTAL  
 (4) D-RINGS ON REAR OF GOOSENECK  
 PLATFORM: 48" LOADING PLATFORM ON FRONT  
 DECK HEIGHT: 57" DECK HEIGHT ON PLATFORM

### MAIN DECK-

LENGTH: OPENS TO 184' 2" WITH PULLOUT BUMPER  
 LOADED DECK HGT: 51"  
 PLATFORM: 18" STEEL PLATFORM AT REAR W/ 4 D-RINGS  
 MAIN FRAME: TELESCOPING MAIN FRAME ( 4 TOTAL SECTIONS )  
 FLAG HOLDERS: ( 3 ) PAIR OF FLAG HOLDERS  
 BUMPER: 20' PULLOUT BUMPER WITH STOPS ON 24" CENTERS - NON LOAD BEARING BUMPER  
 D-RINGS: ( 1 ) PAIR IN TAIL CHANNEL

### REAR DECK:

AXLES: ( 3 ) 25,000 NOMINAL, 80" TRACKING  
 SUSPENSION: HEND-TURNER / 25,000 AIR  
 AXLE SPACING: 71"  
 ABS: 2S1M SPRING BRAKES ON 1 AXLES  
 TIRES: 245/70R/17.5  
 WHEELS: 6.75 X 17.5 STEEL DISC WHEELS  
 BRAKES: 12 1/4" X 7 1/2"  
 DRUMS: HUB PILOT/ OUTBOARD DRUMS  
 ELECTRICAL: 12V SEALED GROTE SYSTEM WITH 3 TAILLIGHT PACKAGE  
 MUD FLAPS: MINIMIZER WHEEL COVER OVER EACH AXLE WITH MUDFLAP

### ADDITIONAL:

PAINT: RAISE AND LOWER VALVE  
 BLACK URETHANE WITH 2 PART EPOXY PRIMER  
 LIQUID FILLED AIR GAUGE  
 13HP HYDRAULIC POWER UNIT  
 LODAR REMOTE FOR STEERING  
 4" AMBER STROBE LIGHT TO BE USED AS 3RD TAIL LIGHT  
 (2) BUNK SECTIONS  
 (1) 48" ROLLING SECTION WITH 55" HEIGHT OVER REAR MOST BEAM ONLY  
 PSI TIRE INFLATION SYSTEM

#### DISCLAIMER

Specifications are believed to be correct, but may contain errors and/or omissions. Photographs are the representative of the subject equipment but may not be identical. Equipment availability, prices and specifications are subject to change without notice.