




# HALE TRAILER BRAKE & WHEEL



**A020536-A020543**  
**VINS: A4410-A4417**

## SALES | RENTALS | PARTS | SERVICE

<b>Allentown, PA:</b>	800-383-8894	<b>Jacksonville, FL:</b>	800-828-3055
<b>Baltimore, MD:</b>	888-601-7500	<b>Little Rock, AR:</b>	833-424-8944
<b>Boston, MA:</b>	800-854-5310	<b>Portland, ME:</b>	800-325-4253
<b>Concord, NC:</b>	800-438-2250	<b>Richmond, VA:</b>	866-839-3495
<b>Delmar, DE:</b>	866-486-1400	<b>Scranton, PA:</b>	800-569-1400
<b>Des Moines, IA:</b>	888-673-5011	<b>Springfield, MA:</b>	800-854-5306
<b>Elkton, MD:</b>	800-544-7127	<b>Voorhees, NJ:</b>	866-315-0235

HaleTrailer.com | @haletrailer     

**800-232-6535** \*FINANCING AVAILABLE

Workhorse 55 PVR (Model: WORKHORSE 55 PVR)	
	Est. Wt.: 23,480# +/- 3%
TRAILER - GENERAL	
<b>Capacity:</b> 50 tons in 12-foot length or 55 tons in 16-foot with 4 axles close coupled - GAWR and tire ratings determine legal payloads	
<b>Length (Trailer Only):</b> 53 feet 0 inches	
<b>Width:</b> 8 feet 6 inches	
<b>Compatibility:</b> Designed to Accept Optional 51/60 Rear Axle	
GOOSENECK	
<b>Gooseneck Design:</b> Narrow hydraulic removable non-ground bearing - swing radius of 102 inches (11ft 7in overall gooseneck length) set up for wetline operation	
<b>Loaded Fifth Wheel Height:</b> Dual Cam Pawl Arm Assembly with 7 ride height positions (50 inches nominal)	
<b>Kingpin:</b> Kingpin at 102 inch radius	
<b>Power Source:</b> Set Up for Wet Line Operation	
<b>Tool Box:</b> Open storage area located in back of gooseneck with chain bar	
<b>Hydraulic Fittings:</b> OEM Standard 1/2 inch	
DECK	
<b>Framework:</b> All Main Longitudinal Members Fabricated with 100,000# Minimum Yield Steel Flanges with 50,000# Webs	
<b>Deck Design:</b> Flat level deck design (tapered beam design)	
<b>Deck Length:</b> 24 feet 0 inches Clear Deck Length	
<b>Loaded Deck Height:</b> 22 inches with 6 inches Ground Clearance	
<b>Crossmembers:</b> On 22 inch Centers (Nominal)	
<b>Flooring:</b> 1.5 inch nominal apitong wood (full width)	
<b>Front Ramps:</b> Apitong Wood Filled Double Hinged Adjustable Width to 44 inches inside to inside (9 degree load angle)	
<b>Extension Brackets:</b> None (mounting brackets included for later installation)	
<b>Tool Box:</b> Preforated plate under hammer plate forming one storage area (Storage area not accessible when covered rear bogie is in place)	
<b>Hammer Plate:</b> Hammer Plate installed over recessed crossmembers. Preforated plate under hammer plate forming one storage area; includes 1 pair of D rings (Hammer Plate not accessible when covered rear bogie is in place)	
REAR BRIDGE	
<b>Front Bogie Ramp:</b> Sloped (16 degree angle)	
<b>Boom Trough:</b> Low Boom Well, with V crossmember with bolt-in V pan	
<b>Deck to Bogie Connection:</b> Fixed w/ ramps outboard mainbeams, apitong wood filled	
<b>Bolsters:</b> Recessed	
<b>Covered Rear Bogie:</b> Load Bearing Wheel Covers- Apitong Wood Filled with center insert for full width loading (insert has 2-point lift capability; bolts in	
<b>Rear Bogie Height:</b> 43 inches	
<b>Connections for Future Axle Attachment:</b> Air and Electrical Connections to Go Along with Connecting Ears	
<b>Accent Package:</b> None	
AXLES	
<b>Number of Axles:</b> 3	
<b>Axle Capacity:</b> 22,500 lb. nominal capacity per axle NOTE: GAWR determined by suspension type, brakes, tires and other components.	

<b>Axle Spread:</b> 54.5 inches (Between Axles)	
<b>Brakes:</b> 16.5 inches x 7 inches with 5.5 inches Autoslacks - Heavy Duty Brake Drums - Outboard Mount	
<b>Spring Brakes:</b> Spring brakes on axle 2	
<b>Dust Shields:</b> None	
<b>Hubodometer:</b> None	
<b>SUSPENSION</b>	
<b>Suspension:</b> Air Ride	
<b>ABS:</b> None	
<b>Third Lift Axle:</b> Air Lift Installed on Third Axle	
<b>Chain Lift:</b> First Axle (acts as a limit chains)	
<b>Override Chains:</b> Override Chains Axle 2 & 3	
<b>Ride Height Control:</b> 7-position mechanical ride height control system	
<b>Dump Valve:</b> Automatic/Manual Raise/Lower Control	
<b>Liquid Filled Gauge:</b> None	
<b>Load Scale:</b> None Standard	
<b>WHEELS AND TIRES</b>	
<b>Wheels:</b> 8.25 x 22.5 Steel Disc - Hub-Piloted	
<b>Tires:</b> 255/70R 22.5 H Ply OEM Standard	
<b>Tire Inflation System:</b> None	
<b>Hubodometer:</b> None Standard	
<b>Tire Inflation:</b> None Standard	
<b>LIGHTING</b>	
<b>Electrical System:</b> DOT Sealed Beam and Harness with LED Lights and 4-inch Flush Mounted Battery Powered Amber Strobes	
<b>Tail Lights:</b> 3 Tail Light Package	
<b>Marker Lights:</b> 3 Marker Lights Per Side Including Mid-Turn	
<b>Electrical Receptacle:</b> J560 7-Pin Connector	
<b>Additional Marker Lights:</b> None Standard	
<b>PAINT</b>	
<b>Paint:</b> Fontaine Black Polyurethane Enamel	
<b>MISCELLANEOUS</b>	
<b>Lash Rings:</b> 17 Pair - 34 Total	
<b>Flag Holders:</b> 2 Pair Flag Holders	
<b>VIN Plate:</b> Bilingual VIN Plate	
<b>Registration/Document Holder:</b> Registration/document holder installed	

DISCLAIMER

Specifications are believed to be correct, but may contain errors and/or omissions. Photographs are the representative of the subject equipment but may not be identical.  
Equipment availability, prices and specifications are subject to change without notice.