

# HALE TRAILER


BRAKE & WHEEL



A020671-A020674  
VIN: 74428-74431

## SALES | RENTALS | PARTS | SERVICE

<b>Allentown, PA:</b>	800-383-8894	<b>Jacksonville, FL:</b>	800-828-3055
<b>Baltimore, MD:</b>	888-601-7500	<b>Little Rock, AR:</b>	833-424-8944
<b>Boston, MA:</b>	800-854-5310	<b>Portland, ME:</b>	800-325-4253
<b>Concord, NC:</b>	800-438-2250	<b>Richmond, VA:</b>	866-839-3495
<b>Delmar, DE:</b>	866-486-1400	<b>Scranton, PA:</b>	800-569-1400
<b>Des Moines, IA:</b>	888-673-5011	<b>Springfield, MA:</b>	800-854-5306
<b>Elkton, MD:</b>	800-544-7127	<b>Voorhees, NJ:</b>	866-315-0235

HaleTrailer.com | @haletrailer     

**800-232-6535** \*FINANCING AVAILABLE

## CHIPPER

Model # TNAR44FR920-2025

**Weight** 13281 lbs. \*\*\* **Cubic Yards** 98

### BODY

LOAD PROFILE	MATERIAL, 80K GVWR	0.0
LENGTH	44	
WIDTH	102	
DRIVE UNIT	KEITH, 25 SLAT 3-1/2 IN. CYLINDER (HEAVY DUTY)	
	keith 26 slat drive 2293 horizontal seal 3 1/2 cyl	
FLOOR	KEITH 2190 (1975), 7/32 IN. (102 W)	
	ADD 24 INCH WEAR STRIPS TO END OF SLATS	
HYDRAULIC PIPE	STAINLESS STEEL HYDRAULIC PIPE	
CROSSMEMBER TYPE	HEAVY FULL	
CROSSMEMBER SPACING	5-1/4 IN. I-BEAMS, 12 O.C.	
RUBBER SEAL	NONE	
WALL HEIGHT	92	
FRONT WALL THICKNESS	.062	
	ALL BLACK PREPAINTED PANELS	
MID WALL THICKNESS	.062	
REAR WALL THICKNESS	.062	
	LAST SHEET AT REAR TO BE .125" THICKNESS	
FULL LID	NONE	
TOP RAIL OPTION	STD TOP RAIL	
	<b>STD TOP RAIL</b>	
UPRIGHT SPACING	14 IN.	0.0
	12" UPRIGHT SPACING	
ADDITIONAL UPRIGHTS AT FRONT	NO	0.5
BULKHEAD	.165	
BULKHEAD STEPS	LADDER ONLY	
	16" WIDE LADDER	
FRONT FENDERS WITH FLAPS	NONE	
BOTTOM RAIL	SQUARE NO CLEAN OUT	
UPPER CROSS TUBES / ARCH	6	0.0
	USE ONLY 3 CROSS TUBES (ROLLED GALVANIZED CROSSTUBES) BETWEEN FRONT AND REAR CAPS	
FRONT CAP	YES	0.0
	W/ GRAB HANDLE	
REAR CAP	NO	0.5
TIRE CARRIER	(1) IN MIDDLE ONLY	

### LIGHTS

LIGHT TYPE	TRUCKLITE L.E.D. W/ GROMMET
LIGHT PANEL	4 LARGE-3 SMALL-4 LARGE (SPLIT LIGHT PANEL) OOOO ooo OOOO

APRON	NONE	
STD. MARKER LIGHTS	(5) EACH SIDE	0.0
	(7) PER SIDE TOP & BOTTOM PENNY LIGHTS.	2.3
MID-TURNS	(1) PAIR L.E.D. (COMBO)	
BACK-UP LIGHTS	(1) PAIR L.E.D. BACK UP LIGHTS	0.0
	ADD ONE PAIR OF WORKLIGHTS TO INSIDE FRONT - TO BE DUAL STOP/WORK LIGHT COMBO 4" LIGHT . WIRE TO FRONT ON TARP SWITCH - ADD RED INDICATOR LIGHT WHEN WORKLIGHTS ARE ON	1.0
AUXILIARY CABLE	7 WAY (ISO)	
	B/U ON BLACK MAIN	
REAR POCKET LIGHTS	(1) PAIR	

## GATE

GATE OPERATION	BI-FOLD	0.0
	SWING DOORS - QUAD LOCKS	1.0
GATE OPTIONS	SOLID .080	
	BLACK DURAPLATE	
HINGE TYPE	BARN DOORS SIDE SWING (ALUM.)	0.0
	S/S HINGES	0.5
SAFETY CHAIN	YES	
WINDERS / SAFETY LATCH	NONE	
GATE STEPS	NONE	
TARP HOOKS	NONE	

## PRIMARY AXLES

MODEL	CLOSED TANDEM	0.0
	ADDED CROSSMEMBER GUSSETS OVER SUB FRAME AREA	1.0
NO. OF PRIMARY AXLES	1	
SUSPENSION	HEND. INTRAAX AA-250 TP - 25K (77.5)	
	GAWR 24K	
AXLE SPACING	60	
	REAR AXLE SET AT 60"	
SUB-FRAME	TANDEM (ALUM T-BEAM)	
AXLES	AXLE FOR INTRAAX ONLY	
BRAKES	DISC BRAKES - HEND. MAXX22T W/ DUCTILE STEEL HUB (23,000 LB ONLY)	
CAM GUARDS	NONE	
HUB AND DRUM	NONE, DISC BRAKES	
TIRES	GOODYEAR MARATHON RSS 11R 22.5 16 PLY	
WHEELS	ALUMINUM HP 22.5X8.25 - ALL POLISHED (XP)	

## LIFT AXLES

NO. OF LIFT AXLES	1	
LIFT AXLE SUSPENSION	HEND. INTRAAX AAL-25K (77.5)	
LIFT KIT	HEND. UBL-002 (INTRAAX AAL)	
LIFT AXLE DISTANCE	60	
LIFT AXLE	AXLE FOR INTRAAX ONLY	
LIFT AXLE BRAKES	DISC BRAKES - HEND. MAXX22T W/ DUCTILE STEEL HUB (23,000 LB ONLY)	
LIFT AXLE CAM GUARDS	NONE	
LIFT AXLE HUB AND DRUM	NONE, DISC BRAKES	
LIFT AXLE TIRES	GOODYEAR MARATHON RSS 11R 22.5 16 PLY	
LIFT AXLE WHEELS	ALUMINUM HP 22.5X8.25 - ALL POLISHED (XP)	
LIFT AXLE CONTROLS	AIR IN CAB & BALL VALVE NO/ REG.	
	W/ AUTO LIFT	
FREE WHEEL VALVE	NONE	

## STEERABLE LIFT AXLES

NO. OF STEERABLE AXLES	0	
STEERABLE AXLE SUSPENSION	NONE	
STEERABLE AXLE DISTANCE	N/A	
STEERABLE AXLES	NONE	

STEERABLE AXLE BRAKES	NONE
STEERABLE AXLE HUB AND DRUMS	NONE
STEERABLE AXLE TIRES	NONE
STEERABLE AXLE WHEELS	NONE
STEERABLE AXLE CONTROLS	NONE
STEERABLE AXLE LIFT KIT	NONE

### CHASSIS

PIN SETTING	36	
5TH WHEEL PLATE	3/8 LOW PROFILE GALVANIZED	
5TH WHEEL PLATE HEIGHT	48 IN. HIGH	
GALVANIZED SUSPENSION HANGERS	INCLUDED W/ SUSPENSION	
SUSPENSION CONTROL	ELECTRIC THRU AUX. & BALL VALVE	
QUICK RELEASE GLADHANDS		
ABS FOR TRAILER	(1) 2S1M MERITOR / WABCO	
SLACKS	AUTOMATIC	
TIRE INFLATION SYSTEM	NONE	
AXLE LUBRICATION	5 YR. SYNTHETIC GREASE	
HUBODOMETER	NONE	
DUST COVERS	NONE	
DOLLIES - LANDING GEAR - LANDING LEGS	JOST A451 - (62,500 LB.) - 10 YEAR NO LUBE - STEEL - (REVERSE MOUNT) D.S.	
ADD ONE PAIR OF WORKLIGHTS NEAR DOLLIES. WIRE TO FRONT ON TARP SWITCH - ADD RED INDICATOR LIGHT WHEN WORKLIGHTS ARE ON		1.0
REGISTRATION HOLDER	BETTS PS-1 W/ SIGHT GLASS (ROUND HOLDER)	
AIR GAUGE / SYSTEM	YES, IN FRONT	
ENCLOSURE FOR SWITCHES	NONE	
AIR TANKS	12 IN. ALUMINUM TANK	
HYDRAULIC HOSE FITTING	1 IN. X 108 IN. HOSE W/ WING FITTING	
RUN HYDRAULIC PIPE OUT THE COUPLER TO 45 DEGREE FITTINGS AND HOSES, WINGED COUPLERS 3/4" ON RETURN AND 1" ON PRESSURE - REF PIC FOR HOSE, LADDER & ELECTRICAL SET UP		
FLAPS FRONT OF TIRES	NONE	
FLAPS REAR OF TIRES	FLAP BEHIND REAR AXLE	
BUMPER	D.O.T. BUMPER	0.0
TRACTION TAPE ON "STEP" PORTIONS OF BUMPER - ADD STIRRUP STEP		1.0

### TARP

TARP MANUFACTURER	NONE
ROLL RITE STS ELECTRIC SIDE ROLL TARP SYSTEM	
TARP CONTROL	NONE
TARP COLOR	NONE
TARP BRACKET	NONE

### PAINT

SUSPENSION COLOR	BLACK SOFT COAT
PIN STRIPING	BLACK (931716)

#### DISCLAIMER

Specifications are believed to be correct, but may contain errors and/or omissions. Photographs are the representative of the subject equipment but may not be identical. Equipment availability, prices and specifications are subject to change without notice.