

XL SPECIALIZED TRAILERS

XL 90 HDGS: Mini-Deck

OVERALL LENGTH OVERALL WIDTH CAPACITY WEIGHT +/- 3%

102" 90,000 LB DISTRIBUTED; 90,000 LB IN 16" 0,000 LB

LOW-PROFILE SCRAPER NECK

53'

GOOSENECK

NECK STYLE LENGTH KINGPIN SETTING SWING CLEARANCE 5TH WHEEL HEIGHT HYDRAULICS DECKING DENRINGS FLIP NECK

11' 16' 86' 49'W/5 VARIABLE RIDE HEIGHT POSITIONS 13HP HONDA SCU, DUAL HYDRAULICS WITH ALUMINUM COVER 1 //8' APITONG DECKING, FLUSH (2) BENT D-RINGS PER SIDE PREP FOR 38' FLIP NECK EXTENSION 36' FLIP NECK EXTENSION

MAIN DECK

LENGTH LOADED DECK HEIGHT DECKING

CROSSMEMBER

BEAMS

D-RINGS

RAMPS

AXLES SUSPENSION AXLE SPACING ABS TIRES BRAKES DRUMS ELECTRICAL DECKING D-RINGS D-RINGS

OUTRIGGERS

3 BEAM DESIGN 33' WITH 32' 6' CLEAR DECK 13' W 4' GROUND CLEARANCE STEEL DECKING BETWEEN MAIN BEAMS WITH DURABAK 1 3/8' APITONG DECKING, RAISED BETWEEN MAIN BEAMS AND OUTER BEAMS 6' & 4' JR. I-BEAMS ON 12' CENTERS MID-HEADER IN MAIN DECK (3) 9' FAB BEAMS (12) BENT D-RINGS PER SIDE NONE TAPERS TO 4''

REAR DECK LENGTH LOADED DECK HE

	9'
k height	40"
	(2) 25,000 LBS NOMINAL, (5/8" WALL)
	HENDRICKSON / 25,000 CAPACITY / AIR RIDE
G	54"
	4S2M WITH SPRING BRAKES ON (2) AXLES
	255 / 70R / 22.5 (H)
	8.25 X 22.5 10-HOLE PILOT MOUNT POLISHED ALUMINUM OUTSIDE, STEEL INSIDE DISC
	16 1/2" X 7"
	OUTBOARD
	12V SEALED GROTE SYSTEM WITH (3) TAILLIGHT ALUMINUM PACKAGE
	4" AMBER STROBE TO BE USED AS 3RD TAILLIGHT
	1 1/8" APITONG DECKING FLUSH
	(1) PAN STYLE D-RINGS IN EACH CORNER
	(2) BENT D-RINGS IN TAIL CHANNEL

ADDITIONAL

PAINT

MANUAL RIDE HEIGHT CONTROL PREP FOR (2) FLIP AXLES RAISE AND LOWER VALVE LIQUID FILLED AIR GAUGE WITH CHART 4-WAY PLUG AT REAR

SIMILAR TO 22630

BLACK

TO FIT TO 22 FA 22631

DISCLAIMER