

HALE

TRAILER

BRAKE & WHEEL



HT Original®

Resale Inventory
A021063-A021091
VIN: 068001-068030

SALES | RENTALS | PARTS | SERVICE

Allentown, PA: 800-383-8894	Jacksonville, FL: 800-828-3055
Baltimore, MD: 888-601-7500	Little Rock, AR: 833-424-8944
Boston, MA: 800-854-5310	Portland, ME: 800-325-4253
Concord, NC: 800-438-2250	Richmond, VA: 866-839-3495
Delmar, DE: 866-486-1400	Scranton, PA: 800-569-1400
Des Moines, IA: 888-673-5011	Springfield, MA: 800-854-5306
Elkton, MD: 800-544-7127	Voorhees, NJ: 866-315-0235

HaleTrailer.com | @haletrailer

800-232-6535 *FINANCING AVAILABLE

DRY FREIGHT EXTERIOR SKIN 53'

LENGTH EXTERIOR.	53' 0"		
-INT.	52'-6"		
WIDTH -EXT.	102.36"		
-INT.	98.75"		
HEIGHT -EXT.	13'-6"		
-INT.	110"		
UPPER COUPLER HT.	47"		
KING PIN LOCATION	36"		

TIRES

TYPE	MICHELIN XTE X-ONE	REV. 1	
SIZE	445/50 R 22.5 (G)	X	

ROOF

ROOF SHEET	.075" KEMLITE ETR TRANSLUCENT	X	
ROOF BOW TYPE	ALUMINUM	X	
ROOF BOW SPACING	16" CENTERS FULL LENGTH	X	

FRONT

CORNER RADIUS	6" ALUMINUM		
FRONT SHEETS	.050" PPW ALUMINUM		
FRONT UPRIGHTS	(4) 2.5" DEEP STL HATS WELD TO U.C.	X	
GLADHANDS	PHILLIPS QWIK-E W/FILTERS	X	
REG. CARDHOLDER	JAMES KING #350 ON LOWER ROAD SIDE FRONT	X	

SIDEWALL

SIDE MATERIAL	.050" PREPAINTED WHITE ALUMINUM		
SIDE UPRIGHTS	1.13" DEEP ALUMINUM HAT POSTS	X	
UPRIGHT CENTERS	12" CENTERS THROUGHOUT	X	

FORWARD & UPPER COUPLER AREA

UPPER COUPLER	3.40" JOGGLED W/ 52.25" EXPOSED. PRIME PAINTED ONLY.		
APPROACH PLATE	.25" THICK 80,000 LB YIELD. 2 EXTRA LONGTUDINALS		
BOTTOM MAINBEAM PL	.25" THICK 80,000 LB YIELD		
FORWARD XMEMBERS	HAT SHAPED: U.C. TO SUPP. GEAR		
SUPPORT GEAR	JOST 401G317-28 W/7 CROSSMEMBER MOUNT	REV. 2	
SHOES	10" X 10" LOW PROFILE CUSHION FOOT		
LOCATION	95" C/L SUPP. GEAR TO C/L KING PIN	X	
CRANK HANDLE	ROADSIDE		
BAY AREA XMEMBERS	4" ALUMINUM I-BEAMS	X	
XMEMBER CENTERS	BAY: 8" C/L & FORWARD AREA: 10" C/L	X	
TIRE CARRIER	NONE		

UPPER RUNNING GEAR AREA

U.R.G. XMEMBERS	3" STEEL I-BEAMS	X	
XMEMBER CENTERS	8" C/L	X	
U. R.G. RAILS	216" RAIL LENGTH (65"-169")		
SLIDER ASSEMBLY	HOLLAND ULTRA LITE 2	X	
MUDFLAPS	PLASTIC W/ HYUNDAI LOGO		

LOWER RUNNING GEAR AREA

SUSPENSION	HOLLAND ULTRA-LITE 2 (2" OFF SET)	X	
SPRINGS	MERITOR SIMILAIR COMPOSITE SPRING	X	
BRAKE SYSTEM	SEALCO #110500 VALVE W/WABCO 2S/1M ABS		
CHAMBERS	TSE 3030 COMBINATION CHAMBER W/CLAMP BAND ON SERVICE CHAMBER	X	
BRAKES	16.5" x 7" MERITOR MA212		
AXLES	MERITOR TP4670Q .50" WALL 77.50" TRACK FOR 2" OFF SET 'P' SPINDLE	X	

BRAKE ADJUSTERS	GUNITE AUTO - 5.50"		
HUB & DRUM	10 STUD HUB PILOTED OUTBOARD MTD CENTRIFUSE DRUMS 'P' SPINDLE	X	
WHEELS	22.5 x 14.00 ACCURIDE ALUM DISC (MILL FINISHED)	X	
OIL SEALS	STEMCO PLATINUM PERFORMANCE SYSTEM OIL FOR 'P' SPINDLE	X	

HUBODOMETER	NONE		
REAR			
HEADER	2" SHALLOW HEADER (110" DOOR OPENING HEIGHT)	X	
REAR DOOR TYPE	WHITING INNOVATOR II LIGHTWEIGHT SWING DOOR	X	
REAR DOOR MAT'L	WHITING HONEY COMB	X	
LOCK RODS	BLOXWICH, 1 PER DOOR WITH MID-CAM LOCK	X	
HINGES	ALUMINUM, 4 PER DOOR		
UNDERRIDE PROTECTIO	4" x 4" TUBE, HOT DIPPED GALVANIZED STEEL W/DOCK LOCK BRACING	X	
RUBBER BUMPERS	1 PR. 2" X 4" RUBBER BLOCKS		
LINING			
SIDE LINING	1 ROW X 12" HIGH HD. EXTRUDED ALUM SCUFF (NOMINAL 3/16") AT FLOOR LEVEL WITH 2 ROWS X 12" HIGH - TOTAL 24" HIGH STANDARD DUTY (NOMINAL 1/8") CORRUGATED ALUM SCUFF IMMEDIATLEY ABOVE FIRST ROW, TOTAL 36" HIGH EXTRUDED ALUM SCUFF. .060" KEMLITE L1062 REMAINDER. LINING MUST BE "TUCKED" BEHIND SCUFFBAND	REV. 3	
SIDE SCUFFBAND	NONE	X	
NOSE LINING	1 ROW X 12" HIGH HD. EXTRUDED ALUM SCUFF (NOMINAL 3/16") AT FLOOR LEVEL WITH 2 ROWS X 12" HIGH - TOTAL 24" HIGH STANDARD DUTY (NOMINAL 1/8") CORRUGATED ALUM SCUFF IMMEDIATLEY ABOVE FIRST ROW, TOTAL 36" HIGH EXTRUDED ALUM SCUFF. .060" KEMLITE L1062 REMAINDER. LINING MUST BE "TUCKED" BEHIND SCUFF BAND	REV. 3	
FRONT SCUFFBAND	NONE		
CEILING LINING	NONE		
FLOOR			
FLOOR	1-3/16" HAVCO COMPOSITE	X	
FLOOR SCREWS	(3).31" DIA.SCREWS/BOARD/XMBER		
THRESHOLD PLATE	.13" X 20" STL DIA.PLT. PRIMED	X	
ELECTRICAL			
LIGHTS	SEE ITEM # 4	X	
MID-TURN SIGNAL	SEE ITEM # 4	X	
ELECTRICAL CONN.	PHILLIPS 7-WAY WITH CIRCUIT BREAKERS	X	
LOCATION	OVERLAID ON LOWER ROADSIDE FRONT		
PAINT & FINISH			
UNDERCARRIAGE	BLACK UNDERCOATING		
CHASSIS & SUPP GEAR	GRAY		
REAR FRAME	HOT DIPPED GALVANIZED STEEL REAR FRAME & BUCKPLATE		
WHEELS	MILL FINISHED ALUMINUM	X	
DECALS	CONSPICUITY TAPE - HYUNDAI LOGO TYPE - SIDE TAPE TO BE MOUNTED ON SIDE SHEETS		
INSPECTION DECAL	FHWA INSTALLED		
TEMP LIFT PADS	NONE		
1 TEMPORARY LICENSE PLATE FOR TRANSPORT. FASTEN WITH NUT & BOLT			
2 Hot Dipped Galvanized Support Gear Bracing and Wing Plates			
3 Rear lower side marker lights to be approx. flush with bottom rail.			
4 All marker lights to be Trucklite LED #33 including rear header and ABS Locate lights 2 upper front rail & 2 upper side rail Bottom rail center light to be wired as combination marker & turn signal. Grote Stop, Tail, Turn signals			
5 Meritor PSI Tire Inflation System			
6 Delete rubber door stops on rear doors.			
7 Install rear door hinges with camtainers to allow doors to open as close to sidewall as possible			
8 Delete galv. Front corner lining and install alum pre-painted white corner lining			
9 Rear dock Height not to be less than 47".			
10 Note: Versitex lining to be fastened and glued to uprights. Fasteners to be as flush as possible to lining so not to snag cargo			
11 Stainless Steel front impact guard with stainless steel impact striker angle			
12 DELETE Customer Furnished unit numbers inside and outside. Location to be determined per Customer Furnished Schematic 13			
Delete the air hose line guide mounting bracket			
14 Eliminate the center section of the mud flap bracket			
15 Install carriage bolts on the threshold plate corners			
16 Target weight: 12,820 lbs or less			
17 Similar to 3-5198			

DISCLAIMER

Specifications are for the equipment at the time it was produced and may not accurately reflect its current condition. Photographs are the representative of the subject equipment but may not be identical. Equipment availability, prices and specifications are subject to change without notice.