

HALE

TRAILER

BRAKE & WHEEL



A021439-A021447



VIN: 468001-468009

SALES | RENTALS | PARTS | SERVICE

Allentown, PA:	800-383-8894	Jacksonville, FL:	800-828-3055
Baltimore, MD:	888-601-7500	Little Rock, AR:	833-424-8944
Boston, MA:	800-854-5310	Portland, ME:	800-325-4253
Concord, NC:	800-438-2250	Richmond, VA:	866-839-3495
Delmar, DE:	866-486-1400	Scranton, PA:	800-569-1400
Des Moines, IA:	888-673-5011	Springfield, MA:	800-854-5306
Elkton, MD:	800-544-7127	Voorhees, NJ:	866-315-0235

HaleTrailer.com | @haletrailer

800-232-6535 *FINANCING AVAILABLE

GVWR

GVWR:	Trailer to meet 68,000 Pound GVWR
* VIN PLATE:	Canadian/Transport Canada Compliant - VIN Plate to Read in English and French, Pounds and Kilograms
Product Type:	HT Thermotech-Truck Load w/Swing Door
Product Class:	HT Thermotech TL

GEOMETRY

Length - Exterior:	53'-0"
** Length - Interior:	52'-2"
Width - Exterior:	102.36"
** Width - Interior:	97.4"
Height - Exterior:	13'-6"
** Height - Interior:	105.5" Front
Deck Height:	Standard application
Fifth Wheel Height:	47"
King Pin Location:	36"
Landing Gear Location:	105" from King Pin (+ 1"/-1/4")

TIRES & WHEELS

Tire Furnished:	Factory Furnished
* Tire Manufacturer:	Hankook TL21(G), Low Rolling Resistance Tire
Tire Size:	295/75R22.5
Wheel Furnish:	Factory Furnished
Wheel Material:	All Steel Wheel
Wheel Manufacturer:	HT Standard (TCC 361)
Wheel Size:	8.25 x 22.5, 5-Hand Hole (Steel, Inner & Outer)
Wheel Finish for Steel:	Powder Coated White Steel Disc
Tire Stem Valve Position:	Dual Wheel Steel / Aluminum / Combo (STD 180°outboard & straight inboard)
Wheel Finish for Aluminum:	None (Due to All Steel Wheel Application)
Valve Stem & Cap:	Valve Stem & Metal Dome Cap

UPPER COUPLER

Upper Coupler-Reefer:	4.00" deep, Floor Over Coupler and Running to Front, Bolting Type
* Approach Plate:	5/16" thick 50,000 Lb Yield - 6 Support Channels
* King Pin (BTM Main) Plate:	5/16" thick 50,000 Lb Yield
King Pin & Manufacturer:	Standard (Jost) AAR Cruciform King Pin
Front Bottom Rail:	Stainless Steel & Stainless Steel Wrap-Around Impact Guard Striker Angle

BODY/BASE

Forward Crossmember:	4" Extruded Aluminum I-Beams: 12" C/L
* Landing Gear Crossmember:	4" Steel I-Beams (80,000 PSI) : 8" C/L (6" On Forward Edge : 7ea)
Bay Area Crossmember:	5.5" Extruded Aluminum I-Beams : 12" C/L
Running Gear Crossmember:	4" Steel I-Beams (80,000 PSI) : 12" C/L with 8" C/L Last 4' (For Reefer Van only)
Slider Body Rail (RV):	204" Rail Length
Slider Rail Supplier:	Hutchens Slider Rails
Slider Rail Duty:	Standard Duty
Slider Rail Hole Space & Dia.:	4" increments holes with large diameter holes (Hutch & Binkley)
* Tire Protect Plate:	Front-12 GA Galv steel x22"x55" long or the nearest XM/ Rear-12 GA Galv steel x22" x

length to cover entire running gear area (Snap in Type)
 * Tire Protect Install: Behind Upper Coupler & Tandem Area at Both Side
 * Fuel Tank Location: One Mounted behind Landing Gear, with fuel line conduit thru landing gear, forward & UC
 * Fuel Tank Furnish: Customer Furnished Thermoking Fuel Tank
 Fuel Tank Size: 50 Gal and 22" Diameter
 Fuel Tank Install: Cap to be 8" inboard from bottom rail (MFC's Recommended STD)
 Fuel Tank MT'G Method: Manufacturer's Recommended MT'G

FLOOR
 Floor- Assembly Method: Aluminum Floor Assembly with Weld (MIG). Seams to be Continuously / Uniformly Weld
 * Floor-Detail Spec. - RV: 1.34" Extruded Aluminum (6061-T6) NW Flat Floor
 Floor-Surface Spec. - RV: Ridged Floor Surface with Safety Grip (Knurled)
 * Rear Gutter & Trough: Flush w/ Top of Floor (Mig) & w/o Trough -> Floor Plank will be extended to rear gutter (FLAT & DIARY TYPE STD)
 Floor Ratings - RV: 18,000lb Rated Floor
 Floor Drain - RV: (4) Drains w/ Kazoo
 Floor Filler Mat'l: I-Filler (Ridge PVC)
 Floor Inserts -RV: Extruded Aluminum (STD)

FRONT
 Front Corner Radius: 6" Extruded Aluminum STD Duty Post (RV)
 Front Panel & Color - RV: 0.04" Aluminum Prepainted White w/ Aluminum Insert
 * Corner Radius Insert - RV: 0.035" Stainless Steel
 Front Posts: (4) Posts - (2) 3.15" Deep Steel Hats / (2) AL "Z" Post
 Gladhands: Phillips Qwik-E with Filters Control Line Only. Overlaid(Back open)+ aluminum plate
 Front Receptacle(7-Way): Phillips 7-Way w/ 3" Deep, No Circuit Breaker (HT Reefer STD)
 Gladhand/7-Way Location: Overlaid on Lower Roadside Front
 * Corner Radius Protector: (2) 0.125" X 12" SMOOTH Alum Each Side at Top
 Reefer Unit Front Frame: Brace for type "A" (Large Opening)

RV-VAN ITEM
 * Reefer Unit Manufacturer: Thermoking
 * Reefer Unit Type: Multi-Temperature Type
 * Reefer Unit Spec.: Thermoking Multi-Temp
 * Reefer Unit Furnish: Customer Furnished
 Reefer Unit Install: Factory Install
 * Reefer Commissioning: Commission unit at Factory
 * Battery: Factory Furnished Battery
 * Battery Spec: Interstate Battery
 * Evaporator Furnish: Customer Furnished
 * Evaporator-Configuration: (1) Thermo King S6 (Full-Width, S3+ S3)
 * Evap - Location by Side: (1) Evaporator in Full Width
 * 1st Evap - Location/Distance: 1st Evaporator: 540" from Front Interior wall to the C/L of the evaporator
 * 1st Evap. - Air Blow Direction: 1st Evaporator blowing direction : Toward Front of Trailer
 * Evap - Drain Configuration: Evaporator to have (1) Drain on Roadside & (1) Drain on Curbside, drain tube cup in side wall to be recessed with flange mounted outside, over the lining and sealed around edges for moisture resistance into foam
 * Evap- Trough Location: Located on Roof
 * Evaporator Guard Furnish: Customer Furnished
 ** Evaporator Guard Spec.: (1) ThermoKing evaporator guards for S-6

SIDE
 Side Material: 0.04" Aluminum Prepainted White w/ natural color rivets
 Side Posts: 1.0" Deep Extruded Aluminum "Z" Post (STD)
 Side Post Centers: 24" C/L with 12" C/L @ Upper Coupler and Support Gear
 Side Top Rail: Standard Side Top Rail for Thermotech
 Side Bottom Rail: Side Bottom Rail for Reefer 5.5" High Bay Crossmember - TL Thermotech

Fasteners to Bottom Rail: Standard Rivets to attach C/Members to the Side Bottom Rail

REAR

Rear Frame: Swing Door Reefer Rear Frame (w/1 Lock Rod per LH & RH Door)
Rear Door Opening Spec.: Swing Door - HT Standard Reefer Door Opening Application (97.2" Width).
Corner Post Feature: Standard
Door Sill Level (RV): Door to Flush with Floor (HT STD)
Door Sill Feature: Standard
Door Header Feature: Standard
Door Type (RV): Swing Door w/ Aluminum Frame & (1) Rubber Door Bumper on Each Door (HT Standard)
* Door-Outer Cover (RV): Swing Door-Stainless Steel Outer Cover Sheet w/ Diamond(Quilted) Pattern
Door-Inner Lining (RV): Swing Door-PP050 (0.043") Polar X
* Door Scuff: Install 0.125" Smooth Aluminum x 16" high rear door scuff
Option - Door Install Instruct (RV): Standard Door Installation Per Manufacturer's Recommendation
Option - Door Hold Back (RV): Standard for Swing Door
Hinges: Four (4) Aluminum Hinges per Door
* Additional Hinge Option: Additional One(1) Aluminum Hinge (Total 5 Per Door)
Rear Underride Guard: 4" Tube Bolt on Assembly w/ Welded Perforated(Poched) Horizontal. Rear Impact Guard (RIG30-NEW)
Option - Horiz Member/Other: One piece roll formed w/continuous welding
Underide Bolt Spec.: Stainless steel bolts & nuts - Optional
* Dock Bumper: Pair 3" X 6" Mold Bolted Bumper
* Rubber Bumper Location: Outboard of Light As Close to Edge As Possible

LIFT GATE

ROOF

* Roof Panel: 0.032" One Piece Corrugated Aluminum
Roof Bow: 1" Extruded Aluminum
Roof Bow Centers: 32" Centers Full Length

LINING/SCUFF

Side Lining - Reefer: Polar X Pp050 0.043"
Front Lining - Reefer: Polar X PP050 0.043"
Roof Lining - Reefer: Polar X PP050 0.043"
Sub-Floor: Polar X Pp030 0.023"
Side Scuff Mt'g Method: Recessed (STD)
* Side Scuff for Reefer: 16" High Extruded Aluminum
* Logistic Track for Reefer: (2) Row of "E" Track, Galvanized, Both Side
* Logistic Track Mt'g Method: Overlaid (Horizontal)
* Logistic Track Locate: Located at 30" & 60" Floor to Centerline of Track

URETHANE INSULATION

Front Insulation: Front Insulation - 4" Polyurethane
Side Insulation: Side Insulation - 2" Polyurethane
* Roof Insulation: Roof Insulation - 3" Polyurethane
* Floor Insulation: Floor Insulation - 2" Polyurethane
Door Insulation: Swing Door-Insulation - 3" Polyurethane

LANDING GEAR

L/Gear Spec.: Jost HT421.G3.17.157 5 Year Warranty Full HDG
L/Gear Mt'g Method: Inboard Mounting (Standard)
L/Gear Shoes: 10" X 10" RCF (Removable Cushion Foot) Low Profile
L/Gear Ground Clearance: Nom. 12" Ground Clearance
L/Gear Mt'g Bracket: Hot Dip Galvanized Large Wing Plate
L/Gear Crank Handle: Roadside
L/Gear Options: None (HT STD)
L/Gear Cross Brace Design: HT Standard Cross Brace attachment Design

RUNNING GEAR

Bogie Type: Sliding Tandem(2) Axle Bogie
 Axle Spacing: 49" Axle Spacing
 Axle ABS System: Tandem Axle w/2S1M ABS System
 Bogie & Axle Location: Location to be Sliding Tandem Axle for specified slider Length w/Stop Bars @ Front & Rear
 Option-Related Bogie Stopper Feature: STD plug stopper
 Susp. Manufacturer: Hendrickson
 Suspension Capacity: Standard Duty
 Hendrickson Susp. Specification: Hendrickson Vantraxx HKANT40K Air Ride
 Surelok (Anti-Dock): Surelok (Anti-Dock) Installed
 Locking Pin Mechanism: Air-Assist Pin Puller or Quik Draw
 Susp. Sub-Frame: Hendrickson K-2 STD Duty
 Type of Susp Spring: Air Bag
 Spring Specification: Air Bag
 * Axle Diameter: 5.75"
 Axle Supplier: Hendrickson
 Axle-General Spec.: Axle - Tandem (2) Axle included in Suspension (For 2S1M or 2S2M System)
 Axle-Track Length: 77-1/2"
 * Axle-Spindle Type: Parallel Spindle
 Brake Lining Size: 16.5" X 7"
 Brake Lining Spec.: Hendrickson Extended Service (Abex-3030-197)
 Brake Control System: 2S/1M Wabco ABS
 Spring Brake Control: Sealco 110500 Springbrake Priority
 Brake Cont-Hose & etc.: Standard Air Line & Hose Application (US&Canada)
 * Slack Adjuster Spec.: Wabco Auto-5.5", 28 Spline EasyFit (No Grease)
 * Brake Chamber Spec.: Wabco Premium Chamber
 * Stroke Length: 3" Long Stroke Length
 Hub Specification: HT Standard (KIC) 10 Stud Hub Piloted Outboard Iron Hub
 Drum Specification: HT Standard (KIC) Cast Drum
 Hub/Drum-Opt(Nut&Other): Standard
 Bearing Specification: Stemco
 Lubrication Spec.: Chev Delo Gear EP5 80-90 oil
 * Wheel Seals Spec.: Stemco Discover Seals, Hub Cap included in tire inflation system, Pro-Torq Nut
 * Tire Inflation Spec.: Hendrickson Tire Maax Inflation System for Undressed Axle (This kit include Hendrickson Hub Cap for TireMaax)
 Tire Inflation Pressure: 100 PSI
 * Tire Inflation Lamp Location: Indicator PSI Light at Roadside Mounted over corner radius. (STD location)
 * Tire Inflation Lamp Spec.: 33 Series Lamp

ELECTRICAL

* Harness-General Spec.: Molded Color Code Grote Harness Oval molds with front terminal rings
 Harness-Special Feature: Manufacturer's Standard Feature
 * Front Light: (4) Trucklite 33275Y LED PC Rated Mounted with Grommet (2-Front & 2-Side)
 * Rear ID Header Light: (5) Trucklite 33275R LED (Cluster of 3 & 1 Each Outboard)
 Rear Side Marker Type(Shape): Mini Button Style Lamp with Antitheft Bracket
 * Rear Side Marker Detail Spec: (2) Trucklite 33275R LED PC Rated Flush w/ Grommet 33725 w/ anti-theft hardware
 Rear Side Marker MT'G Location: Mounted on Standard Location on Rear Corner Post - HT STD
 * S/T/Tail Light-Quantity & Type: (6) Trucklite 40 or 44 Series (Round Style) or Equivalent
 * S/T/Tail Light-Detail Spec: (6) Trucklite 44334R LED Mounted w/ SUS Base Rings Anti Theft
 Main Mid-Turn Light: Install the Mid turn lamp
 Mid-Turn Mounting Method: Mounting Bracket
 * Main Mid-Turn Light-Detail Spec: (2) Trucklite 60420Y LED Flange Mounted with Stainless Steel Rivets
 * ABS Light Detail Spec: (1) Trucklite 33275Y LED PC Rated w/ Grommet 33725 w/ anti-theft hardware
 ABS Light MT'G Location: Mounted on Standard Location on Rear Corner Post - HT STD
 * License Light: (1) Trucklite 33210C LED with 33815 Anti-Theft Flange
 * Option Related Lamps/Harness: Additional Trucklite 33 LED series Marker Lights. (3) Each Side Top Rail & (2) Each

Side Bottom Rail Top and Bottom rail lights to match up (Center Combination to match up with center top rail lamp)
Comment: Top and Bottom rail lights to match up (Center Combination to match up with center top rail lamp)

Electrical Related Regulation: Standard Application
* Roof Dome Lamp Gen Spec.: Install Phillips LED Dome Lights
* Roof Dome Lamp Detail Spec: Phillips 51-22221 LED Motion Sensor Domelights
* Roof Dome Lamp Quantity: Install (3) Three
* Roof Dome Lamp Mt'g Method: Flush Mount Down with Recessed Housing
* Roof Dome Lamp Location: Evenly Spaced at C/L of Ceiling for Swing Doors

MARKING/DECALS

HT & Product Type Decal Package: Hyundai Logo & Product Type Decals Application(For not having pre-painted white panels for side/door/front, Apply white HT Corporate decals)
Decal Package: Factory Furnished Hyundai Information & Regulatory Decal Package with FMCSA Specified in Notes
Decal Opt 2-Decal Location: Standard Application
Decal Opt 3-Decal Installation: Standard Application
Decal Opt 5-Decal Location-reefer: Standard Application
Decal Opt 6-Decal Installation-reefer: Standard Application
Conspicuity Vendor: 3M
Conspicuity Markings: Hyundai Standard Conspicuity with Logo Applied to Side Bottom Rail
License Plate: Temporary For Delivery. Fasten on SUS Mounting Plate
License Plate Brk't Install: Standard Install Location - Roadside Below Door Sill
Furnish Document Holder: Factory Furnished
Document Holder Detail Spec: (1) Phillips 16-802
Document Holder/Manifest Loc.: Overlaid on Lower R/S Front
* Vent Door Specification: (1) Bottom Hinged Swing type Vent Door & (1) Side Hinged Swing type Vent Door (with screens)
* Vent Door Location: (1) Upper R/S Front, (1) Lower C/S Rear Respectively
* Vent Door Step & Handle: (2) Folding Access Steps & Grab Handle (One Side)

PAIN/FINISH

Upper Coupler Finish: Stainless Steel-Forward Section w/ Black Undercoating inside of Upper Coupler
Crossmembers Finish: HDG : ALL Steel Crossmembers including Hat C/M, L/G & Bogie Area (Except any Aluminum)
* Axle & Components Finish: Black Undercoating
* Susp. Sub-Frame Finish: Black Undercoating
L/Gear(K-Bracing) Finish: Hot Dip Galvanized
L/Gear(Upper Leg) Finish: Hot Dip Galvanized
Rear Frame-Finish: Stainless Steel
Rear Frame-Paint Color: None (For Galvanized or Stainless Steel)
Rear Underride-Finish & Spec.: Hot Dip Galvanized
Rear Underride-Paint Color: None (For Galvanized or Stainless Steel)

MISCELLANEOUS

Mudflap Provider: Factory Furnished Mudflaps
Mudflap Specification: 24"x30" White Plain Plastic with Hyundai Logo 3/8# thick with Anti-spray ribs
Mudflap Mounting Location: Suspension frame (Tandem/Single axle frame without P.H.)
Mudflap Mounting Method/Install: STD Location w/ H.D Washer Retainer

DISCLAIMER

Specifications are believed to be correct, but may contain errors and/or omissions. Photographs are the representative of the subject equipment but may not be identical.
Equipment availability, prices and specifications are subject to change without notice.