

Base Model: DF48 x 102 Air Spread 22.5

Serial #: 43584 - 43592

CAPACITY Standard Beam Pkg - 80,000 GVWR (60,000 in 10' Span)

OVERALL LENGTH 48' - Base Weight 12,200# TOP DECK-LGTH/HGT 10' Length = 59" Height

LOWER DECK-LGTH/HGT 38' Length = Front 41", Center 42" Rear 40" Heights

OVERALL WIDTH 8'6"

KING PIN SETTING 18" - Squared Front UPPER COUPLER PLATE 3/8" (+)53#

3/8" Plate.

UPPER COUPLER HEIGHT 48"

BULKHEAD None

MAIN FRAME 26" Fab.-PreCamb.I-Beams-(80K Pkg)

SIDE RAILS 6" - 6.5# Per Foot

TOP DECK FLOOR SILLS 4" Steel I-Beam - 18" O.C.

LOWER DECK FLOOR SILLS 4" Steel I-Beam 12" O.C. HD Pkg

COIL HAUL PACKAGE None FLOOR DECKING 1-1/8" Apitong

WINCHES 12

STRAPS None
WINCH TRACK Steel Slide Entire Length of Drivers Side

LANDING GEAR Two Speed

SUSPENSIONS Air Ride - Hendrickson Intraax - 23K - 2 Axles

SUSPENSION LOCATION Set at Rear most Position - 32.5" Center of Rear Axle to Rear of Trailer

AXLES (2) 23K Capacity - Type 30 Chambers - Auto Slacks - ABS - 22.5 Tires (1463#)

AXLE SPACING 10'2" Wide Spread

LIFT AXLE None

DUMP VALVE Elect.-Wired Thru Aux 7way Plug @ Front of Trailer-Dump Rear Axle(+9#) SCALES

PARKING BRAKES All Axles

ABS SYSTEM Wabco ABS System 2S/1M

DUST SHEILDS None

WHEELS Disc - Hub Piloted - 22.5 - Steel (672#)

TIRES 255/70R 22.5 - Firestone

TIRE INFLATION SYSTEM None

ANTI-SAIL MUD FLAPS Behind All Axles

STAKE POCKETS 24" O.C. Sides & 4 Across Front, 5 Across Rear

PIPE SPOOLS Double

RUB BAND STEEL 3/8" X 2-1/2" Recessed for DOT Tape

DOCK BUMPERS Rubber Inboard

CARGO TIE DOWN None

CONTAINER TWIST LOCKS NONE

TIRE CARRIERS Tire Carrier Positioned In Front of Main Beams Between Landing Gear

TOOLBOX TYPE None

TOOLBOX LOCATION None

LIGHTS Grote Ultra Blue Sealed Wiring Harness- 2 Micros Per Side & Mid Turn-3/3/3 Rear

CUSTOM LIGHTS None

PAINT Black - PPG Epoxy Primer and Acrylic Polyurethane - Shot Blasted

DECAL PACKAGE Standard Dorsey Logo Kit