

# HALE TRAILER BRAKE & WHEEL

A021535-A021552

SALES | RENTALS | PARTS | SERVICE

Allentown, PA:	800-383-8894	Jacksonville, FL:	800-828-3055
Baltimore, MD:	888-601-7500	Little Rock, AR:	833-424-8944
Boston, MA:	800-854-5310	Portland, ME:	800-325-4253
Concord, NC:	800-438-2250	Richmond, VA:	866-839-3495
Delmar, DE:	866-486-1400	Scranton, PA:	800-569-1400
Des Moines, IA:	888-673-5011	Springfield, MA:	800-854-5306
Elkton, MD:	800-544-7127	Voorhees, NJ:	866-315-0235

HaleTrailer.com | @haletrailer     

800-232-6535 \*FINANCING AVAILABLE



<input checked="" type="checkbox"/> Flat Extendable	<input checked="" type="checkbox"/> Drop	<b>Length :</b> 54' to 219' with bumper
<b>Fifth wheel height :</b> 48		<b>Width :</b> <input checked="" type="checkbox"/> 102"
<b>King Pin</b> <input checked="" type="checkbox"/> Other : 28.5		<b>Steering axles :</b> <input checked="" type="checkbox"/> 3
<b>Location :</b> <input checked="" type="checkbox"/> Bolt-on		<b>Suspension :</b> <input checked="" type="checkbox"/> Turner HT-250U
<b>Coupler</b>		<input checked="" type="checkbox"/> Scale-O-Matic <input checked="" type="checkbox"/> COLAS Valve
<b>Plate:</b> <input checked="" type="checkbox"/> 1/2" HTS		<input checked="" type="checkbox"/> Shut-off valve
<b>Gooseneck:</b> <input checked="" type="checkbox"/> Hinged		<b>Steering mecanism :</b>
<b>Frame :</b> Extendable with camber		<input checked="" type="checkbox"/> Forced steer with front turn table
<b>Extendable boxed beams (caisson):</b> <input checked="" type="checkbox"/> 3+1		<input checked="" type="checkbox"/> Suspension and axles with turn tables
<b>Removable blade support on beams:</b> <input checked="" type="checkbox"/> 1		<b>Steering control :</b> <input checked="" type="checkbox"/> Automatic <input checked="" type="checkbox"/> Manual
<b>X-Member :</b> Fabricated special		<input checked="" type="checkbox"/> 13 HP Honda power pack
<b>Nose corners :</b> <input checked="" type="checkbox"/> 45°		<b>Axles :</b> <input checked="" type="checkbox"/> D-22
<b>Rub rail :</b> <input checked="" type="checkbox"/> None		<b>Axle track :</b> <input checked="" type="checkbox"/> Other : 79
<b>Stake pocket :</b> <input checked="" type="checkbox"/> None		<b>Brake type:</b> <input checked="" type="checkbox"/> Drum brakes
<b>Floor :</b> <input checked="" type="checkbox"/> Other : Steel covered with rubber		<b>Seals :</b> Stemco Guardian HP <b>Bearings :</b> Stemco
<b>Bumper :</b> <input checked="" type="checkbox"/> Long <input checked="" type="checkbox"/> Steel Extendable 20'		<b>Brake Chambers:</b> TSE 30/30T
<b>Fenders :</b> Plastic over axles		<b>Automatic Slack adjuster :</b> <input checked="" type="checkbox"/> TSE
<b>Mud flaps :</b> <input checked="" type="checkbox"/> Témisko		<b>Brake valve :</b> Rockwell Wabco
Location : Back of gooseneck and at each axle		<b>A.B.S. Brake :</b> <input checked="" type="checkbox"/> 2S/1M
<b>Land. gear :</b> <input checked="" type="checkbox"/> Holl. Mark V		<input checked="" type="checkbox"/> Blue wire on first axle <input type="checkbox"/> A.B.S. Plug <input type="checkbox"/> Y <input checked="" type="checkbox"/> N
Crank : <input checked="" type="checkbox"/> R/S		<b>Hubs :</b> <input checked="" type="checkbox"/> Dura Light 8 studs steel piloted hubs
<b>Lights :</b> <input checked="" type="checkbox"/> Truck-lite round type (2/s) <input checked="" type="checkbox"/> 45° flasher		<b>Drums :</b> <input checked="" type="checkbox"/> Standard <input type="checkbox"/> Centrifuse
<input checked="" type="checkbox"/> LED lights		<b>Rims :</b> Qty : <u>12</u>
<input checked="" type="checkbox"/> Other: Beacon light at rear bumper		<input checked="" type="checkbox"/> 17.5 x 6.75 <input checked="" type="checkbox"/> Alum. machined finish
Strobe lights in bumper on switch (clearance cuircuit)		<b>Tires :</b> Qty : <u>12</u>
<b>Title hold :</b> <input checked="" type="checkbox"/> Truck-lite		Model: Michelin XTA2 ENERGY Size : 245/70R17.5
Location :		<input checked="" type="checkbox"/> Plastic spacer (rim & rim) <input checked="" type="checkbox"/> Plastic spacer (hub & rim)
<b>Tool box :</b>		<b>Tire carrier Témisko Fab :</b>
<input checked="" type="checkbox"/> Alum. Témisko FAB		<input checked="" type="checkbox"/> 1 <input checked="" type="checkbox"/> C/S
Dimensions : 25" X 24" X 48"		<b>Hubodometer :</b> <input checked="" type="checkbox"/> None
Location : In front of tridem, on both sides		Location :
		<b>Paint :</b> Colour : Black
		Colour code: RAL 9005 <input checked="" type="checkbox"/> Tape 100%
		Trim : <input checked="" type="checkbox"/> None
		Rim : <input checked="" type="checkbox"/> Natural
		<b>Rack :</b> <input checked="" type="checkbox"/> None
Visual lock indicators for inter beam locking		
Aluminum checkerplate on front coupler, Aluminum checkerplate front fenders		
(4) supports for air and hydraulic lines/beam		
Power pack in aluminum box on R/S		
Double redundant hydraulic steering circuit.		
On board steering control, Plug in remote control and wireless remote control (Lodar) + antenna		
dual Hydraulic drop leg to facilitate extending		
"D" rings on each side of the front and rear loading platforms, total of 2X loading bunks		
180 ft of hydraulic lines from front to back		
Oversized sign at rear		

DISCLAIMER

Specifications are believed to be correct, but may contain errors and/or omissions. Photographs are the representative of the subject equipment but may not be identical. Equipment availability, prices and specifications are subject to change without notice.