

HALE

TRAILER

BRAKE & WHEEL



Resale Inventory
A021553-A021555
VIN: 53248, 53252, 53253

SALES | RENTALS | PARTS | SERVICE

| | | | |
|------------------------|---------------------|--------------------------|---------------------|
| Allentown, PA: | 800-383-8894 | Jacksonville, FL: | 800-828-3055 |
| Baltimore, MD: | 888-601-7500 | Little Rock, AR: | 833-424-8944 |
| Boston, MA: | 800-854-5310 | Portland, ME: | 800-325-4253 |
| Concord, NC: | 800-438-2250 | Richmond, VA: | 866-839-3495 |
| Delmar, DE: | 866-486-1400 | Scranton, PA: | 800-569-1400 |
| Des Moines, IA: | 888-673-5011 | Springfield, MA: | 800-854-5306 |
| Elkton, MD: | 800-544-7127 | Voorhees, NJ: | 866-315-0235 |

HaleTrailer.com | @haletrailer     

800-232-6535 *FINANCING AVAILABLE

Velocity Drop Deck 53 Tridem Air Ride (HAVSD22TAF)

General

| | |
|------------------------|--|
| Model | HAVSD22TAF |
| Length x Width | 53 feet x 102 inches |
| Deck Length | 11 feet Front and 42 feet Rear |
| Rear Deck Height | 40 inches - Loaded |
| Suspension | Tridem Air Ride |
| Frame Rating | 100,000 lbs Distributed - GAWR and Tire Ratings Determine Legal Payloads |
| Kingpin Setting | 18 inches |
| Fifth Wheel Height | 49 inches |
| Axle Spread | 60 inches, 60 inches - Kingpin to Center Axle 40 feet 10 7/8 inches |
| VIN Plate | Bilingual US/Canadian VIN plate |
| Estimated Weight | Est. Weight: 13990 lbs. +/-3% |

Structural

| | |
|--------------------|---|
| Main Beams | 130K Load Bearing Flanges |
| Crossmembers | 18 inch Centers Front Deck / 12 inch Centers Rear Deck - 4 inch Jr. I-Steel |
| Knee Braces | Fabricated on Approx. 60 inch C/C |
| Side Rails | 6 inch Structural Channel @ 6.5 lbs/ft |
| Stake Pockets | 3/16 inch Steel on 24 inch Centers |
| Pipe Spools | Double Between Stake Pockets |
| Rubrail | 3/8 inch x 2 1/2 inch Steel |
| Front Corners | Tapered |
| Bumper | Weld-On; Meets U.S. Underride Requirements |
| Winch Track | Full-length integrated steel on both road side and curb side |
| Bulkhead Pockets | 4 - F-5 DOT-Type Steel |

Landing Gear

| | |
|--------------|---------------------------------|
| Landing Gear | Jost A400G19 Steel Landing Gear |
|--------------|---------------------------------|

Flooring

| | |
|----------|---------------------|
| Flooring | 1 1/4 inch FIR Wood |
|----------|---------------------|

Suspension

| | |
|-----------------------|--|
| Suspension Detail | Hendrickson AANL23K Intraax Air Ride |
| Number of Axles | 3 |
| Axle Spindle | Tapered |
| Brakes | Spring Brakes, Auto Slacks |
| Hubs and Drums | 10-Hole Hub-Piloted with Outboard Cast Drums |
| Wheel Ends | Grease in Hubs - *** 5-Year Wheel End Warranty *** |
| Tire Inflation System | None Standard |
| Air Lift | None Standard |

Wheels and Tires

| | |
|--------|---|
| Wheels | (12) 22.5 x 8.25 Steel disc wheels - pre-painted white - STANDARD |
| Tires | (12) 255/70R 22.5 16PR OEM Standard tires |



Air System

| | |
|---------------------|---|
| Air Line Filters | (2) Meritor In-line Type Installed |
| ABS | 4S/2M - No Cable or Tool |
| Full System Dump | Auto Glad Hand Dump Installed |
| Electric Dump Valve | Wired to 7-Way Auxiliary Socket to Dump Rear Axle |
| Gladhand Position | Front Gladhands and Electrical Connections in Center of Trailer |

Electrical System

| | |
|--------------------|----------------------------|
| Tailskirt Lights | LED: 2 Lights/Side on Rear |
| Side Marker Lights | LED: 3 Lights/Side |

Paint and Decal

| | |
|----------------------|---|
| Paint | Black Urethane with Velocity Decals |
| Conspicuity Tape | Per NHTSA Specs - Installed on Rubrails |
| Unit Number & Decals | Fontaine Standard Decals Installed |

Miscellaneous

| | |
|---------------------|--|
| Mudflaps | 1 Set OEM Standard |
| Sliding Winches | 12 standard: 2 Top Deck - 10 Lower Deck |
| Winch Location | All Road Side |
| 27' Winch Straps | None Standard |
| 30' Winch Straps | None Standard |
| Dock Bumpers | 1 Pair Rubber on Rear |
| Registration Holder | Install Registration Holder - OEM Standard |

Options

| | |
|--------------------|--|
| Bulkhead | None Standard |
| Spare Tire Carrier | 1 Standard - Mounted Between Lower Gooseneck Beams |
| Hubodometer | None Standard |
| Tool Box | None Standard |

Literature

| | |
|--------------------|-----------------------------------|
| Trailer Literature | Velocity Brochure |
|--------------------|-----------------------------------|

DISCLAIMER

Specifications are for the equipment at the time it was produced and may not accurately reflect its current condition. Photographs are the representative of the subject equipment but may not be identical. Equipment availability, prices and specifications are subject to change without notice.