

HALE TRAILER BRAKE & WHEEL



A021576-A021577
VIN: 23967 & 23970

SALES | RENTALS | PARTS | SERVICE

Allentown, PA:	800-383-8894	Jacksonville, FL:	800-828-3055
Baltimore, MD:	888-601-7500	Little Rock, AR:	833-424-8944
Boston, MA:	800-854-5310	Portland, ME:	800-325-4253
Concord, NC:	800-438-2250	Richmond, VA:	866-839-3495
Delmar, DE:	866-486-1400	Scranton, PA:	800-569-1400
Des Moines, IA:	888-673-5011	Springfield, MA:	800-854-5306
Elkton, MD:	800-544-7127	Voorhees, NJ:	866-315-0235

HaleTrailer.com | @haletrailer     

800-232-6535 *FINANCING AVAILABLE

XL SPECIALIZED TRAILERS

XL 130 Hydraulic Detachable Extendable

OVERALL LENGTH	57'
OVERALL WIDTH	102"
CAPACITY	130,000 LB DISTRIBUTED; 110,000 LB IN 10' CLOSED
WEIGHT +/- 3%	0,000 LB
GOOSENECK	
LENGTH	12' 5" NARROW NECK
KINGPIN SETTING	16"
SWING CLEARANCE	105"
5TH WHEEL HEIGHT	52" W/7 VARIABLE RIDE HEIGHT POSITIONS
HYDRAULICS	RUNS OFF WET KIT
FLIP NECK	PREP FOR 96" FLIP NECK 96" FLIP NECK EXTENSION 95,000 LBS MAX KING PIN FORCE LIFTING CAPACITY WITH 96" FLIP NECK ATTACHED TO 12'-5" GOOSENECK
MAIN DECK	
LENGTH	30' 1" / OPENING TO 52' 11" 30" MINI DECK
LOADED DECK HEIGHT	24" W/ 6" GROUND CLEARANCE
DECKING	1 1/8" APITONG DECKING, FLUSH, CENTER COVERED
CROSSMEMBER	6" JR. I-BEAM AND KNEE BRACES ON 12" CENTERS
BEAMS	(4) FAB I-BEAMS
D-RINGS	(10) BENT D-RINGS PER SIDE
OUTRIGGER	REMOVABLE SWINGOUT OUTRIGGERS ON 24" CENTERS
CHAIN DROPS	(10) CHAIN DROPS PER SIDE - OUTSIDE BEAMS - STAGGER BETWEEN D-RINGS
REAR DECK	
LENGTH	14' 6"
LOADED DECK HEIGHT	41"
AXLES	(3) 25,000 LBS. NOMINAL (5/8" WALL)
SUSPENSION	HENDRICKSON / 25,000 CAPACITY / AIR RIDE
AXLE SPACING	60"
ABS	N/A SPRING BRAKES ON 1 AXLES
TIRES	275 / 70R / 22.5 (J) MICHELIN
WHEELS	8.25 X 22.5 10-HOLE PILOT MOUNT, POLISHED ALUMINUM OUTSIDE, STEEL INSIDE, DISC
BRAKES	16 1/2" X 7"
DRUMS	OUTBOARD
ELECTRICAL	12V SEALED GROTE SYSTEM WITH (3) TAIL LIGHT ALUMINUM PACKAGE 4" AMBER STROBE WITH SWITCH TO MAKE 3RD TAIL LIGHT
DECKING	1 1/8" APITONG DECKING FLUSH, COVERED WHEELS WITH OPEN BOOM TROUGH
D-RINGS	(1) PAN STYLE D-RING IN EACH CORNER
D-RINGS	(2) BENT D-RINGS IN TAIL CHANNEL
PAINT	BLACK
ADDITIONAL	(2) PAIR OF FLAG HOLDERS RAISE AND LOWER VALVE PREP FOR A TWO AXLE POWER BOOSTER (3+2) MANUAL RIDE HEIGHT CONTROL 31" FRONT LOADING RAMPS (1) EXTRA CLEARANCE LIGHTS PER SIDE ON GOOSENECK (5) EXTRA CLEARANCE LIGHTS PER SIDE ON MAIN DECK (1) EXTRA CLEARANCE LIGHTS PER SIDE ON WHEEL AREA (2) EXTRA MID TURNS PER SIDE ON THE MAIN DECK EXTENSION STOPS ON 24" CENTERS LIQUID FILLED AIR GAUGE ALUMINUM BOX BETWEEN AXLES ON ROADSIDE FOR AIR COMPONENTS DETACHABLE WHEEL AREA WITH VERTICAL PINS PSI TIRE INFLATION SYSTEM DUST SHIELDS TO FIT TO: 22 FA INT 23968 22 FA REAR 23969 42 PMB SO 77651

DISCLAIMER

Specifications are believed to be correct, but may contain errors and/or omissions. Photographs are the representative of the subject equipment but may not be identical. Equipment availability, prices and specifications are subject to change without notice.