

HALE

TRAILER

BRAKE & WHEEL



**KALYN
SIEBERT**

A021599-A021604

VIN: 174557-174562

SALES | RENTALS | PARTS | SERVICE

Allentown, PA:	800-383-8894	Little Rock, AR:	833-424-8944
Baltimore, MD:	888-601-7500	Portland, ME:	800-325-4253
Concord, NC:	800-438-2250	Raleigh, NC:	833-418-9777
Delmar, DE:	866-486-1400	Scranton, PA:	800-569-1400
Des Moines, IA:	888-673-5011	Springfield, MA:	800-854-5306
Elkton, MD:	800-544-7127	Voorhees, NJ:	866-315-0235
Jacksonville, FL:	800-828-3055	Walpole, MA:	800-854-5310

haletrailer.com | @haletrailer

800-232-6535 *FINANCING AVAILABLE

Trailer Model:

Kalyn Hydraulic Sliding Axle KS-HSA-2A-40T-50

		<u><i>KS-HSA-2A-40T-50 Standard Equipment</i></u>	
Net Capacity:	40 Tons	80,000 lbs Distributed in 50 ft, 50,000 lbs Concentrated in 10 ft	
Nominal:	50 feet OAL	Kingpin to center of rear axle 40 feet in Transport Mode	
	8 feet 6 inches Wide	Dump angle 16°	Loading angle 7°
GOOSENECK:		SUSPENSION:	
10'-8" Gooseneck Length (48' & 50') / 11'-6" (53')		25,000 lb nominal capacity with Oil seals, 5/8" wall, tapered spindles	
48" Loaded 5th Wheel Height, 18" Kingpin Setting		50" axle spacing 71" track	
86" Swing Radius (48' & 50') / 96" Swing Radius (53')		12-1/4" x 7-1/2" Brakes ABS Module: 2S1M	
20,000# Planetary Winch With Air Clutch; 100' of 5/8" Cable		Auto Slack Adjusters and Spring Brakes on all Axles	
Work lights on the winch 2 Tool compartments		6.75 x 17.5 Hub Piled Disc Wheels	
Wet Kit: Trailer Operation; 3/4" Hydraulic Couplings		235/75 R 17.5 16PR Tires Manual Dump Valve	
Integrated Tool Box in Neck W/ Stainless Hinges and Alum. Door		Suspension: Ridewell or Equivalent Air ride Air Ride	
2-Speed Landing Gear, Crank Handle Roadside		Alignment Bracket for Sliding Suspension	
DECK:		GENERAL:	
Nominal Deck Length:	39.34 feet	12 Volt System with 7 way Sealed Harness	
Nominal Deck Width:	102 in	DOT Rubber Mounted Sealed Beam LED Lights	
Loaded Deck Height:	37 in	Galvanized frame, Black Polyurethane Landing Legs / Axle Assemblies	
4 Beam design - 100,000 psi yield flanges & 80,000 web minimum		2 Function Wireless Remote for Winch	
14" tall main beams and 15" tall side rails		Heavy Duty DOT Approved Bumper	
4" I-beam cross members on 9" Centers, 1-3/8" Aplong Deck (full width)		Red & White Conspicuity tape KS Mud Flaps	
Double Key Hole Chain Slots in Upper Flange on 36" Centers		3 LED marker lights each side including mid turn	
Double Key Hole Chain Slots Along Center of Deck on 36" Centers		Strobe light with toggle switch on rear	
Reinforced Rear Approach Plate with 6 Chain Slots			
Cable Roller Centered at Front of Lower Deck			

Kalyn Hydraulic Sliding Axle Optional Equipment

- 2 Axle, 40 ton, 50' model
- Full galvanized frame
- Side rail paint (with full galvanized option)
- 6 function wireless remote
- bolt on side step (driver side)
- Aluminum wheels outside all axles
 - OEM 235/75 R 17.5 16 PR tires
- AirWeigh load scale
- Tire Inflation
- 74,000 lb dock levelers (simultaneous controls)
- Central lube - 18 point manual
- 30,000 lbs winch

Estimated weight of the equipment with options: 18,625

DISCLAIMER

Specifications are believed to be correct, but may contain errors and/or omissions. Photographs are the representative of the subject equipment but may not be identical. Equipment availability, prices and specifications are subject to change without notice.