

HALE TRAILER

BRAKE & WHEEL

Resale Inventory
A021766-A021770



SALES | RENTALS | PARTS | SERVICE

Allentown, PA:	800-383-8894	Jacksonville, FL:	800-828-3055
Baltimore, MD:	888-601-7500	Little Rock, AR:	833-424-8944
Boston, MA:	800-854-5310	Portland, ME:	800-325-4253
Concord, NC:	800-438-2250	Richmond, VA:	866-839-3495
Delmar, DE:	866-486-1400	Scranton, PA:	800-569-1400
Des Moines, IA:	888-673-5011	Springfield, MA:	800-854-5306
Elkton, MD:	800-544-7127	Voorhees, NJ:	866-315-0235

HaleTrailer.com | @haletrailer

800-232-6535 *FINANCING AVAILABLE

GEOMETRY

LENGTH EXTERIOR.	48' 0"		X
-INT.	47'-6"		
WIDTH -EXT.	102.36"		
-INT.	99"		X
HEIGHT -EXT.	13'-6"		
-INT.	110"		
UPPER COUPLER HT.	47"		
KING PIN LOCATION	36"		

TIRES

TYPE	GENERAL RIB ST (G)		
SIZE	295/75 R 22.5 (G)		

ROOF

ROOF SHEET	.040" ONE PIECE ALUMINUM		
ROOF BOW TYPE	16 GA. GALV. STEEL		
ROOF BOW SPACING	24" CENTERS FULL LENGTH		

FRONT

CORNER RADIUS	6" ALUMINUM		
FRONT SHEETS	.050" PPW ALUMINUM		
FRONT UPRIGHTS	(4) 3.2" DEEP STL HATS WELD TO U.C.		X
GLADHANDS	PHILLIPS QWIK-E W/FILTERS SWIVEL TYPE RECESSED		X
REG. CARDHOLDER	TITE SEAL TUBULAR MOUNTED ON ROADSIDE SUPPORT GEAR		X

SIDEWALL

SIDE MATERIAL	.050" PREPAINTED WHITE ALUMINUM		
SIDE UPRIGHTS	1.25" DEEP 14GA GALVANIZED STEEL 'A' SLOTTED LOG POSTS		X
UPRIGHT CENTERS	16" C/L, 12" @ U.C. & SUPP.GEAR		X

FORWARD & UPPER COUPLER AREA

UPPER COUPLER	3.40" JOGGLED W/ 52.25" EXPOSED. PRIME PAINTED ONLY.		
APPROACH PLATE	.25" THICK 80,000 LB YIELD. 2 EXTRA LONGITUDINALS		
BOTTOM MAINBEAM PL	.25" THICK 80,000 LB YIELD		
FORWARD XMEMBERS	HAT SHAPED: U.C. TO SUPP. GEAR		
SUPPORT GEAR	JOST 401G317 (ON 8" CROSSMEMBER CENTERS)		X
SHOES	10" X 10" LOW PROFILE CUSHION FOOT		
LOCATION	107" C/L SUPP. GEAR TO C/L KING PIN		
CRANK HANDLE	ROADSIDE		
BAY AREA XMEMBERS	4" STEEL I-BEAMS		
XMEMBER CENTERS	BAY AREA: 8" C/L & FORWARD AREA: 10" C/L - USING .25" THICK HAT SECTIONS & .13" x NOMINAL		X
TIRE CARRIER	NONE		

UPPER RUNNING GEAR AREA

U.R.G. XMEMBERS	4" STEEL I-BEAMS		
XMEMBER CENTERS	8" CENTERS		X
U. R.G. RAILS	168" RAIL LENGTH (65"-125")		REV.01
SLIDER ASSEMBLY	HENDRICKSON K-2 SLIDE		X
MUDFLAPS	PLASTIC W/ HYUNDAI LOGO		

LOWER RUNNING GEAR AREA

SUSPENSION	HENDRICKSON HK190 AIR RIDE W/SURELOK		X
SPRINGS	NONE		X
BRAKE SYSTEM	SEALCO #110500 VALVE W/WABCO 2S/1M ABS		
CHAMBERS	TSE 3030 TAMPER RESIST		
BRAKES	16.5" x 7" DANA SPICER SILVER EXTENDED LIFE BRAKE LINING		X
AXLES	DANA D22AX603 .63" WALL 77.50" TRACK		X



LOWER RUNNING GEAR AREA

BRAKE ADJUSTERS	GUNITE AUTO - 5.50"	
HUB & DRUM	10 STUD HUB PILOTED OUTBOARD MTD CAST	
WHEELS	22.5 x 8.25 5 HAND HOLE STEEL DISC	
OIL SEALS	STEMCO PLATINUM PERFORMANCE SYSTEM	
HUBODOMETER	STEMCO READING IN MILES ON R/S FRONT AXLE	X

REAR

HEADER	2" SHALLOW HEADER	
REAR DOOR TYPE	.75" PLYMETAL SWING DOOR	
REAR DOOR MAT'L	26 GA GALV., 0.03" PPW ALU.	
LOCK RODS	BLOXWICH, 1 PER DOOR	
HINGES	ALUMINUM, 4 PER DOOR	
UNDERRIDE PROTECTIO	4" x 4" TUBE. HOT DIPPED GALVANIZED STEEL W/PERFORATED (POOCHED) MAT'L	
RUBBER BUMPERS	1 PR. 2" X 4" RUBBER BLOCKS	

LINING

SIDE LINING	.25" PONDEROSA PLWD	X
SIDE SCUFFBAND	1.00" X 24" HIGH LAMINATED HARDWOOD, RECESSED	X
NOSE LINING	.50" PONDEROSA PLYWOOD, FULL HT.	
FRONT SCUFFBAND	.75" X 24" HIGH LAMINATED HARDWOOD, OVERLAID	X
CEILING LINING	NONE	

FLOOR

FLOOR	1-3/8" NOMINAL DOMESTIC LAM. OAK HARDWOOD	
FLOOR SCREWS	(3).31" DIA.SCREWS/BOARD/XMBER	
THRESHOLD PLATE	.13" X 12" STL DIA.PLT. PRIMED	

ELECTRICAL

LIGHTS	TRUCKLITE SERIES 19 Side & Front, 35 LED Rear header &40 Flange mount Tail lights	
MID-TURN SIGNAL	TRUCKLITE 60 SERIES	
ELECTRICAL CONN.	PHILLIPS 7-WAY W/O CIRCUIT BREAKERS IN RECESSED PAN ON ROADSIDE FRONT	X
LOCATION	OVERLAID ON RDSIDE FRONT	

PAINT & FINISH

UNDERCARRIAGE	BLACK UNDERCOATING	
CHASSIS &SUPP GEAR	GRAY	
REAR FRAME	HOT DIPPED GALVANIZED STEEL REAR FRAME & BUCKPLATE	
WHEELS	PRE-PAINTED WHITE	
DECALS	CONSPICUITY TAPE - HYUNDAI LOGO TYPE	
INSPECTION DECAL	FHWA INSTALLED	
TEMP LIFT PADS	NONE	

- 1 TEMPORARY LICENSE PLATE FOR TRANSPORT. FASTEN WITH NUT & BOLT
- 2 Hot Dipped Galvanized Support Gear Bracing and Wing Plates. Use Grade 8 bolts to Support Gear Bracing
- 3 Rear lower side marker lights to be approx. flush with bottom rail.
- 4 Stainless steel front impact guard w/stainless steel striker angle.
- 5 Spring loaded rear door hold back - Fleet engineering part # 023-00024
- 6 Hot dipped galvanized 3/16" x 16" high angle plate to wrap around lower post from outside face to rear sill face, fully welded. 7 Floor screws at floor connection with threshold plate to have nuts on screws.

DISCLAIMER

Specifications are for the equipment at the time it was produced and may not accurately reflect its current condition. Photographs are the representative of the subject equipment but may not be identical. Equipment availability, prices and specifications are subject to change without notice.