

HALE

TRAILER

BRAKE & WHEEL



A021953-A021954
VIN: 43294-43295

SALES | RENTALS | PARTS | SERVICE

Allentown, PA:	800-383-8894	Jacksonville, FL:	800-828-3055
Baltimore, MD:	888-601-7500	Little Rock, AR:	833-424-8944
Boston, MA:	800-854-5310	Portland, ME:	800-325-4253
Concord, NC:	800-438-2250	Richmond, VA:	866-839-3495
Delmar, DE:	866-486-1400	Scranton, PA:	800-569-1400
Des Moines, IA:	888-673-5011	Springfield, MA:	800-854-5306
Elkton, MD:	800-544-7127	Voorhees, NJ:	866-315-0235

HaleTrailer.com | @haletrailer



800-232-6535 *FINANCING AVAILABLE

Base Model: DF48x102 60 Ton 275 Tires Extreme Duty

Serial #: 43294

components description

CAPACITY Extreme Duty Package - 120,000 lbs. GVWR (110K Eq. Dist. & 90,000 in 10' Span)

** (70,000 in 4').**

OVERALL LENGTH 48'

UPPER DECK LENGTH 12'

*** Minimum Pitch of 2-3/4" ***

LOWER DECK LENGTH 36' (Deck Height-42")

OVERALL WIDTH 8' 6"

KING PIN SETTING 18"

UPPER COUPLER PLATE 5/16"

UPPER COUPLER HEIGHT ** 50" **

BULKHEAD None

MAINFRAME 26" Fabricated - PreCambered I-Beams - Heavy Duty

** Main Beams 1/2" X 6" Top Flange, 3/4" x 6" Bottom, 1/4" Webs Throughout, Lower Deck, 1/4 Rear Section, 1/4" Web in Neck. **

** Transition Plate **

** 1/4" Diamond Plate Over Wheels. **

*** 1/4" Diagonal Bracing, Main Beam to Outer Rail. ***

**** Rear of Trailer Prep for 4th Flip Axle. ****

SIDE RAILS 8" Heavy Duty

FLOOR SILLS 6" I-Beam 12/12/12 O.C. HD Pkg. Drop Frame

** Approx. 6 Aux. Crossmembers over Suspension at Middle of Trailer, and in Gooseneck. **

** Install Sub Sils in High Stress Areas. **

FLOOR DECKING ** 1-1/2" Apitong **

WINCH TRACK Steel Slide Entire Length of Drivers Side

WINCHES 12

STRAPS None

LANDING GEAR Two Speed

SUSPENSIONS (Hendrickson)- 30K Suspension W/ (30K) Lift Rear Axle

9" Ride Height.

LIFT AXLE Lift Rear Axle

DUMP VALVE Dump Valve in Box Includes: Manual Override, Liquid Filled Gauges and Lift Axles

** All Air Control valve in Box.**

SCALES None

AXLES (3) 25K Capacity - Type 30 Chambers - Auto Slacks - ABS - Air Ride(Parallel Spindle)

Parallel Spindle.

23K Brake Linings.

AXLE SPACING 61" Wide Spread

PARKING BRAKES 3 Axle

DUST SHEILDS None

WHEELS Disc - Hub Piloted - Steel Inside and Polished Aluminum Outer

*** Steel Inside, Polished Outside w/ Wheel Pads Between Wheels ***

TIRES 275/70R 22.5 - 42" Loaded Deck Height

ANTI-SAIL MUD FLAPS Rear Frame

STAKE POCKETS 4" Deep - 24" O.C. - Sides Only

RUB BAND STEEL 3/8" X 3"

PIPE SPOOLS Double

DOCK BUMPERS None

*** Heavy Duty Rear Skirt and Rear End Material ***

** Aluminum Sheet on Outside Rear to Cover 3 Light Stop/Tail/Turn **

DOVETAIL None

LOADING RAMPS None

TIRE CARRIERS None

CARGO TIE DOWN None

TOOLBOXES None

TOOLBOX TYPE None

LIGHTS Sealed Wiring Harness w/ LED Pkg

Use Flange Mounted Anti-Theft S/T/T On Rear Skirt, (Due To Skirt Thickness).

PAINT Black - PPG Epoxy Primer and Acrylic Polyurethane - Shot Blasted

CUSTOM 1. Strobe Kit- 3-3-3 Toggle Switch - D/S - Rear Trailer

CUSTOM 2. None

CUSTOM 3. None

Reference #: 36273

DISCLAIMER

Specifications are believed to be correct, but may contain errors and/or omissions. Photographs are the representative of the subject equipment but may not be identical.

Equipment availability, prices and specifications are subject to change without notice.