



A021970-A021977 VIN: 43972-43979

SERVICE SALES RENTALS PARTS

Allentown, PA: 800-383-8894 Jacksonville, FL: 800-828-3055 Baltimore, MD: 888-601-7500 Little Rock, AR: 833-424-8944 Boston, MA: 800-854-5310 Portland, ME: 800-325-4253 Concord, NC: 800-438-2250 Richmond, VA: 866-839-3495 Delmar, DE: 866-486-1400 Scranton, PA: 800-569-1400 Des Moines, IA: 888-673-5011 Springfield, MA: 800-854-5306 Voorhees, NJ: Elkton, MD: 800-544-7127 866-315-0235

HaleTrailer.com | @haletrailer 👔 💟







800-232-6535

*FINANCING

Model: AC-20 20 Capacity in tons:

1. TONGUE

Pintle eye Adjustable pintle eye (3" ID) with 48" chain and grab hooks

5'-6" with lockable tool box with aluminum diamond plate lid - move hinge 4" Tongue

forward

2-speed, 50,000# crank down dual landing leg, mounted to main beams and Drop leg

headboard

Electrical receptacle Seven pin connector Headboard 8" high full width

2. DECK

Deck section design One piece tongue, main beam and beavertail (cold formed)

27'-0" (21'-0" flat with 6'-0" beavertail) Deck section length

8'-6" Deck section width Loaded deck height 32-1/4"

Flooring 1-1/2" apitong - individual wheel well covers

Lash rings 10 total -

> 4 each side on flat deck (straight style), 8 total 1 each side on beavertail (straight style), 2 total

Mainbeams 12" deep hi-tensile 6" deep hi-tensile Crossmembers 8" deep hi-tensile Sidemembers

6'-0" Double break with wood flooring full width Beavertail

Ramps 5'-0" with wood flooring with 3 springs per ramp and grab handles

3. RUNNING GEAR

Number of axles

Axle capacity 25,000# Full width track

Brakes 12-1/4" x 7-1/2" air with 2S/1M ABS. Spring brakes on both axles.

Wheels Steel disc with oil seals (6.75 x 17.5) Tires Eight (8) 215/75R17.5 (H) 16PR radials Use valve stem extensions on inside wheels

Suspension 44,800# Hutch spring

4. GENERAL Lights and wiring 12 volt LED system (license plate regular), supplied with female 7-way plug on

tongue, SUPPLY JUMPER CORD FOR TRUCK

Valspar standard Talbert black, R-Cure 800 series paint Paint Additional general specifications Formed step in front of 1st axle both sides of trailer