

# XL SPECIALIZED TRAILERS

# XL 70 MFG: Mini-Deck

OVERALL LENGTH OVERALL WIDTH CAPACITY WEIGHT +/- 3%

53'

16"

84"

49"

9

10' FULL-WIDTH NECK

AIR SUPPORT ARM 1 1/8" APITONG DECKING FLUSH

(2) BENT PER SIDE

ALUMINUM MUD FLAPS

TRIPLE DONUTS

3 BEAM DESIGN

34' (33' CLEAR)

SHIMMABLE NECK - SHIMS INCLUDED

(1) PAN STYLE IN EACH CORNER

102" 70,000 LB DISTRIBUTED; 60,000 LB IN 16' CONCENTRATED 0,000 LB

# GOOSENECK

LENGTH KINGPIN SETTING SWING CLEARANCE **5TH WHEEL HEIGHT** 

DECKING D-RINGS

MUD FLAPS TOOLBOX

#### **MAIN DECK** I ENGTH

LOADED DECK HEIGHT DECKING

CROSSMEMBER BEAMS D-RINGS OUTRIGGERS RAMPS CHAIN DROPS.

### 12" W 4" GROUND CLEARANCE STEEL DECKING BETWEEN MAIN BEAMS WITH DURBAK 1 1/8" APITONG DECKING, FLUSH BETWEEN MAIN BEAMS AND OUTER BEAMS 4" JR J-BEAM ON 18" CENTERS FABRICATED BEAMS (12) BENT PER SIDE NONE TAPERS TO 4" CHAIN DROPS ON 18" CENTERS

TOOLBOX IN REAR OF GOOSENECK WITH LIGHT AND CHAIN RACK, ALUMINUM

## **REAR DECK** LENGTH

LENGTH	5
LOADED DECK HEIGHT	40"
AXLES	( 2 ) 25,000 LBS NOMINAL (5/8" WALL)
SUSPENSION	HENDRICKSON / 25,000 CAPACITY / AIR RIDE
AXLE SPACING	54"
ABS	4S2M WITH SPRING BRAKES ON 2 AXLES
TIRES	255 / 70R / 22.5 ( H )
WHEELS	8.25 X 22.5 10-HOLE STEEL INSIDE, ALUMINUM POLISHED OUTSIDE DISC WHEELS
BRAKES	16 1/2" X 7"
DRUMS	OUTBOARD
ELECTRICAL	12V SEALED GROTE SYSTEM WITH ( 3 ) TAILLIGHT ALUMINUM PACKAGE
	4" AMBER STROBE TO BE USED AS 3RD TAILLIGHT
DECKING	1 1/8" APITONG DECKING, FLUSH
D-RINGS	( 2 ) BENT IN TAIL CHANNEL
	(1) PAN STYLE IN EACH CORNER

PAINT

**ADDITIONAL** 

LIQUID FILLED AIR GAUGE WITH CHART 4-WAY PLUG AT REAR MANUAL RIDE HEIGHT CONTROL PREP FOR FLIP AXLE RAISE AND LOWER VALVE (2) PAIR OF FLAG HOLDERS

SAME AS 23379

BLACK

DISCLAIMER