

# HALE




## TRAILER

### BRAKE & WHEEL

Resale Inventory  
 A022044-A022046 & A022049  
 VIN: 69498, 69877, 69500, P69876

#### SALES | RENTALS | PARTS | SERVICE

Allentown, PA:	800-383-8894	Jacksonville, FL:	800-828-3055
Baltimore, MD:	888-601-7500	Little Rock, AR:	833-424-8944
Boston, MA:	800-854-5310	Portland, ME:	800-325-4253
Concord, NC:	800-438-2250	Richmond, VA:	866-839-3495
Delmar, DE:	866-486-1400	Scranton, PA:	800-569-1400
Des Moines, IA:	888-673-5011	Springfield, MA:	800-854-5306
Elkton, MD:	800-544-7127	Voorhees, NJ:	866-315-0235

HaleTrailer.com | @haletrailer     

**800-232-6535** \*FINANCING AVAILABLE

Single Drop, Low Profile 60 ton Trailer Standard Equipment

Net Capacity: 60 Tons in 12' of Closed Deck, 2 Point Load Extended  
 Nominal Dimension: OAL 53 ft Closed, 74 ft Open & Width 8.5 ft  
 Capable up to 2-3-2 Configuration

**GOOSENECK:**  
 Fixed Narrow Arched Neck  
 50" Loaded 5th Wheel Height, 18" Setting, 2" King pin  
 Narrow neck, Chain tray provision in neck's rear  
 Two position King Pin at 96" & 108" Swing, Front lugs for flip neck  
 Capable of 60" Flip neck (max) for a total swing of 168"  
 Landing Gear 2-speed, curbside crank handle.

**DECK:**  
 40.5 ft Closed, 61.5 ft Open Length Deck with 8.5 ft Width deck  
 30" loaded deck ht at rated capacity (Front and rear of lower deck)  
 Full Depth Cambered Deck Beams  
 4 Beam design - 100,000 psi yield flanges & 80,000 web minimum  
 I-Beam Cross members on (approx.) 24" Centers  
 1 3/8" Nominal Apitong Decking with Open Center  
 Floor screws used to secure decking on every other cross member

1 Tie Downs per bolster, 1 D ring per Bolster  
 3/8x2 1/2 rub rail, 24" centers for stake pockets & double pipe spools  
 Air operated for extendable length with stops approximately 48"

**KALYN SIEBERT®**

**REAR SECTION:**  
 Axles: Three, 5" round, 5/8" wall 25000# nominal capacity  
 Suspension: Air ride with Oil Seals  
 54.5" axle spacing, Open wheel wells  
 Auto Slack Adjusters  
 12-1/4" X 7-1/2" Air. Parking brakes on all axles  
 Hub: 10 Stud, Hub Piloted, Long studs, Cast Drums  
 245/70 R 17.5 Tires on Steel Wheels  
 Automatic/ Manual ride height control with dump valve & Air Gauge  
 Air Ride Suspension With adjustable Ride Height  
 Rear lugs, air & electrical connections for spreader bar & flip axle

**GENERAL:**  
 12 Volt System with 7 way Sealed Harness  
 LED Sealed beam Lights w/ Modular Harness  
 Strobe light package with toggle switch on rear  
 Epoxy Primer & Black Polyurethane Paint  
 Flag and Flag Holders - 2 Pairs - front deck and rear of trailer  
 Mid-Turn Signal/Clearance Light  
 KS Mud Flaps Oversize load sign Brackets  
 Red & White Conspicuity tape  
 NOTE: Optional Equipment Specifications are on next page

---

Single Drop, Low Profile 60 ton Trailer Optional Equipment

- Extendable Trailer - 3 Axle 60T, 53-74 ✓

**Option**

- 60" Flip Neck ✓
- Spreader Bar - 14'1" Mechanical
- Single Axle Flip ✓
- Single Intermediate / Tag axle

- 60" Axle Spacing (Ext Deck Length Changes)
  - Standard Size - 245/70R 17.5
- Michelin Tires
- Aluminum Outside Wheels (Polished) all Axle
- AirWeigh Load Digital Scale
- Tire Inflation System

Estimated Weight of the Equipment with the options : **38,910 lbs.**

± 3% For trailers other than standard specification, weight and dimensional drawing will be provided by plant after order is received and accepted.

**TANDEM AXLE JEEP**

Capacity - 48K Lbs, 8'6" Wide  
 King pin at 51" unladen, 50" loaded  
 96" & 108" Swing for atleast 14' Front Spread  
 Twin two speed landing gear  
 Sliding fifth wheel, 48" slide  
 Lifting & Stacking D rings 2 pair  
 Axles, Tires and Wheels Match Trailer  
 Wt. 8,500 lbs +3%

**24" FLIP NECK:**

Extension provides 132" swing  
 Wt. 630 lbs +3%

**SPREADER BAR**

Lugs set up for single axle booster  
 14' 1" from rear of last trailer axle to booster axle  
 Two options - Mechanical & Nitrogen assisted  
 Mechanical System : Wt. 2,830 lbs +3%  
 Nitrogen Assisted System: Wt. 6,365 lbs +3%

**60" FLIP NECK:**

Extension provides 168" swing  
 Wt. 2100 lbs +3%

**SINGLE AXLE FLIP**

Capacity - 24K Lbs, 8'6" Wide  
 Lifting & Stacking D rings 1 pair  
 Axles, Tires and Wheels Match Trailer  
 Wt. 3,050 lbs +3%

**INTERMEDIATE SINGLE TAG AXLE:**

Capacity - 24K Lbs, 8'6" Wide  
 Lifting & Stacking D rings 1 pair  
 Axles, Tires and Wheels Match Trailer  
 Wt. 3,250 lbs +3%

**DISCLAIMER**

Specifications are believed to be correct, but may contain errors and/or omissions. Photographs are the representative of the subject equipment but may not be identical. Equipment availability, prices and specifications are subject to change without notice.