

  A022065-A022072 VIN: 65791-65798	SALES RENTALS PARTS SERVICE			
	Allentown, PA: 800-383-8894 Baltimore, MD: 888-601-7500 Boston, MA: 800-854-5310 Concord, NC: 800-438-2250 Delmar, DE: 866-486-1400 Des Moines, IA: 888-673-5011 Elkton, MD: 800-544-7127	Jacksonville, FL: 800-828-3055 Little Rock, AR: 833-424-8944 Portland, ME: 800-325-4253 Richmond, VA: 866-839-3495 Scranton, PA: 800-569-1400 Springfield, MA: 800-854-5306 Voorhees, NJ: 866-315-0235	HaleTrailer.com @haletrailer     	
800-232-6535 *FINANCING AVAILABLE				

We propose to furnish the following described equipment, material and services at prices, terms and delivery set forth below:

PEERLESS TRANSPORT SEMI: Dual Axle, Live Floor, 53' Length, 18.0 Units

STANDARD SPECIFICATIONS: CTSSF-53

- Type: Peerless dual axle, transport semi-trailer, **45 degree front**
- Design: Box design, flat floor, end dump, live floor
- Construction: **Skin stressed .063 prepainted white aluminum with aluminum interior posts (14.5" centers)**
Skins to extend to bottom of lower rail
- Side Rail: **Aluminum**
- Unloading Time: Approximately 8 minutes
- Capacity: 18.0 units (133 cu yd)
- Dimensions: **53' long, 8' 6" wide, 13' 0" high**, 37" king pin location, 36" rear axle from rear of trailer
- Tires: Eight (8) **11:00 x 24.5 radial tires**
- Wheels: Eight (8) 24.5 x 8.25 - 10 hole, 11 1/4" B.C. hi-tensile, **outside aluminum, steel inner, Unimount**
- Axles: 25,000# cap. inserted spindles, 77 1/2" track, 10 stud, 11 1/4" B.C. hubs, outboard drums, oil seals, quick change brake shoes, auto slacks
- Brakes: 16 1/2" x 7" air, CM18 lining, type 3030 air chambers, DOT relay emergency system
- A.B.S.: 2 sensor - 1 module
- Suspension: **Hendrickson Vantraax air ride suspension**, with manual dump valve
- Landing Gear: Two speed, crank on driver's side (**Holland Atlas 55**)
- King Pin: Standard SAE, heat treated, **36" setting, 48" height, 3 I-beams with 5/16" plate**
- Cross Sills & Decking: Keith 7/32" two live floor, **4" Jr. I-Beams on 12" centers** with aluminum sub-deck,
- Top: Flat design, open top, (2) center ties
- Top Cover: **Shur-lok roll over tarp, vinyl material black in color, rear crank**



- Tarp Bows: **6” rise tarp bows located on 4’ centers**
- Rear Door: Full opening, **side hinged, solid freight door with four (4) latches, low mount**
- Dump Stands: Two (2) blades at rear for standard Peerless backstop
- Screens: **Safety screens on front and under drive**
- Ladders: **Catwalk located across front and ladder located at rear**
- Mud Flaps: Legal, rubber
- Wiring: Unitized wiring system, 12 volt, air and light plugs on front center
- Lights: Four (4) legal DOT combination stop, tail and directional lights. Legal DOT clearance lights, **5 clearance lights top and bottom of each side**
- Reflectors: Legal DOT
- Paint: Aluminum natural, **steel components primed and painted grey**
- Weight: Approximately 14,300#

DISCLAIMER

Specifications are believed to be correct, but may contain errors and/or omissions. Photographs are the representative of the subject equipment but may not be identical. Equipment availability, prices and specifications are subject to change without notice.