

HALE

TRAILER

BRAKE & WHEEL



A022234-A022235
VINS: 43713-43714

SALES | RENTALS | PARTS | SERVICE

Allentown, PA:	800-383-8894	Jacksonville, FL:	800-828-3055
Baltimore, MD:	888-601-7500	Little Rock, AR:	833-424-8944
Boston, MA:	800-854-5310	Portland, ME:	800-325-4253
Concord, NC:	800-438-2250	Richmond, VA:	866-839-3495
Delmar, DE:	866-486-1400	Scranton, PA:	800-569-1400
Des Moines, IA:	888-673-5011	Springfield, MA:	800-854-5306
Elkton, MD:	800-544-7127	Voorhees, NJ:	866-315-0235

HaleTrailer.com | @haletrailer     

800-232-6535 *FINANCING AVAILABLE

Base Model: DC53 x 102 17.5 Rear Axle Slider
 CAPACITY Standard Beam Pkg - 80,000 GVWR (60,000 in 10' Span)
 OVERALL LENGTH 53' - Base Weight 11,420#
 TOP DECK-LGTH/HGT 10'6" Length = 59" Height
 LOWER DECK-LGTH/HGT 42'6" Length = Front 36.50", Center 37.50" Rear 35.50" Heights OVERALL
 WIDTH 8' 6"
 KING PIN SETTING 24" - Tapered Pickup Plate
 UPPER COUPLER PLATE 1/4"
 UPPER COUPLER HEIGHT 48"
 FRONT SKIRT Aluminum Front and Corners
 REAR SKIRT Aluminum
 BULKHEAD None
 MAIN FRAME 26" Fab.-PreCamb.I-Beams-(80K Pkg)
 SIDE RAILS 6"-Alum-Extruded W/Double L Track
 TOP DECK FLOOR SILLS 4" Steel I-Beam - 18" O.C.
 LOWER DECK FLOOR SILLS 4" Steel I-Beam 12" O.C. HD Pkg
 COIL HAUL PACKAGE Single Coil Placement - 5 Extra Stud Sils-Ctr On Trailer
 FLOOR DECKING 1-1/8" HD Aluminum W/ 2 Nailer Boards
 WINCHES 12 DOUBLE L
 WINCH TRACK Double L Aluminum - Extruded Siderail C/S & R/S - Both Sides
 TIE BAR D/S & C/S - Full Length Both Sides - 3/8" x 2"
 STRAPS None
 LANDING GEAR Two Speed - Jost A500
 SUSPENSIONS Air Ride - Hendrickson HT 250 - 2 Axles Fixed
 SUSPENSION LOCATION R.A.S.- Cal Legal (Center of KP to Center of Rear Axle 40' in Closed Position)
 AXLES (2) 25K Capacity - Type 30 Chambers - Auto Slacks - ABS - 17.5 Tires
 AXLE SPACING RAS - 2 Position - 54-1/2" & 10' 2" Spread
 LIFT AXLE None
 DUMP VALVE Elect.-Wired Thru Aux 7way Plug @ Front of Trailer-Dump Rear Axle(+9#) SCALES None
 PARKING BRAKES All Axles
 ABS SYSTEM Wabco ABS System 2S/1M
 DUST SHEILDS None
 WHEELS Disc - Hub Piloted - 17.5 (2-AX) - Steel
 TIRES 235/75R 17.5 - Double Coin
 TIRE INFLATION SYSTEM None
 ANTI-SAIL MUD FLAPS Behind Rear Axle
 STAKE POCKETS 24" O.C. Sides & 5 Across Rear
 SPOOL Triangular Shaped
 RUB BAND ALUM 3/8" x 3" - Aluminum - Recessed for DOT Tape
 DOCK BUMPERS Rubber Inboard
 CARGO TIE DOWN 14 Pair of Recessed Chain Ties Evenly Spaced
 CONTAINER TWIST LOCKS None
 TIRE CARRIERS Tire Carrier Positioned In Front of Main Beams Between Landing Gear DUNNAGE
 RACK None
 TOOLBOX MATERIAL None
 TOOLBOX LOCATION None
 LIGHTS Grote Ultra Blue Sealed Wiring Harness- 2 Micros Per Side & Mid Turn-3/3/3 Rear CUSTOM
 LIGHTS None
 PAINT Black - PPG Epoxy Primer and Acrylic Polyurethane - Shot Blasted
 DECAL PACKAGE Standard Dorsey Logo Kit

DISCLAIMER

Specifications are believed to be correct, but may contain errors and/or omissions. Photographs are the representative of the subject equipment but may not be identical.
 Equipment availability, prices and specifications are subject to change without notice.