

# HALE

## TRAILER

### BRAKE & WHEEL



A022247-A022248  
VINS: 000453-000454

#### SALES | RENTALS | PARTS | SERVICE

<b>Allentown, PA:</b>	800-383-8894	<b>Jacksonville, FL:</b>	800-828-3055
<b>Baltimore, MD:</b>	888-601-7500	<b>Little Rock, AR:</b>	833-424-8944
<b>Boston, MA:</b>	800-854-5310	<b>Portland, ME:</b>	800-325-4253
<b>Concord, NC:</b>	800-438-2250	<b>Richmond, VA:</b>	866-839-3495
<b>Delmar, DE:</b>	866-486-1400	<b>Scranton, PA:</b>	800-569-1400
<b>Des Moines, IA:</b>	888-673-5011	<b>Springfield, MA:</b>	800-854-5306
<b>Elkton, MD:</b>	800-544-7127	<b>Voorhees, NJ:</b>	866-315-0235

HaleTrailer.com | @haletrailer

**800-232-6535** \*FINANCING AVAILABLE

**Base Weight:** 11,820

### 30NTT 30 Ton Tridem Non Tilt Tags

#### TRAILER

<b>Overall Length</b>	37 ft. 7 in.
<b>Overall Width</b>	102 in.
<b>Weight lbs +/- 2%</b>	13334, including options
<b>A-Frame</b>	6 ft. 11 in. Hi-Tensile Cold Formed Wide Flange Beam
<b>Hitch</b>	3 in. pintle eye, adjustable 5 position 23 1/2 in. to 32 1/2 in.

#### DECK

<b>Deck Length</b>	24 ft.
<b>Loaded Deck Height</b>	34 in.
<b>Main Frame</b>	Hi-Tensile Wide Flange 14 in. @ 26
<b>Cross Members</b>	Hi-Tensile 6 in. Channel @ 8.2
<b>Side Rail</b>	Hi-Tensile 8 in. Channel @ 11.5 open on inside
<b>Floor</b>	1 3/8 in. x 7 in. Keruing Shiplapped
<b>Landing Gear</b>	*NPO*: Dual 2 Speed Holland Mark V, Galvanized Landing Gear
<b>Step</b>	*NPO*: Bolt on, Located on Front Corner of deck, Driver side and 1 on Passenger side ahead of lead axle

#### SUSPENSION/AXLES

<b>Axles</b>	25,000 lbs Capacity 77.5 in. Track ,1 Lift Axle with Control Box
<b>Spread</b>	49 in.
<b>Suspension</b>	Heavy Duty spring ride., 1 Ridewell RAR 260 Underslung Air ride 25,000lbs. (includes air gauge)
<b>Alum Air Tank</b>	*NPO*: Drain plug with cable
<b>Brakes</b>	Quick Change 12 1/4 in. x 7 in.
<b>Brake Chamber</b>	#3030, All Axles
<b>Air Brake System</b>	2S/1M
<b>Air Tank(s)</b>	Aluminum
<b>Bearings</b>	Oil Bath
<b>Slack Adjusters</b>	Automatic
<b>Hubs &amp; Drums</b>	8 Stud Unimount C / W Cast Drums
<b>Tires</b>	235/75R17.5 16 ply
<b>Wheels</b>	Alum. Wheel Pkg. 17.5 (6 steel, 6 polished)

#### BEAVERTAIL

<b>Length</b>	6 ft. Beavertail, Planked
---------------	---------------------------

#### RAMPS

<b>Length</b>	* 38 in. x 76 in. Wood Filled Air Operated Ramp
---------------	---

#### GENERAL SPECIFICATIONS

<b>Electrical System</b>	Modular, Vapor Proof GROTE Ultra Blue
<b>Lights</b>	LED CMVSS 108 / FMVSS 108
<b>Lights</b>	*NPO*: Amber Flashing Strobe Lights(Mounted in Ramps)
<b>Lights</b>	*NPO*: Switch for strobes mounted in toolbox
<b>Front Connector</b>	SAE J560 7 Pin

**GENERAL SPECIFICATIONS**

<b>Color</b>	Galvanized
<b>Mudflaps</b>	1 set of BWS at rear
<b>Toolbox</b>	Full A Frame mounted with solid bottom and aluminum cover
<b>Load Securement</b>	9 pair of D-rings: 7 pr on main deck, evenly spaced, 1 pr on top of mai beam at headboard, 1 pr on top of A Frame top flange, one on each side of toolbox
<b>Fenders</b>	3/16 in. deck plate

**GVWR Rating is based on standard configuration and a 15% Tongue weight distribution**

**DISCLAIMER**

Specifications are believed to be correct, but may contain errors and/or omissions. Photographs are the representative of the subject equipment but may not be identical. Equipment availability, prices and specifications are subject to change without notice.