

HALE TRAILER BRAKE & WHEEL



A022305-A022307
VIN: 65766-65768

SALES | RENTALS | PARTS | SERVICE

Allentown, PA:	800-383-8894	Jacksonville, FL:	800-828-3055
Baltimore, MD:	888-601-7500	Little Rock, AR:	833-424-8944
Boston, MA:	800-854-5310	Portland, ME:	800-325-4253
Concord, NC:	800-438-2250	Richmond, VA:	866-839-3495
Delmar, DE:	866-486-1400	Scranton, PA:	800-569-1400
Des Moines, IA:	888-673-5011	Springfield, MA:	800-854-5306
Elkton, MD:	800-544-7127	Voorhees, NJ:	866-315-0235

HaleTrailer.com | @haletrailer     

800-232-6535 *FINANCING AVAILABLE

PEERLESS TRANSPORT SEMI: Dual Axle, Live Floor, 48' Length, 16.2 Units

STANDARD SPECIFICATIONS: **CTSSF-48 (South Specs)**

Type:	Peerless dual axle, transport semi-trailer, 45 degree front
Design:	Box design, flat floor, end dump, live floor
Construction:	Skin stressed .063 natural aluminum with aluminum interior posts (14.5" centers) Skins to extend to bottom of lower rail
Unloading Time:	Approximately 8 minutes
Capacity:	16.2 units (119.8 cu yd)
Dimensions:	48' long, 8' 6" wide, 13' 3" high , 37" king pin location, 36" rear axle from rear of trailer
Tires:	Eight (8) 11:00 x 24.5 radial tires
Wheels:	Eight (8) 24.5 x 8.25 - 10 hole, 11 1/4" B.C. hi-tensile steel, Unimount
Axles:	25,000# cap. inserted spindles, 77 1/2" track, 10 stud, 11 1/4" B.C. hubs, outboard drums, oil seals, quick change brake shoes, auto slacks
Brakes:	16 1/2" x 7" air, CM18 lining, type 3030 air chambers, DOT relay emergency system
A.B.S.:	2 sensor - 1 module
Suspension:	Four spring three leaf tandem (Hutch H9700T with slider)
Landing Gear:	Two speed, crank on driver's side (Holland Atlas 55), channel bracing
King Pin:	Standard SAE, heat treated, 37" setting, 49" height, 3 I-beams with 5/16" plate
Cross Sills & Decking:	Keith 7/32" two live floor, 4" Jr. I-Beams on 12" centers with aluminum sub-deck,
Top:	Flat design, open top, single center tie
Top Cover:	Shur-lok roll over tarp, vinyl material black in color, rear crank, <u>flat tarp bows</u>
Rear Door:	Full opening, side hinged, solid freight door with four (4) latches, low mount, <u>offset hinges</u>

Dump Stands: Two (2) blades at rear for standard Peerless backstop

Screens: **Safety screens on front and under drive**

Ladders: **One located at front and one located at rear**

Mud Flaps: Legal, rubber

Wiring: Unitized wiring system, 12 volt, air and light plugs on front center

Lights: Four (4) legal DOT combination stop, tail and directional lights. Legal DOT clearance lights

Reflectors: Legal DOT

Paint: Aluminum natural, **steel components primed and painted BLACK**

Weight: Approximately 14,300#

DISCLAIMER

Specifications are believed to be correct, but may contain errors and/or omissions. Photographs are the representative of the subject equipment but may not be identical.
Equipment availability, prices and specifications are subject to change without notice.