

HALE TRAILER BRAKE & WHEEL



A022370-A022372
VIN: 455-457

SALES | RENTALS | PARTS | SERVICE

Allentown, PA:	800-383-8894	Jacksonville, FL:	800-828-3055
Baltimore, MD:	888-601-7500	Little Rock, AR:	833-424-8944
Boston, MA:	800-854-5310	Portland, ME:	800-325-4253
Concord, NC:	800-438-2250	Richmond, VA:	866-839-3495
Delmar, DE:	866-486-1400	Scranton, PA:	800-569-1400
Des Moines, IA:	888-673-5011	Springfield, MA:	800-854-5306
Elkton, MD:	800-544-7127	Voorhees, NJ:	866-315-0235

HaleTrailer.com | @haletrailer

800-232-6535 *FINANCING AVAILABLE

Base Weight: 12,760

30ART 30 Ton Tridem Air Tilt/Air Ramp Tags

TRAILER

Overall Length	39 ft. 6 in.
Overall Width	102 in.
Weight lbs +/- 2%	13406, including options
A-Frame	6 ft. 11 in. Hi-Tensile Cold Formed Wide Flange Beam
Hitch	3 in. pintle eye, adjustable 5 position 17 in. to 31 in.

DECK

Deck Length	26 ft.
Loaded Deck Height	34 in.
Main Frame	Hi-Tensile Wide Flange 14 in. @ 30
Cross Members	Hi-Tensile 6 in. Channel @ 8.2
Side Rail	Hi-Tensile 8 in. Channel @ 11.5 open on inside
Air Tilt Deck	* 4 Air Bags
Floor	1 3/8 in. x 7 in. Keruing Shiplapped
Landing Gear	Dual Holland Mark V 2 Speed
Step	*NPO*: Bolt on, Located on Front Corner of deck, Driver side and 1 on Passenger side ahead of lead axle

SUSPENSION/AXLES

Axles	25,000 lbs Capacity 77.5 in. Track ,1 Lift Axle with Control Box
Spread	49 in.
Suspension	Heavy Duty spring ride., 1 Ridewell RAR 260 Underslung Air ride 25,000lbs. (includes air gauge)
Alum Air Tank	*NPO*: Drain plug with cable
Brakes	Quick Change 12 1/4 in. x 7 in.
Brake Chamber	#3030, All Axles
Air Brake System	2S/1M
Air Tank(s)	Aluminum
Bearings	Oil Bath
Slack Adjusters	Automatic
Hubs & Drums	8 Stud Unimount C / W Cast Drums
Tires	235/75R17.5 16 ply
Wheels	Alum. Wheel Pkg. 17.5 (6 steel, 6 polished)

BEAVERTAIL

Length	6 ft. @ 6 degree slope, Planked in
---------------	------------------------------------

RAMPS

Length	38 in. x 76 in. Air Operated Planked
Brackets	*NPO*: To hold ramp brace when not in use, 1 per side

GENERAL SPECIFICATIONS

Electrical System	Modular, Vapor Proof GROTE Ultra Blue
Front Connector	SAE J560 7 Pin
Lights	*NPO*: Switch for strobes mounted in toolbox

GENERAL SPECIFICATIONS

Lights	Amber Flashing Strobe (Mounted in Ramps)
Finishing	Preparation by Steel Shot Blast, Commercial / Industrial Topcoat, Oven Baked
Color	Black
Mudflaps	1 set of BWS at rear
Toolbox	Full A Frame mounted with solid bottom and cover
Load Securement	11 pair of D-rings: 7 pr main deck, evenly spaced; 2 pr on B/T; 1 pr on main beam at headboard, 1 pr on top of A Frame top flange on each side of the toolbox
Fenders	3/16 in. deck plate

GVWR Rating is based on standard configuration and a 15% Tongue weight distribution

DISCLAIMER

Specifications are believed to be correct, but may contain errors and/or omissions. Photographs are the representative of the subject equipment but may not be identical. Equipment availability, prices and specifications are subject to change without notice.