

# HALE

## TRAILER

### BRAKE & WHEEL



**A022549-A022550**  
**VIN: 000476-000477**

#### SALES | RENTALS | PARTS | SERVICE

<b>Allentown, PA:</b>	<b>800-383-8894</b>	<b>Jacksonville, FL:</b>	<b>800-828-3055</b>
<b>Baltimore, MD:</b>	<b>888-601-7500</b>	<b>Little Rock, AR:</b>	<b>833-424-8944</b>
<b>Boston, MA:</b>	<b>800-854-5310</b>	<b>Portland, ME:</b>	<b>800-325-4253</b>
<b>Concord, NC:</b>	<b>800-438-2250</b>	<b>Richmond, VA:</b>	<b>866-839-3495</b>
<b>Delmar, DE:</b>	<b>866-486-1400</b>	<b>Scranton, PA:</b>	<b>800-569-1400</b>
<b>Des Moines, IA:</b>	<b>888-673-5011</b>	<b>Springfield, MA:</b>	<b>800-854-5306</b>
<b>Elkton, MD:</b>	<b>800-544-7127</b>	<b>Voorhees, NJ:</b>	<b>866-315-0235</b>

HaleTrailer.com | @haletrailer   
**800-232-6535** \*FINANCING AVAILABLE

**Base Weight:** 12,300

#### 30 ANR 30 Ton Tridem Air Tilt/No Ramp Tags

##### TRAILER

<b>Overall Length</b>	37 ft. 6 in.
<b>Overall Width</b>	102 in.
<b>Weight lbs +/- 2%</b>	13006, including options
<b>A-Frame</b>	6 ft. 11 in. Hi-Tensile Cold Formed Wide Flange Beam
<b>Hitch</b>	3 in. pintle eye, adjustable 5 position 17 in. to 28 in.

##### DECK

<b>Deck Length</b>	24 ft.
<b>Loaded Deck Height</b>	34 in.
<b>Main Frame</b>	Hi-Tensile Wide Flange 14 in. @ 30
<b>Cross Members</b>	Hi-Tensile 6 in. Channel @ 8.2
<b>Side Rail</b>	Hi-Tensile 8 in. Channel @ 11.5 open on inside
<b>Air Tilt Deck</b>	* 4 Air Bags
<b>Floor</b>	1 3/8 in. x 7 in. Keruing Shiplapped
<b>Rear</b>	Wedge Style bumper with air assisted tilt deck for ground loading
<b>Landing Gear</b>	*NPO*: Dual 2 Speed , Galvanized Landing Gear
<b>Step</b>	*NPO*: Bolt on, Located on Front Corner of deck, Driver side and 1 on Passenger side ahead of lead axle

##### SUSPENSION/AXLES

<b>Axles</b>	25,000 lbs Capacity 77.5 in. Track ,1 Lift Axle with Control Box
<b>Spread</b>	49 in.
<b>Suspension</b>	Heavy Duty spring ride., 1 Ridewell RAR 260 Underslung Air ride 25,000lbs. (includes air gauge)
<b>Alum Air Tank</b>	*NPO*: Drain plug with cable
<b>Brakes</b>	Quick Change 12 1/4 in. x 7 in.
<b>Brake Chamber</b>	#3030, All Axles
<b>Air Brake System</b>	2S/1M
<b>Air Tank(s)</b>	Aluminum
<b>Bearings</b>	Oil Bath
<b>Slack Adjusters</b>	Automatic
<b>Hubs &amp; Drums</b>	8 Stud Unimount C / W Cast Drums
<b>Tires</b>	235/75R17.5 16 ply
<b>Wheels</b>	Alum. Wheel Pkg. 17.5 (6 steel, 6 polished)

##### BEAVERTAIL

<b>Length</b>	6 ft. @ 8 degree slope, Self Cleaning Outside , Planked in inside
---------------	---

##### GENERAL SPECIFICATIONS

<b>Electrical System</b>	Modular, Vapor Proof GROTE Ultra Blue
<b>Front Connector</b>	SAE J560 7 Pin
<b>Lights</b>	LED CMVSS 108 / FMVSS 108
<b>Lights</b>	Amber Flashing Strobe Lights(Mounted in Bumper)
<b>Color</b>	Galvanized

**GENERAL SPECIFICATIONS****Mudflaps**

1 set of BWS at rear

**Toolbox**

Full A Frame mounted with solid bottom and aluminum cover

**Load Securement**

9 pair of D-rings: 7 pr on main deck, evenly spaced; 1 pr on top of main beam at headboard; 1 pr on top of A frame top flange, one on each side of toolbox (Ref - wo#10015744-47)

**Fenders**

3/16 in. Deck plate

**GVWR Rating is based on standard configuration and a 15% Tongue weight distribution****DISCLAIMER**

Specifications are believed to be correct, but may contain errors and/or omissions. Photographs are the representative of the subject equipment but may not be identical. Equipment availability, prices and specifications are subject to change without notice.