



A022617-A022618 VIN: 5A5021-5A5022

## SALES | RENTALS | PARTS | SERVICE

Allentown, PA: 800-383-8894 Jacksonville, FL: 800-828-3055 Baltimore, MD: 888-601-7500 Little Rock, AR: 833-424-8944 Boston, MA: 800-854-5310 Portland, ME: 800-325-4253 Concord, NC: Richmond, VA: 866-839-3495 800-438-2250 Delmar, DE: 866-486-1400 Scranton, PA: 800-569-1400 Des Moines, IA: 888-673-5011 Springfield, MA: 800-854-5306 Elkton, MD: Voorhees, NJ: 800-544-7127 866-315-0235

HaleTrailer.com | @haletrailer f 쭞 🛅 🎯 🔠

**800-232-6535** \*FINANCING AVAILABLE

Renegade X20 Extendable Deck, Air Tandem, 20 inch Loaded Deck Height, (Model: RENEGADE X20)	Mechanical Gooseneck
(Hoden Kenzende Azo)	
	Est. Wt.: 23,750# +/- 39
TRAILER - GENERAL	ı
Capacity: 40 tons in 16-foot length - GAWR and tire ratings determine legal loads	
Load Base: 16-foot rigid 2-point load centered in deck	
Length (Trailer Only): 48 feet 0 inches	
Width: 8 feet 6 inches	
Compatibility: Designed to accept optional flip box (gooseneck extension) and third flip axle	
Length / Width: 47 feet 11 inches ** unless 34 60 deck length selected then overall length is 53 - 102 inches wide	
GOOSENECK	
Gooseneck Design: Mechanical removable with removable fifth wheel guide rollers - Combination figure-8 plate which provides 50 inches and 52 inches loaded - Swing radius of 81 inches	
Gooseneck Platform: Full width gooseneck platform with 1 1/8 inch wood floor	
Tool Box: None	
Gooseneck Fenders: Aluminum fenders at rear of gooseneck	
DECK	-
Deck Design: Flat level telescopic deck design	
Deck Length: 34 feet 0 inches clear deck length (retracted) - 60 feet 0 inches	
(extended) ** Note trailer overall length is 53 feet	ļ
Loaded Deck Height: 20 inches with 6 inches ground clearance	
Flooring: 1 3/8 inch nominal wood (full width)	
Recessed Floor Mounted D-Ring Package: None	
Crossmembers: On 24 inch centers	
Front Ramps: None, front of deck sloped top down to assist in loading with traction cleats	
Extension Brackets: Outriggers - 14 pair - 28 total removable swing type, 1 pair - 2 total removable hook-on type	
Front Bogie Ramp: Sloped steel bogie ramp (full width)	
Deck to Bogie Connection: Fixed	
AXLES	1
Number of Axles: 2	
<b>Axle Capacity:</b> 25,000 lb. nominal capacity per axle NOTE: GAWR determined by suspension type, brakes, tires and other components.	
Axle Spread: 54.5 inches spread (between axles)	
<b>Brakes:</b> 16.5 inches $x$ 7 inches with 5.5 inches autoslacks - heavy duty brake drums - outboard mount	
Spring Brakes: Spring brakes on 2 axles	
Dust Shields: None	l
SUSPENSION	
Framework: All main longitudinal members fabricated with 100,000# minimum yield steel flanges with 50,000# webs	
Suspension: Air ride with automatic controls	
First Axle Lift: Chain lift included on first axle when 34ft deck is selected	

ABS: 4S/2M system without diagnostic tool and cable		
Load Scale: None Standard		
WHEELS AND TIRES		
Wheels: 8.25 x 22.5 LvL One buffed outside/steel inside - hub-piloted		
Tires: 255/70R 22.5 H ply OEM Standard		
Hubodometer: None Standard		
Tire Inflation: None Standard		
REAR BRIDGE		
Covered Rear Bogie: Rear bogie platform with 1 1/8 inch wood floor		
Rear Bogie Height: 41 inches		
Bumper: 3 tail light package		
Connections for Future Axle Attachment: Air and electrical connections to go along		
with connecting ears		
Mini Boom Trough & Traction Cleats: None		
Liquid Filled Gauge: Included		
Accent Package: Stainless steel accent package		
LIGHTING		
<b>Electrical System:</b> DOT sealed beam and harness with LED lights and 4 inch flush mounted battery powered amber strobes		
Electrical Receptacle: J560 7-pin connector		
Marker Lights: 8 marker lights per side including mid-turn		
Additional Marker Lights: None Standard		
PAINT		
Paint: Fontaine black polyurethane enamel		
MISCELLANEOUS		
Lash Rings: 9 pair - 18 total		
Flag Holders: 2 pair flag holders		
VIN Plate: Bilingual VIN plate		
Registration/Document Holder: Registration/document holder installed		