

A022627-A022628 VIN: 232313-232314

## SALES | RENTALS | PARTS | SERVICE

Allentown, PA: 800-383-8894 Jacksonville, FL: 800-828-3055 Baltimore, MD: 888-601-7500 Little Rock, AR: 833-424-8944 Boston, MA: 800-854-5310 Portland, ME: 800-325-4253 Concord, NC: 800-438-2250 Richmond, VA: 866-839-3495 Delmar, DE: 866-486-1400 Scranton, PA: 800-569-1400 Des Moines, IA: 888-673-5011 Springfield, MA: 800-854-5306 Voorhees, NJ: Elkton, MD: 800-544-7127 866-315-0235

HaleTrailer.com | @haletrailer f 쭞 🛅 🎯 🤠

	800-232-6535 *FINANCING AVAILABLE
ITEM	DESCRIPTION
TYPE	DIN ON AVI E FOR DI ATFORM
	PIN ON AXLE FOR PLATFORM  •• manac
DIMENSIONS	04.4/0
LENGTH WIDTH	61 1/2". 102".
WILLI	102 .
COUPLING	
COUPLER PLATE	For anchor joints, 4 x 2" dia. rods and bushings.
STRUCTURE	
FLANGES	1/2" x 6", 100 000 psi steel.
WEB	3/16" plate, 80 000 psi steel. 13 1/2" high.
ENDS	
BUMPER	Rectangular steel tubing.
	Including supports with flag and excessif width sign.
ELECTRICAL	
FRONT CONNECTOR	Cord with 7 ways connector.
ELECTRICAL SYSTEM	Shock proof lights, polycarbonate lenses, in compliance with CMVSS 108.
MAIN SYSTEM	Grote Ultra blue LED, sealed beams, in a closed back rubber grommet.
	(tail lights with male pins #54332, markers #47122 (2 1/2" dia.),
	licence light #60280-M).
STROBE LIGHTS	(2), installed (1) on each side, (Grote 77353 amber) (stainless steel rings)
SWITCH	Sealed, to activate strobe lights, installed **on rear rail**.
BASIC SUSPENSION	
BOGIE	Fixed.
SUSPENSION	Hendrickson HT-250US (9), single.
U-BOLTS	With nuts at top.
SPRINGS	Air.
AXLE(S)	Hendrickson, HP-S506, 27 000 lbs. capacity.
SPIDERS	Welded.
CAM SHAFTS	28 splines.
TRACK	77 1/2".
DUST SHIELDS	None (Hendrickson axles).
BRAKES	16 1/2" standard, long life H26-HXS Hendrickson lining.
READINGS	HM 518445

**BEARINGS** HM 518445. **SLACK ADJUSTERS** Meritor, automatic, 28 splines. **SEALS** Stemco, "Guardian" type, with "Gearlube" mineral oil, SAE 80W90. **BRAKE CHAMBERS** T.S.E. brake, "Omnibrake" (30-30), long stroke. (4 years warranty by T.S.E. for parts only). **HUBS AND DRUMS** WEBB, 10 studs disc hubs, balanced drums 117 lbs, outboard mount, 285.75mm B.C., single flange nuts. For dual steel wheels or single wheels. (Heavy duty 25000 lbs cap.) (Bearings HP). **RIMS** 22.5 x 8.25, disc (10 holes), 285.75mm B.C., single flange nuts, 2 hand holes. Standard duty with light steel.

Continental, 275/70 R 22.5 HSR2 SA

18 ply

(38.0")

**TIRES** 





ITEM	DESCRIPTION	
AIR SYSTEM		
GLAD HANDS	Fix.	
AIR VALVES	Sealco, synflex 3/8" diameter.	
ACCESSORIES		
REGISTRATION HOLDER	One plastic, Betts-PS-1 or equivalent.	
MUD FLAPS	One set, rubber with Manac logo and vertical grooves to reduce spray.	
FINISHING		
PAINT	No paint nor primer applied on. Structure prepared and shipped ready to be galvanized.	
AXLE(S) PAINTED	Color: Grey, code: PPG Q37-939514.	
HUBS	Color: Grey, code: PPG Q37-939514.	
WHEELS OR RIMS	White.	
RETROREFLECTIVE TAPES	Conspicuity striping in compliance with CMVSS 108.	
	Gray and red, each side, fully covers rear bumper.	
PAINT	V.I.N. plate to be stick on an aluminum plate riveted on the frame.	
ADDITIONAL OPTIONS	SAME AS U#215309	
UNIT COUPLED TO	Job:	
	Q#242712	
	Q#242710	
R	Due to the deep backlogs, material/component availability, price fluctuation	
	and transportation costs, Manac reserves the right to adjust the price based	
	these instabilities. If needed, Manac will contact the dealer or customer app	
	3 months prior to assembly with revised pricing, or a change in components.	
	At that time, the customer will have the option to accept the change or cance	
	This will prevent and any possible cancellation fees from our suppliers.	
CONFORMITY	This semi-trailer does not comply with GHG regulations. Should GHG	
	regulations come into force prior to the production of the trailer(s), Manac	
	will have the obligation to ensure the trailer(s) produced meet minimum	
	GHG guidelines. Any modifications required to meet the GHG regulations	
	will be added to the initial purchase price and charged back to the	
	customer.	