

Base Model: LB55 - 18DD Serial #: 44028 - 44030 components description CAPACITY 55 Tons in 16' Concentrated Load **OVERALL LENGTH 53'** OVERALL WIDTH 8' 6" DECK LENGTH 25'4" DECK HEIGHT 18" - Loaded DECK FLOORING Apitong - 1 1/2" - Covering Outside Only MAINBEAMS 12" Fabricated I-Beams - Positive Camber SIDE RAILS 12" Fabricated I-Beams - Positive Camber GOOSENECK Non-Ground Bearing Hydraulic Detachable Neck - With Honda Pony Motor **KING PIN SETTING 16"** KING PIN PLATE 5/16 Plate **KING PIN SWING RADIUS 108"** KING PIN HEIGHT 48" (5 Postions) DOVETAIL No WHEEL WELL Open with Load Bearing Bolsters **Open Wheel Wells.** BOOM TROUGH Open - "V" Crossmembers w/ Steel Grating Center REAR LOADING RAMP No FRONT LOADING RAMP Front Flip Ramps - 18" x 24" - Steel w/ Traction Bars LANDING GEAR None D RING 16 WIDENING BRACKET 11 Pair of 12" Brackets (extends deck width 2') TOOL BOX Tool Box in Front & Rear of Deck AXLE (3) 25,000 lb. Capacity w/ 54 1/2" Axle Spacings, Auto Slack, SETUP FOR 4TH FLIP OR SB No 4TH FLIP AXLE OR SB No SUSPENSION Air Ride - Lift Rear Axle WHEELS Disc - Hub Piloted - POLISHED ALUMINUM on 6 Outside wheels TIRES 275/70R22.5 PARKING BRAKES Type 30/30 Spring Brakes - 2 Axle WIRING D.O.T Sealed Wiring Harness LIGHTS LED w/ Amber Strobes in Bumper & Battery Back-Up

DISCLAIMER