

# HALE TRAILER BRAKE & WHEEL








A022753-A022758

VIN: 24244-24249

SALES | RENTALS | PARTS | SERVICE

<b>Allentown, PA:</b>	800-383-8894	<b>Jacksonville, FL:</b>	800-828-3055
<b>Baltimore, MD:</b>	888-601-7500	<b>Little Rock, AR:</b>	833-424-8944
<b>Boston, MA:</b>	800-854-5310	<b>Portland, ME:</b>	800-325-4253
<b>Concord, NC:</b>	800-438-2250	<b>Richmond, VA:</b>	866-839-3495
<b>Delmar, DE:</b>	866-486-1400	<b>Scranton, PA:</b>	800-569-1400
<b>Des Moines, IA:</b>	888-673-5011	<b>Springfield, MA:</b>	800-854-5306
<b>Elkton, MD:</b>	800-544-7127	<b>Voorhees, NJ:</b>	866-315-0235

HaleTrailer.com | @haletrailer     

**800-232-6535** \*FINANCING AVAILABLE

## XL SPECIALIZED TRAILERS

### XL 70 HDG: Mini-Deck

<b>OVERALL LENGTH</b>	53'
<b>OVERALL WIDTH</b>	102"
<b>CAPACITY</b>	70,000 LB DISTRIBUTED; 60,000 LB IN 16'
<b>WEIGHT +/- 3%</b>	20,850 LB
<b>GOOSENECK</b>	
<b>STYLE</b>	FULL WIDTH SCRAPER
<b>LENGTH</b>	11'
<b>KINGPIN SETTING</b>	16"
<b>SWING CLEARANCE</b>	86"
<b>5TH WHEEL HEIGHT</b>	49" W/ 5 VARIABLE RIDE HEIGHT POSITIONS
<b>HYDRAULICS</b>	13 HP HONDA POWER UNIT, DUAL HYDRAULICS WITH ALUMINUM COVER
<b>DECKING</b>	1 1/8" APITONG DECKING FLUSH
<b>D-RINGS</b>	( 2 ) BENT D-RINGS PER SIDE ( 1 ) PAN STYLE IN EACH CORNER
<b>MAIN DECK</b>	
<b>LENGTH</b>	3 BEAM DESIGN
<b>LOADED DECK HEIGHT</b>	33" WITH 32' 6" OF CLEAR DECK
<b>DECKING</b>	12" W 4" GROUND CLEARANCE STEEL DECKING BETWEEN MAIN BEAMS WITH DURABAK 1 1/8" APITONG DECKING, FLUSH BETWEEN MAIN BEAMS AND OUTER BEAMS
<b>CROSSMEMBER</b>	4" JR. I-BEAM ON 18" CENTERS MID-HEADER IN MAIN DECK
<b>BEAMS</b>	( 3 ) 8" FAB BEAMS
<b>D-RINGS</b>	( 12 ) BENT D-RINGS PER SIDE
<b>CHAIN DROPS</b>	18" CENTERS - OUTSIDE BEAMS
<b>OUTRIGGERS</b>	NONE
<b>RAMPS</b>	TAPERS TO 4"
<b>REAR DECK</b>	
<b>LENGTH</b>	9'
<b>LOADED DECK HEIGHT</b>	40"
<b>AXLES</b>	( 2 ) 25,000 LBS. NOMINAL, ( 5/8" WALL)
<b>SUSPENSION</b>	HENDRICKSON / 25,000 CAPACITY / AIR RIDE
<b>AXLE SPACING</b>	54"
<b>ABS</b>	4S2M WITH SPRING BRAKES ON ( 2 ) AXLES
<b>TIRES</b>	255 / 70R / 22.5 ( H )
<b>WHEELS</b>	8.25 X 22.5 10-HOLE PILOT MOUNT POLISHED ALUMINUM OUTSIDE; STEEL INSIDE, DISC
<b>BRAKES</b>	16 1/2" X 7"
<b>DRUMS</b>	OUTBOARD
<b>ELECTRICAL</b>	12V SEALED GROTE SYSTEM WITH ( 3 ) TAILLIGHT ALUMINUM PACKAGE 4" AMBER STROBE TO BE USED AS 3RD TAILLIGHT
<b>DECKING</b>	1 1/8" APITONG DECKING, FLUSH
<b>D-RINGS</b>	( 1 ) PAN STYLE D-RING IN EACH CORNER ( 2 ) BENT D-RINGS IN TAIL CHANNEL
<b>PAINT</b>	BLACK
<b>ADDITIONAL</b>	
	MANUAL RIDE HEIGHT CONTROL ( 2 ) PAIR OF FLAG HOLDERS PREP FOR FLIP AXLE RAISE AND LOWER VALVE LIQUID FILLED AIR GAUGE WITH CHART 4-WAY PLUG AT REAR
	REFERENCE 24129

#### DISCLAIMER

Specifications are believed to be correct, but may contain errors and/or omissions. Photographs are the representative of the subject equipment but may not be identical. Equipment availability, prices and specifications are subject to change without notice.