

HALE

TRAILER

BRAKE & WHEEL



Resale Inventory
A022798-A022799
VIN: 37645 & 37646

SALES | RENTALS | PARTS | SERVICE

Allentown, PA:	800-383-8894	Jacksonville, FL:	800-828-3055
Baltimore, MD:	888-601-7500	Little Rock, AR:	833-424-8944
Boston, MA:	800-854-5310	Portland, ME:	800-325-4253
Concord, NC:	800-438-2250	Richmond, VA:	866-839-3495
Delmar, DE:	866-486-1400	Scranton, PA:	800-569-1400
Des Moines, IA:	888-673-5011	Springfield, MA:	800-854-5306
Elkton, MD:	800-544-7127	Voorhees, NJ:	866-315-0235

HaleTrailer.com | @haletrailer
800-232-6535 *FINANCING AVAILABLE

Model: T3-35CC-HRG-T1
Capacity in tons: 35
Flip axle: S/N 37646

1. GOOSENECK

Gooseneck design
 Loaded 5th wheel height
 Swing radius
 Support cylinder
 Power source
 Gooseneck locks
 Electrical receptacle
 Coverplate
 Additional gooseneck specifications

Ratchet
 51"
 90"
 Hydraulically operated with 4" x 3" cylinder mount cross member
 Hydraulic couplings: 3/4" fixed at front with piping for wet line
 Ratchet
 Seven pin connector
 Aluminum
 1) Full penetration weld on gooseneck gusset
 2) Base pivot tube reinforcement

2. DECK

Deck section design
 Deck section length
 Deck section width
 Loaded road clearance
 Loaded deck height
 Flooring
 Gooseneck/deck connection
 Deck/rear bridge connection
 Outriggers
 Reinforced top flange of sidemember
 Slope front of deck top down
 Heavy duty front folding ramps
 Expanded metal
 Additional deck specifications

Four beam
 26'-0" (25'-6" clear)
 8'-6"
 6"
 22"
 1-1/2" apitong secured with deck screws; no lumber between mainbeams
 Horizontal pin and plate with remote lock
 Fixed/welded
 12" swinging/removable with double hook-on at front of deck
 None
 With smoothplate & traction bars
 32" wood filled
 Between mainbeams 1st deck section at front
 None

3. REAR BRIDGE

Rear bridge section width
 Loaded rear bridge height
 Number of axles
 Axle spacing
 Axle capacity
 Brakes
 Anti-lock brake system
 Wheels

8'-6"
 36"
 3
 54"
 25,000# GAWR = 20,280#
 16-1/2" x 7" air actuated with spring brakes on one axle
 Two (2) sensor, one (1) modulator system
 Ten (10) stud; 285.75mm B.C. aluminum disc hub piloted system with oil seals, inner aluminum wheels polished, outer aluminum wheels Dura-Bright
 Twelve (12) 255/70R22.5 (H) 16PR radials
 Ridewell air with 3rd axle (SN37646) flip-up and removable, use chrome tapered connecting pins
 Manual
 New style +3", -3" with override chains on all axles

Tires
 Suspension

Exhaust Valve
 Manual raising & lowering (+3"/-3")

Suspension options	None
Rear Bridge Center Section	Boom well, cross members recessed - recess 1st member additionally
Wide center bolster	With chain slots and flagholder slots
Rear half bolster	Rear of axle 2 & 3
Front bridge ramp	Sloped to deck outboard of mainbeams with smoothplate and traction bars
Fenders	None
Additional rear bridge specifications	1) - Connections for 3rd axle, includes ears and air/electrical connections 2) - Omit 1st cross member in rear bridge section (shock mount cross member)

4. GENERAL

Lights and wiring	12 volt system with the following: All lights to be L.E.D. including mid-turn, excluding license plate light 3 marker lights each side of deck including mid-turn strobe lights and switch at rear of axle 2 & 3 Battery back-up system with switch at rear to flash all marker/tail lights and strobe lights, battery mounted in battery box.
Paint	Standard Talbert black, R-Cure 800 series paint
Lash rings	10 Total 4 each side of deck (bent style), 8 total 2 at rear of axle 3 (bent style), 2 total
Estimated empty weight	17,890#
Additional general specifications	None

DISCLAIMER

Specifications are for the equipment at the time it was produced and may not accurately reflect its current condition. Photographs are the representative of the subject equipment but may not be identical. Equipment availability, prices and specifications are subject to change without notice.