

# HALE TRAILER BRAKE & WHEEL



A022865-A022873

SALES | RENTALS | PARTS | SERVICE

Allentown, PA:	800-383-8894	Jacksonville, FL:	800-828-3055
Baltimore, MD:	888-601-7500	Little Rock, AR:	833-424-8944
Boston, MA:	800-854-5310	Portland, ME:	800-325-4253
Concord, NC:	800-438-2250	Richmond, VA:	866-839-3495
Delmar, DE:	866-486-1400	Scranton, PA:	800-569-1400
Des Moines, IA:	888-673-5011	Springfield, MA:	800-854-5306
Elkton, MD:	800-544-7127	Voorhees, NJ:	866-315-0235

HaleTrailer.com | @haletrailer     

**800-232-6535** \*FINANCING AVAILABLE

## Velocity 53' Spring Slider (Model: HAVSF22SST)

<b>Length / Width:</b> 53 feet x 102 inches
<b>Suspension Type:</b> Sliding spring tandem; This Trailer Design Does NOT Meet Proposed GHG2 Compliance Requirements
<b>Frame Rating:</b> 80,000 lbs distributed - GAWR and tire ratings determine legal payloads
<b>Flooring:</b> 1 1/8 inch wood
<b>Crossmembers:</b> 12 inch centers - 4 inch jr. I-steel
<b>Side Rails:</b> 6 inch structural channel @ 6.5 lbs/ft
<b>Stake Pockets:</b> 3/16 inch steel on 24 inch centers
<b>Pipe Spools:</b> Double between stake pockets
<b>Rubrail:</b> 3/8 inch x 2 1/2 inch steel
<b>Main Beams:</b> 130K load bearing flanges
<b>Kingpin:</b> 30 inches
<b>Loaded Fifth Wheel Height:</b> 49 inches
<b>Landing Gear:</b> OEM Standard with Forward & Rear Bracing
<b>Knee Braces:</b> Fabricated on approx. 60 inch C/C
<b>Bulkheads:</b> None standard
<b>Bulkhead Pockets:</b> 4 - F-5 DOT-type steel
<b>Number of Axles:</b> 2
<b>Axle Spindle:</b> Tapered
<b>Brakes:</b> Spring brakes, auto slacks
<b>Air Line Filters:(2) Meritor In-line type installed</b>
<b>ABS:</b> 4S/2M - no cable or tool
<b>Axle Spread:</b> 49 inches (C/L kingpin to C/L rear axle in front position is 40 feet or less)
<b>Hub and Drums:</b> 10-hole hub-piloted with outboard cast drums
<b>Wheel Ends:</b> Oil in hubs
<b>Wheels:</b> 22.5 x 8.25 steel disc wheels - pre-painted white - STANDARD
<b>Tires:</b> 11R 22.5 14PR OEM standard tires
<b>Tire Inflation System:</b> None standard
<b>Suspension Detail:</b> OEM Standard 3-leaf spring slider - 60 inches adjustable
<b>Front Corners:</b> Tapered
<b>Electrical System:</b> LED: 3 lights/side, 3 lights/side on rear
<b>Paint:</b> Black urethane with Velocity decals - STANDARD
<b>Conspicuity Tape:</b> Per NHTSA specs - installed on rubrails
<b>Bumper:</b> Weld-on type - meets underride requirements
<b>Mudflaps:</b> 1 set OEM standard behind rear axle
<b>Spare Tire Carrier:</b> None standard
<b>Winch Track:</b> Steel on road side
<b>Sliding Winches: (12) with Zinc Finish</b>
<b>27 foot Winch Straps:</b> None standard
<b>30 foot Winch Straps:</b> None standard
<b>Dock Bumpers:</b> 1 pair rubber on rear
<b>Hubodometer:</b> None standard
<b>Registration Holder:</b> Install registration holder - OEM standard
<b>Tool Box:</b> None standard
<b>VIN Plate:</b> Bilingual US/Canadian VIN plate
<b>Unit Numbers &amp; Decals:</b> Not installed

### DISCLAIMER

Specifications are believed to be correct, but may contain errors and/or omissions. Photographs are the representative of the subject equipment but may not be identical. Equipment availability, prices and specifications are subject to change without notice.