B	В АКЕ & WHEEL А023037-А023048 VIN: 22157-22158 А80HDGC (Alpha Series H	Allentown, PA: Baltimore, MD: Boston, MA: Concord, NC: Delmar, DE: Des Moines, IA: Elkton, MD: HaleTrailer.c 800 - 232 -	6535	I PARTS I SERVICE Jacksonville, FL: 800-828-3055 Little Rock, AR: 833-424-8944 Portland, ME: 800-325-4253 Richmond, VA: 866-839-3495 Scranton, PA: 800-569-1400 Springfield, MA: 800-854-5306 Voorhees, NJ: 866-315-0235 etrailer (*) (*) * FINANCING AVAILABLE	
. .			lacitable		
Capacity Concentrated OAL	80,000 lbs. 70,000 lbs. in 16' 48' OAW 102''				
Gooseneck	 10' 5" Hydraulic Detachable 49" 5th Wheel Height 15" King Pin 80" Swing Clearance 2 Bent D-Rings Per Side lighning holes each side platform 5 Position Ride Height Full Width Platform - 1 1/8" Apiton Stainless Mudflaps LED Work Light on Rear Platform 	Sub Fr	ame	9' Long 40" Loaded Deck Height Full Width Decking - 1 1/8" Apitong 1 Pair Flag Holders 1 pair Stake Pockets in Tail Channel Two Pair of Chain Drops in Center One Pair of Pan D-Rings at Rear Frame Reinforcement for Flip Axle	
Main Deck	Axles and Suspension				
	 28' 7" Length 12" Fabricated I-Beams 18" Loaded Deck Height 6" Ground Clearance 6"/4" JRI Beam Cross Members AL⁻ 8 Bent D-Rings per Side Chain Slots on 24" Centers each side 1 1/8" Apitong Flush Decking-Full W Front Ramps tapered to 4" W/Track Removable Swingout Outriggers or 	Γ on 12" Cento le Vidth tion Bars	·	2 - 25,000 lb Axles 54" Axle Spacing Cush Suspension-25k Air 16 1/2" x 7" Drum Brakes 4S2M ABS Spring Brakes on Both Axles Raise & Lower Valve Manual Ride Height Control Airweigh Quickweigh Scale 255/70R22.5 Tires 8.25 x 22.5 Steel Wheels	
Lighting	2 Tail Light Package with Stainless 2 Pr. Side Markers/ 1 Pr. Mid-Turns Grote Ultra Blue-Seal Wire Harness	s in Deck		6.25 X 22.5 Steel Wheels	
Gooseneck			General		
Honda Pony Motor with Stainless Lid			4" Amber Strobe Light Aluminum polished wheels out		
Tool Bo	eck m, 15" LDH, 5" GC x in Front of Deck x in Rear of Deck		Paint Black		

DISCLAIMER

Specifications are believed to be correct, but may contain errors and/or omissions. Photographs are the representative of the subject equipment but may not be identical. Equipment availability, prices and specifications are subject to change without notice.