



Hale Trailer Brake & Wheel
023542-023544

OLB32-102 "Advantage Series" Live Bottom Trailer

10192-OLB32-102

10192 - Kingpin to Center of Last Axle: 31' 11"	36" Direct Drive Live Floor
Overall Length: 36' 7"	3" Pitch Roller Chain
Overall Height (w/ 48" fifth wheel and no hopper extensions): 9' 2"	2 Ply 3/8" Belt w/ Steel Z-Bar Support
Overall Width: 102"	Hydraulic Tap Chain Oiler
Capacity (w/o extensions): 29 cubic yards	Center Mud Flap

Item #	Category	Description	Weight (lbs)	Qty
10192	Materials Hauling	OLB32-102 "Advantage Series" Live Bottom Trailer	13,235	
10198	Fifth Wheel / King Pin	48" 5th-wheel height		
12806	Fifth Wheel / King Pin	Removeable King Pin		
10201	Hopper Sheets	Rear Hopper Sheets: .160" AR450		
10221	Hopper Extensions	6" Steel Extensions w/ Tarp Shelf (+ 5 cubic yards)	268	
10236	Exterior Sheeting	Aluminum Exterior Sheeting w/ Insulation	278	
10247	Drive / Hydraulics	Single Drive (for payloads under 75,000 lbs)		
10251	Belt / Chain	HTORS Belt		
10259	Belt / Chain	Heavy Duty Chain Crossmembers (.160" Domex 100)	188	
10263	Tailgate / Controls	Lock & Lift Air Tailgate: Electric Cab Controls		
10270	Suspensions	Tri Axle: (1) 23k Intraax AAL Front Lift (Equalized) w/ (2) 23k Intraax AAT Air Ride w/ Liquid Filled Pressure Gauge	2,060	
10275	Suspensions	49" / 50" Spacing		

10280	Axles	Intraax Axle (rating determined by suspension) (per axle)		3
10282	Axles	23k Standard Life Brakes w/ 6" Autoslacks (per axle)		3
10288	Brakes / Air	2S1M / 2S2M Anti-Lock Brake System		
10290	Hub / Drum	Duralite Hub-Piloted - Cast Drum (per axle)		3
15065	Down Axle Wheels (inside)	8.25 x 24.5 10-hole steel disc wheel (per wheel) Accuride ILO Std 8.25 x 22.5 10-hole steel disc wheel	64	4
15067	Down Axle Wheels (outside)	8.25 x 24.5 10-hole polished (XP) aluminum wheel (per wheel) Accuride ILO Std 8.25 x 22.5 10-hole steel disc wheel	(64)	4
15065	Lift Axle Wheels (inside)	8.25 x 24.5 10-hole steel disc wheel (per wheel) Accuride ILO Std 8.25 x 22.5 10-hole steel disc wheel	32	2
15067	Lift Axle Wheels (outside)	8.25 x 24.5 10-hole polished (XP) aluminum wheel (per wheel) Accuride ILO Std 8.25 x 22.5 10-hole steel disc wheel	(32)	2
16733	Down Axle Tires	Continental 11R24.5 HSR2 - 16 Ply (per tire) ILO Std General 11R22.5 HT - 14 Ply	152	8
16733	Lift Axle Tires	Continental 11R24.5 HSR2 - 16 Ply (per tire) ILO Std General 11R22.5 HT - 14 Ply	76	4
10304	Ladder	Ladder Over CS Fender (std location)		
10344	Lights / Electrical	LED Lights - DOT Required w/ Midturn		
10313	Tarps	No Tarp		
10294	Flaps, Mud Guards & Fenders	Aluminum Front Fenders		
10296	Flaps, Mud Guards & Fenders	Aluminum Rear Fenders		
10298	Flaps, Mud Guards & Fenders	Front Fender Mudflaps: Short Front, Long Rear		
10299	Flaps, Mud Guards & Fenders	Interior Mudflaps: None		
10301	Flaps, Mud Guards & Fenders	Rear Mudflaps: Post-Mounted Flip-Up		
10303	Landing Gear	Two-Speed (crank road side)	165	
10308	Spray System	No Spray System		
10311	Document Holder	Document Holder: 4-1/2" Round		
08009	Paint	Epoxy primer		
08024	Paint	Black S7203 with white decals		
08713	Decals	Black Logo and Stripe		

10192-Additional Options

Item #	Category	Description	Weight (lbs)	Qty
10284	Axles	P Spindles (required w/ super single tires) (per axle)		3
10346	Lights / Electrical	Dual Halogen Spotlights (std location)	2	
10347	Lights / Electrical	Dual Strobe Lights (std location)	1	
10285	Axles	Dust Shields (per axle)	18	3
10350	Lights / Electrical	Back-up Alarm - 107 db (std location)		
81997	Hopper - Special	81997 (OLB) Probe Hole: Drill 1/4" Hole on Road Side Through Sheeting and Hopper Sheets at Center of Trailer, 1/4 of the Way Up Wall w/ Red Oval Decal Designating "PROBE HOLE" Concentric Over the Hole		

DISCLAIMER

Specifications are believed to be correct, but may contain errors and/or omissions. Photographs are the representative of the subject equipment but may not be identical. Equipment availability, prices and specifications are subject to change without notice.