HALE TRAILER BRAKE & WHEEL

SALES | RENTALS | PARTS | SERVICE

Allentown, PA:	800-383-8894	Little Rock, AR:	833-424-8944
Baltimore, MD:	888-601-7500	Portland, ME:	800-325-4253
Concord, NC:	800-438-2250	Raleigh, NC	833-418-9777
Delmar, DE:	866-486-1400	Scranton, PA:	800-569-1400
Des Moines, IA:	888-673-5011	Springfield, MA:	800-854-5306
Elkton, MD:	800-544-7127	Voorhees, NJ:	866-315-0235
Jacksonville, FL:	800-828-3055	Walpole, MA:	800-854-5310

haletrailer.com | @haletrailer

800-232-6535 *FINANCING AVAILABLE

FONTAINE HEAVY-HAUL

Resale Inventory
A023589-A023594
VIN: A2277, A2280, A2281, A2278, A2279, A2282

Magnitude 70 Class 653P+2MFLD Tandem Bogie with Pin-on Third Axle (Flat Level Deck) (Model: MAG653P2MFLD)	
	Est. Wt.: 44,073# +/- 3%
Capacity: 65 tons in 16 ft as a 3+2 with gooseneck extension to 184	
Load Base: 16-foot rigid 2-point load centered in deck area	
Framework: All main longitudinal members fabricated with 100,000# minimum yield steel flanges	
Compatibility: Designed to accept Spreader, and 70 in flipbox for 402J Jeep	
Gooseneck Design: Hydraulic removable non-ground bearing design	
Loaded Fifth Wheel Height: 50 inches nominal with 7 ride height positions	
Swing Radius: 114 inches and 102 inches (13 feet 10 inches overall gooseneck length) - NGB	
Flipbox: 70 inch hydraulic flipbox (184 inch swing) Order Number A2278	
Alternate Kingpin: Removable kingpin at 114 inch radius	
Power Source: Set up for wet line operation	
Electrical Receptacle: J560 7-pin connector	
Deck Design: Flat Level Deck (FLD)- 28 feet clear deck length	
Loaded Deck Height: Deck: 24 inches Ground Clearance: 6 in.	
Flooring: 2 inch nominal wood - side rails only	
Front Bogie Ramp: Bolt on	
Extension Brackets: 20 pair - 40 total heavy duty removable hook-on type	
Deck to Bogie Connection: Modular	
Tool Box: 2 Fully covered trays in front of deck between mainbeams with lockable covers.	
Crossmembers: Recess last four crossmembers in deck. Deck Crossmembers on 18 in c/c	
Other Deck Specifications: Siderails to have 3/4 x 5 flanges. Locate air and electrical deck to bogie connections under R.S. Mainbeam Flanges at rear of deck.	
Number of Axles: 5 Total - 2 Trailer , 2 Intermediate Flip, 1 Rear Flip	
Rear Bogie Axle Configuration: 2 axles (tandem) with 3rd Intermediate Flip	
Axle Capacity: 25,000 lb. nominal capacity per axle NOTE: GAWR determined by suspension type, brakes, tires and other components.	
Axle Spread: 60 inches (between axles)	
Bogie to Axle Bottom Pin Connection: Manual Pins	
Flip Axle (Intermediate): 60/90 pin-on intermediate axle w Tire Inflation (unless optional wheels selected) Order Number A2280	
Spreader Bar: EQ2 tandem axle hydraulic spreader system Order Number A2279	
EQ2 Axle Spread: 14 ft 7 in Standard C-Links	
Flip Axle (Intermediate 2): 60/90 pin-on intermediate axle w Tire Inflation(unless optional wheels selected) Order Number A2281	
Flip Axle (Rear): 60/90 pin-on rear axle w Tire Inflation(unless optional wheels selected) Order Number A2282	
Dust Shields: None	
Brakes: 16.5 inches x 7 inches with 5.5 inches autoslacks - heavy duty brake drums - outboard mount	
Suspension: Air ride	
First Axle Lift: Chain Lift	
Tires: 275/70R 22.5 OEM Standard	
Wheels: 8.25 x 22.5 LvL One buffed wheels	

Bolsters: Recessed load bearing between all axles and rear of last axle	
Rear Bogie Height: 43 inches	
Boom Trough: V-style boom trough with bolt-in V pan	
Mechanical Ride Height Control: Mechanical ride height control valve (Whittle Style)	
Manual Dump Valve: Manual Dump Valve (Push Pull)	
Bumper: Heavy duty V-style rear bumper	
Width: 8 feet 6 inches	
Electrical System: DOT sealed beam and harness with LED lights and 4 inch flush mounted battery powered amber strobes	
Paint: Special Customer polyurethane enamel matched to Fontaine paint brand • **International Harvester Red F63RL0202 PN 51130416**	
Lash Rings: 15 pair - 30 total	
Flag Holders: Flag holders - 1 pair located at front of deck and on rear bumper	
Liquid Filled Gauge: Liquid filled air gauge installed	
VIN Plate: Bilingual VIN plate	
Registration/Document Holder: Install registration/document holder	
Additional Options:	
Tire inflation system on trailer and axles	
Front Flip ramps	

Est. Wt.: 44,073# +/-

DISCLAIMER
Specifications are for the equipment at the time it was produced and may not accurately reflect its current condition. Photographs are the representative of the subject equipment but may not be identical. Equipment availability, prices and specifications are subject to change without notice.