

# HALE

## TRAILER

### BRAKE & WHEEL



A023661-A023663  
VIN: 000588-000590

SALES | RENTALS | PARTS | SERVICE

Allentown, PA: 800-383-8894

Little Rock, AR: 833-424-8944

Baltimore, MD: 888-601-7500

Portland, ME: 800-325-4253

Concord, NC: 800-438-2250

Raleigh, NC: 833-418-9777

Delmar, DE: 866-486-1400

Scranton, PA: 800-569-1400

Des Moines, IA: 888-673-5011

Springfield, MA: 800-854-5306

Elkton, MD: 800-544-7127

Voorhees, NJ: 866-315-0235

Jacksonville, FL: 800-828-3055

Walpole, MA: 800-854-5310

haletrailer.com | @haletrailer     

**800-232-6535** \*FINANCING AVAILABLE

Base Weight: 9,000

### 22.5NTT 22.5 Ton Tandem Non Tilt Tags

#### TRAILER

Overall Length 37 ft. 8 in.  
Overall Width 102 in.  
Weight lbs +/- 2% 10435, including options  
A-Frame 6 ft. 11 in. Hi-Tensile Cold Formed Wide Flange Beam  
Hitch 3 in. pintle eye, adjustable 5 position 23 1/2 in. to 32 1/2 in.

#### DECK

Deck Length 24 ft.  
Loaded Deck Height 34 in.  
Main Frame Hi-Tensile Wide Flange 14 in. @ 22  
Cross Members Hi-Tensile 5 in. Channel @ 6.7  
Side Rail Hi-Tensile 7 in. Channel @ 9.8 open on inside  
Floor 1 3/8 in. x 7 in. Keruing Shiplapped  
Landing Gear \*NPO\*: Dual Holland Mark V 2 Speed  
Step \*NPO\*: Bolt on, Located on Front Corner of deck, Driver side and 1 on Passenger side ahead of lead axle

#### SUSPENSION/AXLES

Axles 25,000 lbs Capacity 77.5 in. Track  
Spread 49 in.  
Suspension Heavy Duty spring ride  
Alum Air Tank \*NPO\*: Drain plug with cable  
Brakes Quick Change 12 1/4 in. x 7 in.  
Brake Chamber #3030, All Axles  
Air Brake System 2S/1M  
Air Tank(s) Aluminum  
Bearings Oil Bath  
Slack Adjusters Automatic  
Hubs & Drums 8 Stud Unimount C / W Cast Drums  
Tires 235/75R17.5 16 ply  
Wheels Alum. Wheel Pkg. 17.5 (4 steel, 4 polished)

#### BEAVERTAIL

Length 6 ft. Beavertail, Planked

#### RAMPS

Length \* 38 in. x 76 in. Wood Filled Air Operated Ramp  
Ramp Support \*NPO\*: Ramp Support  
Brackets \*NPO\*: To hold ramp brace when not in use, 1 per side

#### GENERAL SPECIFICATIONS

Electrical System Modular, Vapor Proof GROTE Ultra Blue  
Lights LED CMVSS 108 / FMVSS 108  
Lights \*NPO\*: Amber Flashing Strobe Lights(Mounted in Ramps)  
Lights \*NPO\*: Switch for strobes mounted in toolbox

**GENERAL SPECIFICATIONS**

<b>Front Connector</b>	SAE J560 7 Pin
<b>Finishing</b>	Preparation by Steel Shot Blast, Commercial / Industrial Topcoat, Oven Baked
<b>Color</b>	Black
<b>Mudflaps</b>	1 set of BWS at rear
<b>Toolbox</b>	Full A Frame mounted with solid bottom and cover
<b>Load Securement</b>	11 pair of D-rings: 9 pr on main deck, evenly spaced, 1 pr on top of main beam at headboard, 1 pr on top of A Frame top flange, one on each side of toolbox
<b>Fenders</b>	3/16 in. deck plate

**GVWR Rating is based on standard configuration and a 15% Tongue weight distribution**

**DISCLAIMER**

Specifications are believed to be correct, but may contain errors and/or omissions. Photographs are the representative of the subject equipment but may not be identical. Equipment availability, prices and specifications are subject to change without notice.